

Qualification Results Summary for ADuM5210/ADuM5211/ADuM5212 Die Revision, and Data Sheet Change

QUALIFICATION PLAN / STATUS			
TEST	SPECIFICATION	SAMPLE SIZE	RESULTS
High Temperature Operating Life (HTOL)*	JEDEC <i>JESD22-A108</i>	3x77	Pass
Highly Accelerated Stress Test (HAST)*	JEDEC <i>JESD22-A110</i>	3x77	Pass
Temperature Cycle (TC)*	JEDEC <i>JESD22-A104</i>	3x77	Pass
Autoclave (AC)*	JEDEC <i>JESD22-A102</i>	3x77	Pass
High Temperature Storage Life (HTSL)	JEDEC <i>JESD22-A103</i>	1x77	Pass
Solder Heat Resistance (SHR)*	JEDEC/IPC <i>J-STD-020</i>	1x30	Pass
Latch-Up	JEDEC <i>JESD78</i>	1x9	Pass ±200mA @ +8.25V
Electrostatic Discharge <i>Human Body Model</i>	ESDA/JEDEC <i>JS-001</i>	3/voltage	Pass ±4000V
Electrostatic Discharge <i>Field-Induced Charged Device Model</i>	JEDEC <i>JESD22-C101</i>	3/voltage	Pass ±1250V

*Preconditioned per JEDEC/IPC J-STD-020