

Update Data Sheet Regulatory
Information for Select Isolator
Products with DC-to-DC Converters

ADuM3070 - Isolated Switching Regulator With Integrated Feedback



Change Description	Changed From:	Changed To:
Regulatory Information section updated to correctly align the following ratings to	Clearance: 3.8	Clearance: 3.5
agency issued certifed ratings:		
	IEC / EN / CSA 60950-1-03 &	IEC / EN / CSA 62368-1
Insulation and Safety-Related Specifications section updated to correctly align the	IEC 60950-1	Basic Insulation, 350 V rms
specified Minimum External Air Gap (Clearance) in Table 7 with the agency certified	Basic Insulation, 400V rms	
meaurement.		Datasheet Rev. B
	Datasheet Rev. A	
IEC / EN / CSA 62368-1 Basic and Reinforced Insulation ratings specified in Table 6		



ADuM3470/ADuM3471/ADuM3472/ADuM3473/ADuM3474 - PWM Controller and Transformer Driver with Quad-Channel Isolators

Change Description	Changed From:	Changed To:
Regulatory Information section updated to correctly align the following ratings to agency	IEC / CSA 60950-1	IEC / EN / CSA 62368-1
issued certifed ratings:	Basic insulation, 600 Vrms	Basic insulation, 530 Vrms
IEC / CSA 62368-1 Basic Insulation ratings specified in Table 6	Datasheet Rev. B	Datasheet Rev. C

ADuM5240/ADuM5241/ADuM5242 - Dual-Channel Isolators with iso Power Integrated DC-to-DC Converter, 50 mW



-		
Datasheet Rev. B	Datasheet Rev. C	
	Changed From: Creepage 4.01 Clearance 4.90	Creepage 4.01 Clearance 4.90 Clearance 4.0

ADuM6010 - Integrated DC-to-DC Converter



Changed From:	Changed To:
VDE V 0884-10	VDE 0884-17
V _{IORM} 849 Vpeak	V _{IORM} 600 Vpeak
Datasheet Rev. A	Datasheet Rev. B
	VDE V 0884-10 V _{IORM} 849 Vpeak