


NOTES : Unless Otherwise Specified

1. MATERIAL : FR4 OR EQUIVALENT EPOXY, 2 OZ. COPPER CLAD
THICKNESS .062 +/- .006 TOTAL OF 2 LAYERS.
2. FINISH : ALL PLATED HOLES .001 MIN. / .0015 MAX. COPPER PLATE
ELECTRODEPOSITED TIN-LEAD COMPOSITION
BEFORE REFLOW , SOLDER MASK OVER BARE COPPER (SMOBC).
3. SOLDER MASK : BOTH SIDES USING LPI OR EQUIVALENT.
4. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
6. SCORING:



| SIZE | QTY | SYM | PLTD |
|------|-----|-----|-------|
| 20 | 58 | + | PLTD |
| 94 | 5 | X | PLTD |
| 35 | 16 | □ | PLTD |
| 40 | 12 | ◇ | PLTD |
| 37 | 9 | ⊗ | PLTD |
| 120 | 2 | ⊗ | PLTD |
| 205 | 6 | A | PLTD |
| 125 | 4 | B | PLTD |
| 70 | 2 | D | NPLTD |

FAB DRAWING

| | | | | | |
|------------------|---------|--------------------------|--------------------------------------|----------------------------------------------------------------|--|
| APPROVALS | | LINEAR TECHNOLOGY | | 1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900 | |
| DRAWN | INIT | DATE | | | |
| CHECK | | | | | |
| DESIGN | JUNE WU | 8/15/00 | TITLE: DIFFERENTIAL INPUT 24 BIT ADC | | |
| ENGR | S. WANG | 8/15/00 | | | |
| | | | | | |
| | | | | | |
| SCALE = NONE | | DES | SIZE | REV. | |
| | | | A | A | |
| | | | DC346A | LTC2413CGN | |
| | | | SHT 1 of 1 | | |