


NOTES : Unless Otherwise Specified

1. MATERIAL : FR4 OR EQUIVALENT EPOXY, 2 OZ. COPPER CLAD
THICKNESS .062 +/--.006 TOTAL OF 2 LAYERS
2. FINISH : ALL PLATED HOLES .001 MIN. / .0015 MAX. COPPER PLATE
ELECTRODEPOSITED TIN-LEAD COMPOSITION
BEFORE REFLOW , SOLDER MASK OVER BARE COPPER (SNOBC)
3. SOLDER MASK : BOTH SIDES USING LPI OR EQUIVALENT
4. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK
5. ALL DIMENSIONS ARE IN INCHES
6. SCORING:



FAB DRAWING

REVISIONS		
REV	DESCRIPTION	APPR DATE
A	PROTOTYPE RELEASE	

SIZE	QTY	SYM	PLTD
95	6	+	PLTD
20	1	X	PLTD
15	4	NPLTD	PLTD
72	2	NPLTD	NPLTD

APPROVALS DRAWN CHECK DESIGN ENGR		INIT DATE JUNE WU 8/2/00 TOM G. 8/2/00	TITLE: High Efficiency Monolithic Synchronous Step-Down Regulator SIZE A DEMO DC348A LTC1878EMS8 REV. A
SCALE = NONE DES-230396		SHT 1 of 1	



1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900