


SHOWN FROM COMPONENT SIDE

| REVISIONS | | | |
|-----------|-------------------|------|------|
| REV | DESCRIPTION | APPR | DATE |
| A | PROTOTYPE RELEASE | | |


| SIZE | QTY | SYM | PLTD |
|-------|-----|-----|-------|
| 0.035 | 15 | + | PLTD |
| 0.055 | 10 | × | PLTD |
| 0.125 | 4 | □ | PLTD |
| 0.094 | 5 | ◇ | PLTD |
| 0.015 | 144 | ⊗ | PLTD |
| 0.07 | 2 | ⊗ | NPLTD |

NOTES : Unless Otherwise Specified

1. MATERIAL : FR4 OR EQUIVALENT EPOXY, 2 OZ. COPPER CLAD
THICKNESS .062 +/- .006 TOTAL OF 4 LAYERS.
2. FINISH : ALL PLATED HOLES .001 MIN. / .0015 MAX. COPPER PLATE
ELECTRODEPOSITED TIN-LEAD COMPOSITION
BEFORE REFLOW , SOLDER MASK OVER BARE COPPER (SMOBC).
3. SOLDER MASK : BOTH SIDES USING LPI OR EQUIVALENT.
4. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
5. UNUSED SMD COMPONENTS SHOULD BE FREE OF SOLDER.
6. FILL UP ALL VIAS WITH SOLDER.
7. SCORING:



8. PLEASE LOOK AT THE README FILE FOR THE OTHER REQUIREMENTS.

| APPROVALS | | |  LINEAR TECHNOLOGY 1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900 | |
|--------------|----------|----------|--|------------|
| | INIT | DATE | | |
| DRAWN | | | TITLE: Fabrication Drawing 16-BIT, 250ksps ADC | |
| CHECK | | | | |
| DESIGN | KIM T. | 08-01-02 | | |
| ENGR | DEREK R. | 08-01-02 | | |
| | | | SIZE | REV. |
| | | | A | A |
| | | | DEMO | |
| | | | DC379A-2 * LTC1606CG | |
| SCALE = NONE | | | DES- 0000 | SHT 1 of 1 |