



FABRICATION DWG

SIZE	QTY	SYM	PLTD
70	2	U	NPLTD
125	4	V	PLTD
25	4	W	PLTD
35	3	X	PLTD
15	45	Y	PLTD
95	11	Z	PLTD

- ART01 = LAYER 1 ( COMPONENT SIDE )
- ART02 = LAYER 2 (GND,SIGNAL)
- ART03 = LAYER 3 (GND)
- ART04 = LAYER 4 (SOLDER SIDE)

NOTES : Unless Otherwise Specified

1. MATERIAL : FR4 OR EQUIVALENT EPOXY, 2 OZ. COPPER CLAD  
THICKNESS .062 +/- .006 TOTAL OF 4 LAYERS
2. FINISH : ALL PLATED HOLES .001 MIN. / .0015 MAX. COPPER PLATE  
ELECTRODEPOSITED TIN-LEAD COMPOSITION  
BEFORE REFLOW , SOLDER MASK OVER BARE COPPER (SMOBC)
3. SOLDER MASK : BOTH SIDES USING LPI OR EQUIVALENT
4. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK
5. ALL DIMENSIONS ARE IN INCHES

Fabrication Drawing