fab.pho - Mon Oct 30 09:59:32 2006

REVISIONS			
REV	DESCRIPTION	APPR	DATE

NOTES : Unless Otherwise Specified

1. FAB PER IPC-A-600.
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.
   2 OZ. COPPER FINISHED ON OUTER LAYERS.
   1 OZ. COPPER FINISHED ON INNER LAYERS.
   THICKNESS .062 +/-.006 TOTAL OF 4 LAYERS.
   FLAMABILITY RATING: 94 V-0 MINIMUM .
3. SIZE: DIMENSIONS AND TOLERANCES SHOWN.
   0.00 ARE PRIMARY DATUMS.
4. DRILLLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, .001 INCH THICK MIN. ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.
   HOLE LOCATION TOLERANCES ARE +/-.003 INCH IN RELATION TO CENTER
5. FINISH: SMOBC USING LPI BOTH SIDES COLOR GREEN.
   WHITE TIN IMMERSION (OMIKRON) BOTH SIDES.
6. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
8. SCORING:





SIZE	QTY	SYM	PLTD
95	4	+	PLTD
70	2	×	NPLTD
10	6	□	PLTD
35	3	◇	PLTD

FAB DRAWING

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON ANGLE ±1
2 PLACE ±.01 3 PLACE ±005
INTERPRET DIM AND TOL
PER ASME Y14.5M - 1994

APPROVALS		
	INIT	DATE
DRAWN		
CHECK		
DESIGN	JUNE WU	1/6/05
ENGR	Julian Zhu	1/6/05
SCALE = NONE		

LINEAR TECHNOLOGY
1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900

TITLE: LTC3221EDC, Micropower Regulated Charge Pump DC/DC Converter

SIZE	DEMO	REV.
A	DC862A	A

DES-230 | SHT 1 of 1