



REVISION HISTORY				
ECO	REV	DESCRIPTION	APP. ENG.	DATE
-	3	PRODUCTION	SAM Y.	04-23-13

## LAYER STRUCTURE




## NOTES: UNLESS OTHERWISE SPECIFIED



- FAB PER IPC-A-600.
- MATERIAL: -LEAD FREE ASSEMBLY COMPLIANT, ISOLA FR-370HR OR EQUIVALENT.  
-FINISHED THICKNESS TO BE 0.062 +/- .005  
-TOTAL OF 4 LAYERS WITH 2 OZ. CU ON THE OUTER LAYERS AND 1 OZ. CU ON THE INNER LAYERS.  
-FLAMMABILITY RATING: 94 V-0 MINIMUM.
- SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.  
O/O ARE PRIMARY DATUMS.
- DRILLING: -DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, 0.001 THICK MIN.  
-ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.  
-HOLE LOCATION TOLERANCES ARE +/-0.003 IN RELATION TO CENTER
- FINISH: -SMOBC USING LPI BOTH SIDES, COLOR GREEN.  
-GOLD IMMERSION BOTH SIDES.  
-FOR SILKSCREENS: USE WHITE NON-CONDUCTIVE INK.
- DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.  
PAD SIZE CAN BE MODIFIED TO MEET END FINISH.
- PCBS ARE TO BE RoHS COMPLIANT.
- SCORING FOR PANELIZED PCB:



- DESIGN HAS SOLDER MASK DEFINED PADS ON U1 WITH 0.029 PAD, 0.025 SOLDER MASK, AND 0.024 SOLDER PASTE.  
DO NOT CHANGE ANY SIZE ON THIS COMPONENT.



SIZE	QTY	SYM	PLATED	TOL
0.008	292	□	YES	+/-0.003
0.036	24	⊗	YES	+/-0.003
0.07	2	+	NO	+/-0.003
0.094	16	◇	YES	+/-0.003
0.188	4	×	YES	+/-0.003
0.215	2	⊗	YES	+/-0.003

UNLESS OTHERWISE SPECIFIED		APPROVALS		 <b>LINEAR TECHNOLOGY</b> <div>1630 MCCARTHY BLVD MILPITAS, CA 95035 PH: (408)432-1900 www.linear.com LTC CONFIDENTIAL- FOR CUSTOMER USE ONLY</div>	
DIMENSIONS ARE IN INCHES		PCB DES. LT			
TOLERANCES:		APP ENG. SAM Y.		TITLE: FABRICATION DRAWING	
0.XX = ± 0.01				QUAD 4A STEP-DOWN μMODULE REGULATOR	
0.XXX = ± 0.005					
INTERPRET DIM AND TOL				SIZE IC NO. LTM4644EY	
PER ASME Y14.5M-1994				N/A DEMO CIRCUIT 1900A	
THIRD ANGLE PROJECTION				REV 3	
		SCALE = NONE		FILENAME: DC1900A-3.PCB	
				SHT 1 OF 1	