




REVISION HISTORY				
ECO	REV	DESCRIPTION	APP. ENG.	DATE
-	06	PRODUCTION	MM	08-11-19



NOTES: UNLESS OTHERWISE SPECIFIED

1. WORKMANSHIP SHALL BE IN ACCORDANCE WITH IPC-A-610.
2. ASSEMBLY REFLOW PROFILE SHALL BE IN ACCORDANCE WITH J-STD-020 WITH MAXIMUM SOLDER TEMPERATURE OF 250 DEGREES CELSIUS.
3. PARTS TO OMIT WILL BE SPECIFIED ON THE BILL OF MATERIALS
LOCATIONS OF OMITTED PARTS SHALL BE FREE OF SOLDER.
MASK THE SOLDER STENCIL WHERE SMT PARTS ARE OMITTED.
4. INSTALL SHUNTS AS SHOWN ON ASSY DRAWING.
5. DEPANELIZE BOARDS AFTER ASSEMBLY AND ROUTE-OUT THE BREAKOUT TABS ON FOUR SIDES OF THE BOARD EDGE.
6. APPLY ASSEMBLY STAMP OR QA STAMP TO BOTTOM OF BOARD (UNSHOWY AREA).
7. INSTALL TURRETS, STAND-OFFS AS SHOWN BELOW:
8. APPLY DEMO S/N AT AREA ON BOTTOM SIDE AS SHOWN ON SHEET 2.



APPROVALS		ANALOG DEVICES POWER BY LINEAR™ FOR ADI CUSTOMER USE ONLY		
PCB DES	NC	TITLE: TOP ASSEMBLY DRAWING 5V, 6A SYNCHRONOUS STEP-DOWN SILENT SWITCHER		
APP ENG	MM			
		SIZE	IC NO.	REV.
		N/A	LTC3309 DEMO CIRCUIT 2745A	06
SCALE = NONE		SHT 1 OF 1		



APPROVALS		  FOR ADI CUSTOMER USE ONLY		
PCB DES.	NC	TITLE: BOTTOM ASSEMBLY DRAWING 5V, 6A SYNCHRONOUS STEP-DOWN SILENT SWITCHER		
APP ENG.	MM			
SCALE = NONE		SIZE N/A	IC NO. LTC3309 DEMO CIRCUIT 2745A	REV 06
			SHT 2 of 2	