

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
2A	INITIAL RELEASE	03JUL24	X
B	PER ECR-128443	05NOV25	CCORREA

HOLE TOLERANCE

UNLESS SPECIFIED

PLATED: +/- 3 MILS

NON PLATED: +/- 2 MIL

DRILL CHART: TOP to BOTTOM				
ALL UNITS ARE IN MILS				
FIGURE	FINISHED_SIZE	TOLERANCE_DRILL	PLATED	QTY
+	6.0	+3.0/-3.0	PLATED	18
@	10.0	+3.0/-3.0	PLATED	393
o	45.0	+0.0/-0.0	PLATED	6
Δ	100.0	+3.0/-3.0	PLATED	15
⌈	185.0	+2.0/-2.0	NON-PLATED	4

TOTAL HOLES: 436

PRIMARY SIDE

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			APPROVAL		DATE		<div><div></div><div>ANALOG DEVICES</div></div> <div>TITLE</div> <div>FABRICATION</div> <div>EVAL-LT83402-AZ</div>							
TOLERANCES			TEMPLATE ENGINEER X		ddMMMyy									
DECIMALS FRACTIONS ANGLES .XX -.010 --1/32 -- 2 .XXX -.005 .XXXX -.0050			HARDWARE SERVICES X		ddMMMyy									
			HARDWARE SYSTEMS X		ddMMMyy									
MATERIAL			TEST ENGINEER X		ddMMMyy									
			COMPONENT ENGINEER X		ddMMMyy									
			TEST PROCESS X		ddMMMyy									
			HARDWARE RELEASE X		ddMMMyy									
FINISH			DESIGNER CCORREA		05NOV25		SIZE	FSCM NO	DRAWING NUMBER		REV			
			PTD ENGINEER ELAMP		05NOV25									
			CHECKER X		ddMMMyy									
DO NOT SCALE DWG							SCALE	1 / 1				SHEET	1 OF	2

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
2A	INITIAL RELEASE	03JUL24	X
B	PER ECR-128443	05NOV25	CCORREA

NOTES :UNLESS OTHERWISE SPECIFIED

1. DIMENSIONS ARE IN INCHES (EXCEPT WHERE NOTED).
ALL DOCUMENTS & SPECIFICATIONS REFERRED TO BELOW SHOULD BE THE LATEST REVISIONS.

MATERIAL HOMOGENOUS MATERIALS IN THIS BOARD SHALL BE COMPLAINT WITH THE EU DIRECTIVE 2002/95/EC

2. BOARD MATERIAL:(USE CHECKED ITEMS)
 - (X) ISOLA 370HR OR S1000-2 OR IT180 OR EQUIVALENT
 - () ISOLA-FR408HR OR EQUIVALENT
 - () ISOLA IS410
 - () MEGTRON 6
 - () NELCO-4000-13
 - () ROGERS 4350B
 - () ROGERS 3003
 - () ARLON 85N
 - () EM370D
 - () OTHER _____
3. ALL LAMINATES & BONDING MATERIALS SHOULD BE SELECTED FROM IPC-4101 OR IPC-4103.(TG>170 DEGC TD>300 DEGC)
UL FLAMMABILITY RATING 94V-0. BOARD MATERIAL & CONSTRUCTION SHALL MEET THE REQUIREMENTS OF UL796/UL796F.
4. REFER TO IPC-6010 SERIES, CLASS 2 FOR FABRICATION. WORKMANSHIP SHALL CONFORM TO IPC-A-600, CLASS 2.
5. REFER TO LAMINATION DIAGRAM FOR OVERALL BOARD THICKNESS, TOLERANCE APPLIES AFTER ALL LAMINATION AND PLATING PROCESSES. FINISHED THICKNESS MEASURED FROM TOP COPPER TO BOTTOM COPPER.
6. BOW & TWIST NOT TO EXCEED 0.0075 INCHES (0.75%) PER LINEAR INCH AND SHOULD BE MEASURED PER IPC-TM-650, METHOD 2.4.22.
7. ACCEPTABILITY PER ADI SPECIFICATION TS00115.

TOOLING :

8. IMPEDANCE REQUIREMENTS: IF NO STACKUP IS DEFINED, THE VENDOR IS ALLOWED TO ADJUST THE DIELECTRIC THICKNESS & TRACE WIDTHS TO MEET THE IMPEDANCE REQUIREMENT. IF SPECIFIED, THE VENDOR MUST MEET THE REQUIREMENTS LISTED IN THE IMPEDANCE TABLE. ANY ADJUSTMENT MADE TO THE DEFINED STACKUP, TRACE WIDTH & SPACING THAT IMPACT THE REQUIREMENTS MUST HAVE WRITTEN APPROVAL FROM ADI.
9. FILLET OPTIONS TO ENHANCE RELIABILITY AT PAD JUNCTIONS WHERE SPACING PERMITS.
() FILLETS ALLOWED
(X) FILLETS NOT ALLOWED
10. THIEVING:
() VENDOR MAY ADD THIEVING TO COMPENSATE FOR LOW COPPER DENSITY AREAS MAINTAINING A MINIMUM 0.100 INCH CLEARANCE FROM ALL COPPER FEATURES.
(X) VENDOR MAY NOT ADD THIEVING TO COMPENSATE FOR LOW COPPER DENSITY AREAS.
11. LAYER TO LAYER REGISTRATION SHALL BE WITHIN 0.003 INCHES.

FINISH:

12. DRILL SIZES ARE FINISHED HOLE SIZES. ALL HOLES SHALL BE LOCATED WITHIN 0.005 INCHES DTP, UNLESS SPECIFIED.
MINIMUM BARREL PLATING OF 0.001 INCHES. PLATED HOLES SHALL NOT BE ROUGH OR IRREGULAR SO AS TO
HINDER PROPER SOLDER WICKING. BARREL RELIEF ON SOLDERMASK ALLOWED IN UNFILLED VIA IN PAD HOLES.
13. PLATING SPECIFICATION:
(X) REFER TO LAMINATION DIAGRAM FOR FINISHED COPPER WEIGHT/THICKNESS REQUIREMENTS
THE STARTING COPPER WEIGHT/THICKNESS CAN VARY AS LONG AS THE FINISHED COPPER
WEIGHT/THICKNESS IS NOT LESS THAN THE SPECIFIED VALUE.
14. SURFACE FINISH:
(X) IMMERSION GOLD (ENIG) 1.58-3.94 MICRO INCHES OVER 118-236 MICRO INCHES MIN. OF ELECTROLESS NICKEL PER IPC-4552
() OSP (ORGANIC SOLDERABILITY PRESERVATIVE)
() IMMERSION SILVER
() SOFT WIRE BONDABLE GOLD 30-50 MICRO INCHES OF SOFT WIRE
BONDABLE GOLD OVER 100-150 MICRO INCHES OF NICKEL
() EDGE CONNECTOR FINGERS ARE TO BE PLATED WITH 100 MICRO-INCHES(.0001") OF LOW STRESS
NICKEL UNDER 30 MICRO-INCHES (.0003") OF GOLD
() OTHER_____
15. SOLDERMASK:
SOLDERMASK OVER BARE COPPER OR BARE GOLD (BOTH SIDES) TO MEET IPC-SM-840.
IF PRESENT, DO NOT MODIFY SOLDERMASK DEFINED PADS (MASK OPENINGS LESS THAN COPPER PAD) WITHOUT APPROVAL.
(X) LPI
() OTHER_____
- COLOR
(X) GREEN
() OTHER_____
16. APPLY SILKSCREEN TO BOTH SIDES USING A NON-CONDUCTIVE, EPOXY BASED INK PER ARTWORK.
(X) WHITE
() OTHER

TESTING:

17. FINAL ELECTRICAL TEST TO BE PERFORMED USING PROVIDED IPC-D-356A NETLIST OR ODB++ FORMAT FILE.
THE PCB SHALL HAVE A VERIFICATION STAMP.
18. A TIME DOMAIN REFLECTOMETER REPORT (TDR) FOR EACH IMPEDANCE CONTROLLED LAYER & A CERTIFICATE OF COMPLIANCE SHALL BE PROVIDED BY VENDOR AT TIME OF SHIPMENT. INSTANCES WHERE TDR TESTING CAN'T BE PERFORMED BECAUSE THE TRACE LENGTH IS TOO SHORT ON THE OUTER LAYERS AT THE PIN ESCAPES IS ACCEPTABLE, ALL OTHER INSTANCES MUST BE REPORTED.

MISCELLANEOUS :

19. IF PRESENT, ALL BLIND/BURIED VIAS WITH AN ASPECT RATIO $<1:1$ TO BE PLATED SHUT WITH COPPER WHEN USED AS VIA-IN-PAD OR AS A STACKED VIA. BLIND/BURIED VIAS WITH AN ASPECT RATIO $>1:1$ TO BE FILLED WITH NON-CONDUCTIVE EPOXY.
20. FOR VIA FILL INFORMATION REFER TO DRILL CHART:
 - (X) NON-CONDUCTIVE EPOXY FILL ALL LESS THAN 0.012 INCHES DRILLED VIAS
 - () COPPER FILL ALL 0.012 INCHES DRILLED VIAS
21. INTENTIONAL SHORTS:
 - IF AN INTENTIONAL SHORT REPORT IS SUPPLIED AND DOES NOT MATCH THE FAB DATA THEN ADI APPROVAL IS REQUIRED.
22. PEMNUTS:
 - () PEMNUTS TO BE INSTALLED BY FABRICATOR
 - () PEMNUTS NOT TO BE INSTALLED BY FABRICATOR
 - (X) NOT APPLICABLE
23. MANUFACTURER TO ETCH/STAMP WITH PERMANENT NON-CONDUCTIVE INK ON SECONDARY SIDE UNLESS OTHERWISE SPECIFIED:
 - A. UL CODE-FLAMMABILITY RATING FOR THOSE APPROVED MATERIALS(IF APPLICABLE)
 - B. DATE CODE
 - C. LOT NUMBER
 - D. MANUFACTURER LOGO
25. PANELIZATION:
 - BOARDS TO BE SHIPPED IN ARRAY AND KEPT INTACT
 - PANEL TO BE SUBJECTED TO CUSTOMERS APPROVAL
 - PANEL SOLDER PASTE STENCIL GERBER TO BE PROVIDED TO ANALOG
27. MINIMUM DESIGN LINE WIDTH IS .010 INCH.
28. MINIMUM DESIGN LINE SPACING IS .006 INCH.


FAB NOTES REVISION: 2ND NOVEMBER 2022

LAMINATION DIAGRAM				
LAYER NUMBER	LAYER NAME	COPPER THICKNESS (OZ, INCH)	DIELECTRIC THICKNESS (INCH)	MATERIALS

1	TOP	2 OZ, 0.0028"		FINAL CU (THICKNESS AFTER PLATING)
			0.006"	ISOLA 370HR/EQUIVALENT
2	LAYER_2	2 OZ, 0.0028"		CU CLAD
				ISOLA 370HR/EQUIVALENT
3	LAYER_3	2 OZ, 0.0028"		CU CLAD
			0.006"	ISOLA 370HR/EQUIVALENT
4	BOTTOM	2 OZ, 0.0028"		FINAL CU (THICKNESS AFTER PLATING)

THE FINISHED PCB THICKNESS TO BE: 0.062" +/-10%

PRIMARY SIDE

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			APPROVAL		DATE		<div>ANALOG DEVICES</div>			
TOLERANCES			TEMPLATE ENGINEER X		d d M M M y y					
DECIMALS FRACTIONS ANGLES .XX -.010 +-1/32 +- 2 .XXX -.005 .XXXX -.0050			HARDWARE SERVICES X		d d M M M y y		TITLE FABRICATION EVAL - LT83402 - AZ			
MATERIAL			HARDWARE SYSTEMS X		d d M M M y y					
			TEST ENGINEER X		d d M M M y y					
			COMPONENT ENGINEER X		d d M M M y y					
			TEST PROCESS X		d d M M M y y					
			HARDWARE RELEASE X		d d M M M y y					
FINISH			DESIGNER CCORREA		05NOV25		SIZE	FSCM NO	DRAWING NUMBER	REV
			PTD ENGINEER ELAMP		05NOV25		C	24355	09 - 081769	B
			CHECKER X		d d M M M y y					
DO NOT SCALE DWG						SCALE 1 / 1			SHEET 2 OF 2	