

D

C

B

A

D

C

B

A

| 8                                     | 7  | 6             | 5   | 4 | 3  | 2 | 1  |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
|---------------------------------------|--|---------------|---|---|--|---|--|---------------------------------------|--|--|---|-----|--|----------|------------------|--|---------------|-----------|--|--|--------------|--|------------------|--|---------|--|--|-------------|--|-------|--|-----------|--|--|-----------|--|-------|--|--|--|--|-----------|--|-------|--|
|                                       |  |               |   |   |  |   | <table><tr><th colspan="4">REVISIONS</th></tr><tr><th>REV</th><th>DESCRIPTION</th><th>APPROVED</th><th>DATE</th></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr></table>   | REVISIONS                             |  |  |   | REV | DESCRIPTION  | APPROVED | DATE             |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
| REVISIONS                             |  |               |   |   |  |   |  |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
| REV                                   | DESCRIPTION                              | APPROVED      | DATE  |   |  |   |  |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
|                                       |  |               |   |   |  |   |  |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
|                                       |  |               |   |   |  |   |  |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
|                                       |  |               |   |   |  |   |  |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
|                                       |  |               |   |   |  |   | <p>NOTES:</p> <p>UNLESS OTHERWISE SPECIFIED:</p> <p>1. DIMENSIONS ARE IN INCHES (EXCEPT WHERE NOTED).</p> <p>MATERIAL: (USE CHECKED ITEMS FOR MATERIAL)</p> <p>2. BOARD MATERIAL:</p> <p>(X) ISOLA 370HR OR EQUIVALENT</p> <p>( ) ISOLA-FR408HR OR EQUIVALENT</p> <p>( ) NELCO-4000-13</p> <p>( ) MEGTRON 6</p> <p>( ) ROGERS 4350B</p> <p>( ) ROGERS 4003C</p> <p>( ) OTHER -----</p> <p>3. THE PCB SHALL BE FABRICATED TO IPC-6012, TYPE X, CLASS 2.</p> <p>WORKMANSHIP SHALL CONFORM TO IPC-A-600, CLASS 2, CURRENT REVISIONS.</p> <p>4. BOARD MATERIAL &amp; CONSTRUCTION SHALL MEET THE REQUIREMENTS OF UL796 WITH FLAMMABILITY RATING OF 94V-0.</p> <p>5. OVERALL BOARD THICKNESS REFER TO LAMINATION DIAGRAM. TOLERANCE APPLIES AFTER ALL LAMINATION AND PLATING PROCESSES. IT IS TO BE MEASURED FROM TOP PCB METAL TO BOTTOM PCB METAL UNLESS OTHERWISE SPECIFIED.</p> <p>6. BOW &amp; TWIST NOT TO EXCEED 0.0075 IN. (0.75%) PER LINEAR INCH. BOW &amp; TWIST SHOULD BE MEASURED PER IPC-TM-650, METHOD 2.4.22.</p> <p>TOOLING: (USE CHECKED ITEMS FOR TOOLING)</p> <p>7. PHOTO ETCH CIRCUITRY PER ENCLOSED GERBER R5274X OR ODB++ FORMAT FILE. DRILL LOCATION AND SIZE CONTROLLED BY EXCELLON CNC DRILL FILE.</p> <p>8. IF STATED IN THE LAMINATION DIAGRAM, THE DIELECTRIC THICKNESS OF ANY CONTROLLED IMPEDANCE LAYER IS FOR REFERENCE ONLY. FINAL ACCEPTANCE SHALL BE DETERMINED BY THESE LAYERS HAVING A CHARACTERISTIC IMPEDANCE OF +/-10% OHMS AS STATED IN THE LAMINATION DIAGRAM. THE VENDOR CAN MAKE ADJUSTMENTS AS LONG AS THE STATED IMPEDANCE AND OVERALL BOARD THICKNESS IS MAINTAINED. ANY ADJUSTMENT MADE TO TRACE WIDTH OR SPACING MUST HAVE PRIOR WRITTEN APPROVAL FROM MAXIM.</p> <p>9. ALL TRACES FILLETED OPTION TO ENHANCE RELIABILITY AT PAD JUNCTIONS WHERE SPACING PERMITS. UNLESS OTHERWISE SPECIFIED:</p> <p>( ) FILLETED</p> <p>(X) NOT FILLETED</p> <p>10. LAYER TO LAYER REGISTRATIONS SHALL BE WITHIN .003 INCHES. LEGEND TO LEGEND +/- 0.007 INCHES.</p> <p>FINISH: (USE CHECKED ITEMS FOR PLATING)</p> <p>11. FINISHED COPPER WEIGHT/THICKNESS:</p> <p>(X) REFER TO LAMINATION DIAGRAM FOR FINISHED COPPER WEIGHT/THICKNESS REQUIREMENTS. THE STARTING COPPER WEIGHT/THICKNESS CAN VARY AS LONG AS THE FINISHED COPPER WEIGHT/THICKNESS IS NOT LESS THAN THE SPECIFIED VALUE. UNLESS OTHERWISE SPECIFIED.</p> <p>( ) OTHER -----</p> <p>12. CHECK ALL THAT APPLY</p> <p>(X) FINISH CONDUCTOR SURFACES: IMMERSION GOLD, 3-8 MICRO INCHES OVER 100 MICRO INCHES MINIMUM OF ELECTROLESS NICKEL.</p> <p>( ) LEAD FREE AND RH6S COMPLIANT OR EQUIVALENT LEAD FREE PLATING</p> <p>( ) ELECTRODEPOSITED HARD GOLD PLATE, TYPE 1 (99.7% MIN GOLD), GRADE C (KNOPF HARDNESS 130-200), CLASS 1 (50-100 MICRO INCHES THICK) IN ACCORDANCE WITH MIL-G-45204C. GENERAL SURFACING REQUIREMENTS MUST MEET ANSI/IPC-A-600(CURRENT REV) SECTION 4.0, CLASS 3 (50-100 MICROINCHES THICK) OVER ELECTRODEPOSITED NICKEL PLATE IN ACCORDANCE WITH ANSI/IPC-A-600B, SECTION 4.0, CLASS 3 (200-600 MICROINCHES THICK).</p> <p>( ) FINISH CONDUCTOR SURFACES: IMMERSION GOLD, 2-5 MICRO INCHES OVER 118-236 MICRO INCHES MINIMUM OF ELECTROLESS NICKEL.</p> <p>( ) FINGERS TO BE GOLD PLATED.</p> <p>( ) OTHER -----</p> <p>13. DRILL SIZES ARE FINISHED HOLE SIZES. ALL HOLES SHALL BE LOCATED WITHIN .005 DTP. MINIMUM BARREL PLATING OF .001 IN. PLATED HOLES SHALL NOT BE ROUGH OR IRREGULAR SO AS TO HINDER PROPER SOLDER WICKING.</p> <p>14. CHECK ALL THAT APPLY</p> <p>(X) GREEN SOLDERMASK OVER BARE COPPER/BARE GOLD (BOTH SIDES) WITH LIQUID PHOTO IMAGEABLE INK (LPI) PER ARTWORK.</p> <p>( ) GREEN TAIYO PSR-4000</p> <p>( ) OTHER -----</p> <p>15. CHECK ALL THAT APPLY</p> <p>(X) APPLY SILKSCREEN USING A NON-CONDUCTIVE, WHITE EPOXY BASED INK PER ARTWORK.</p> <p>( ) OTHER -----</p> <p>16. VENDOR LOGO &amp; DATE CODE REQUIRED IN INK ON BOTTOM SIDE ONLY. DATE CODE FORMAT MUST BE YYMM ONLY</p> <p>TESTING:</p> <p>17. FINAL ELECTRICAL TEST TO BE PERFORMED USING PROVIDED IPC-D-356A NETLIST OR ODB++ FORMAT FILE. (REQUIRED UNLESS OTHERWISE SPECIFIED IN QUOTE)</p> <p>THE PCB SHALL HAVE A VERIFICATION STAMP.</p> <p>18. A TIME DOMAIN REFLECTOMETER REPORT FOR EACH IMPEDANCE CONTROLLED LAYER AND A CERTIFICATE OF COMPLIANCE SHALL BE PROVIDED BY VENDOR AT TIME OF SHIPMENT.</p> <p>MISCELLANEOUS:</p> <p>19. IF PRESENT, ALL BLIND/BURIED VIAS WITH AN ASPECT RATIO &lt;1:1 TO BE PLATED SHUT WITH COPPER WHEN USED AS VIA-IN-PAD OR AS A STACKED VIA. BLIND/BURIED VIAS WITH AN ASPECT RATIO &gt;1:1 TO BE FILLED WITH NON-CONDUCTIVE EPOXY, UNLESS OTHERWISE SPECIFIED.</p> <p>20. FOR ALL DRILL INFORMATION REFER TO DRILL CHART.</p> <p>( ) NON-CONDUCTIVE EPOXY FILL ALL 0.XXXX INCHES DRILLED VIAS.</p> <p>( ) SILVER FILL ALL 0.XXXX INCHES DRILLED VIAS.</p> <p>21. FINISHED SURFACE CONTACTS AND FILLED VIAS TO BE FREE OF ANY PITS, SCRATCHES, PROBE MARKS OR OTHER DEFORMITIES THAT COULD EFFECT THE APPEARANCE AND PERFORMANCE OF THE CONTACT SURFACE. CONTACTS ARE TO BE AS FLAT AS POSSIBLE. NOT TO EXCEED +/- 0.001" OF FLATNESS.</p> <p>22. THIEVING:</p> <p>( ) SUPPLIER MAY ADD THIEVING TO COMPENSATE FOR LOW COPPER DENSITY AREAS ON THIS DESIGN.</p> <p>(X) SUPPLIER MAY NOT ADD THIEVING TO COMPENSATE FOR LOW COPPER DENSITY AREAS ON THIS DESIGN.</p> <p>23. PENNUT:</p> <p>( ) PENNUTS TO BE INSTALLED BY SUPPLIER.</p> <p>( ) PENNUTS NOT TO BE INSTALLED BY SUPPLIER.</p> <p>(X) NOT APPLICABLE</p> |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
|                                       |  |               |   |   |  |   | <table><tr><td colspan="3">TOLERANCES UNLESS OTHERWISE SPECIFIED</td><td colspan="2" rowspan="2">THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO MAXIM. THE INFORMATION IN THIS DOCUMENT IS NOT TO BE SHOWN, REPRODUCED, OR DISCLOSED TO ANYONE OUTSIDE OF MAXIM WITHOUT PRIOR WRITTEN PERMISSION FROM MAXIM.</td><td colspan="2" rowspan="2"><div><div></div><div>maxim integrated™</div></div></td></tr><tr><td>FRACTIONS<br/>+/-</td><td>DECIMALS<br/>.XX +/- .01<br/>.XXX +/- .005</td><td>ANGLES<br/>+/-</td></tr><tr><td colspan="3">MATERIAL:</td><td colspan="2">DRAWN BY: ST</td><td colspan="2">DATE: 04/04/2017</td></tr><tr><td colspan="3">FINISH:</td><td colspan="2">CHECKED BY:</td><td colspan="2">DATE:</td></tr><tr><td colspan="3">SEE NOTES</td><td colspan="2">APPR. BY:</td><td colspan="2">DATE:</td></tr><tr><td colspan="3"></td><td colspan="2">APPR. BY:</td><td colspan="2">DATE:</td></tr></table>  | TOLERANCES UNLESS OTHERWISE SPECIFIED |  |  | THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO MAXIM. THE INFORMATION IN THIS DOCUMENT IS NOT TO BE SHOWN, REPRODUCED, OR DISCLOSED TO ANYONE OUTSIDE OF MAXIM WITHOUT PRIOR WRITTEN PERMISSION FROM MAXIM. |     | <div><div></div><div>maxim integrated™</div></div> |          | FRACTIONS<br>+/- | DECIMALS<br>.XX +/- .01<br>.XXX +/- .005 | ANGLES<br>+/- | MATERIAL: |  |  | DRAWN BY: ST |  | DATE: 04/04/2017 |  | FINISH: |  |  | CHECKED BY: |  | DATE: |  | SEE NOTES |  |  | APPR. BY: |  | DATE: |  |  |  |  | APPR. BY: |  | DATE: |  |
| TOLERANCES UNLESS OTHERWISE SPECIFIED |  |               | THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO MAXIM. THE INFORMATION IN THIS DOCUMENT IS NOT TO BE SHOWN, REPRODUCED, OR DISCLOSED TO ANYONE OUTSIDE OF MAXIM WITHOUT PRIOR WRITTEN PERMISSION FROM MAXIM. |   | <div><div></div><div>maxim integrated™</div></div> |   |  |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
| FRACTIONS<br>+/-                      | DECIMALS<br>.XX +/- .01<br>.XXX +/- .005 | ANGLES<br>+/- |   |   |  |   |  |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
| MATERIAL:                             |  |               | DRAWN BY: ST  |   | DATE: 04/04/2017                                   |   |  |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
| FINISH:                               |  |               | CHECKED BY:   |   | DATE:  |   |  |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
| SEE NOTES                             |  |               | APPR. BY:   |   | DATE:  |   |  |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
|                                       |  |               | APPR. BY:   |   | DATE:  |   |  |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |
| 8                                     | 7  | 6             | 5   | 4 | 3  | 2 | 1  |                                       |  |  |   |     |  |          |                  |  |               |           |  |  |              |  |                  |  |         |  |  |             |  |       |  |           |  |  |           |  |       |  |  |  |  |           |  |       |  |

maxim integrated.

MAXIM INTEGRATED

1400 N. MOORE AVENUE, SUITE 100

IRVING, TEXAS 76039-1400

TEL: 972.462.0000 FAX: 972.462.0001

WWW.MAXIM-INT.COM


HARDWARE NAME: MAX14877\_EVKIT\_A

HARDWARE NUMBER:

ENGINEER: DESIGNER: ST

DATE: 04/04/2017

USER-DEFINED FILE NOTES



| LAMINATION DIAGRAM                                 |            |                             |                            |                        |
|--|------------|-----------------------------|----------------------------|------------------------|
| LAYER NUMBER                                       | LAYER NAME | COPPER THICKNESS (oz./inch) | DIELECTRIC THICKNESS (in.) | DIELECTRIC MATERIAL    |
| 1  | TOP        | 1 OZ. 0.0014" MIN           |                            | FOIL                   |
|  |            |                             | TBD                        | ISOLA 370HR/EQUIVALENT |
| 2  | BOTTOM     | 1 OZ. 0.0014" MIN           |                            | FOIL                   |
| THE FINISHED PCB THICKNESS TO BE: 0.062" +/-0.010" |            |                             |                            |                        |

|                                       |  |               |   |  |  |  |
|---------------------------------------|--|---------------|---|--|--|--|
| TOLERANCES UNLESS OTHERWISE SPECIFIED |  |               | THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO MAXIM. THE INFORMATION IN THIS DOCUMENT IS NOT TO BE SHOWN, REPRODUCED, OR DISCLOSED TO ANYONE OUTSIDE OF MAXIM WITHOUT PRIOR WRITTEN PERMISSION FROM MAXIM. |  | <div><div></div><div>maxim integrated™</div></div> |  |
| FRACTIONS<br>+/-                      | DECIMALS<br>.XX +/- .01<br>.XXX +/- .005 | ANGLES<br>+/- |   |  |  |  |
| MATERIAL:                             |  |               | DRAWN BY: ST  |  | DATE: 04/04/2017                                   |  |
| FINISH:                               |  |               | CHECKED BY:   |  | DATE:  |  |
| SEE NOTES                             |  |               | APPR. BY:   |  | DATE:  |  |
|                                       |  |               | APPR. BY:   |  | DATE:  |  |
|                                       |  |               | APPR. BY:   |  | DATE:  |  |

|                  |  |                  |              |
|------------------|--|------------------|--------------|
| HARDWARE NAME:   |  | MAX14877_EVKIT_A |              |
| HARDWARE NUMBER: |  | XX-XXXXX-XXX     |              |
| NOT TO SCALE     |  | TEMPLATE REV:    | SHEET 1 OF 1 |