



Product/Process Change Notice - PCN 12_0279 Rev. -

Analog Devices, Inc. Three Technology Way Norwood, Massachusetts 02062-9106

This notice is to inform you of a change that will be made to certain ADI products (see Material Report). Any issues with this PCN or requirements to qualify the change (additional data or samples) must be sent to ADI within 30 days of publication date. ADI contact information is listed below.

PCN Title: ADUM3210 Datasheet Specification Change

Publication Date: 01-Nov-2012

Effectivity Date: 30-Jan-2013 *(the earliest date that a customer could expect to receive changed material)*

Revision Description:

Initial Release

Description Of Change

The minimum operating voltage of the ADUM3210 A and B grades is being changed from 2.7V to 3.0V.

Reason For Change

The datasheet is being updated to accurately reflect the ADUM3210 device capabilities.

Impact of the change (positive or negative) on fit, form, function & reliability

This specification change will not have any impact on the quality or reliability of the ADUM3210.

Summary of Supporting Information

This change to the minimum operating voltage of the A and B grades is reflected in Rev G of the ADUM3210 datasheet.

Supporting Documents None

For questions on this PCN, send email to the regional contacts below or contact your local ADI sales representative

Americas: PCN_Americas@analog.com

Europe: PCN_Europe@analog.com

Japan: PCN_Japan@analog.com

Rest of Asia: PCN_ROA@analog.com

Appendix A - Affected ADI Models

Added Parts On This Revision - Product Family / Model Number (4)

ADUM3210 / ADUM3210ARZ	ADUM3210 / ADUM3210ARZ-RL7	ADUM3210 / ADUM3210BRZ	ADUM3210 / ADUM3210BRZ-RL7	
------------------------	----------------------------	------------------------	----------------------------	--

Appendix B - Revision History

Rev	Publish Date	Effectivity Date	Rev Description
Rev. -	01-Nov-2012	30-Jan-2013	Initial Release

Analog Devices, Inc.

DocId:2162 Parent DocId:None Layout Rev:7