



Product/Process Change Notice - PCN 14_0048 Rev. -

Analog Devices, Inc. Three Technology Way Norwood, Massachusetts 02062-9106

This notice is to inform you of a change that will be made to certain ADI products (see Material Report). Any issues with this PCN or requirements to qualify the change (additional data or samples) must be sent to ADI within 30 days of publication date. ADI contact information is listed below.

PCN Title: ADuM1200UR-EP Datasheet Changes
Publication Date: 21-Feb-2014
Effectivity Date: 21-Feb-2014 *(the earliest date that a customer could expect to receive changed material)*

Revision Description:

Initial Release

Description Of Change

Two changes to the ADuM1200UR-EP data sheet specifications are being made:
The maximum operating temperature is being increased from +105 C to +125 C.
The minimum operating voltage is being changed from 2.7V to 3.0V.

Reason For Change

The datasheet is being updated to accurately reflect the ADuM1200UR-EP device capabilities at higher operating temperatures.

Impact of the change (positive or negative) on fit, form, function & reliability

The changes will not have any impact on the quality or reliability of the ADuM1200UR-EP.

Summary of Supporting Information

These changes to the maximum operating temperature and minimum operating voltage will be reflected in Rev B of the ADuM1200UR-EP datasheet.

Supporting Documents None

For questions on this PCN, send email to the regional contacts below or contact your local ADI sales representative

Americas: PCN_Americas@analog.com

Europe: PCN_Europe@analog.com

Japan: PCN_Japan@analog.com

Rest of Asia: PCN_ROA@analog.com

Appendix A - Affected ADI Models

Added Parts On This Revision - Product Family / Model Number (2)

ADUM1200 / ADuM1200UR-EP

ADUM1200 / ADuM1200UR-EP-RL7

Appendix B - Revision History

Rev	Publish Date	Effectivity Date	Rev Description
Rev. -	21-Feb-2014	21-Feb-2014	Initial Release

Analog Devices, Inc.

DocId:2772 Parent DocId:None Layout Rev:7