



Technical notes on using Analog Devices products and development tools  
 Visit our Web resources <http://www.analog.com/ee-notes> and <http://www.analog.com/processors> or  
 e-mail [processor.support@analog.com](mailto:processor.support@analog.com) or [processor.tools.support@analog.com](mailto:processor.tools.support@analog.com) for technical support.

## ADSP-2159x/SC596 SHARC+® Processor Board Design Guidelines for Dynamic Memory Controller

Contributed by Deepak SH, Nishant Singh

Rev 1 – April 14, 2022

### Introduction

This EE-note provides recommended board design practices for interfacing DDR memory and achieving expected performance from the controller. These guidelines should be used in addition to standard board-level design practices.

### Placement and General Routing Guidelines

Use the following guidelines when designing PCB stack up, trace routing and component placement:

- Place the ADSP-2159x/SC59x SHARC+® Processor and the memory as close as possible to each other while minimizing routing length
- The ADSP-2159x/SC59x SHARC+® Processor DMC interface supports only point-to-point design and does not support fly-by topology
- Plan the PCB stack-up such that all the DMC signals (address, command, and control) have continuous reference planes (ground planes) on an immediately adjacent layer. Ensure that these signals do not travel across splits in the power/ground planes. It is better to increase the distance between the signal and its relevant planes than to implement the “cross split” routing
- For better signal integrity, avoid power-plane-to-signal-plane and power-plane-to-power-plane coupling. Strive to minimize

this coupling

- The PCB trace characteristic impedance must be 50  $\Omega$  for single-ended signals and 100  $\Omega$  for differential signals, with a 5% tolerance
- Route all DDR signals as a group in every layer to avoid a mismatch in trace impedance and propagation delay. Keep all grouped signals on the same layer. For example, the signals named DMC\_DQ00-07, DMC\_LDQS, and DMC\_LDQM, should be routed as a group, in the same layer and having the same ground reference. Changing the ground reference plane can change the trace impedance
- To avoid crosstalk, ensure that all DDR signals have center-to-center spacing of at least 3W between DDR signals and 4W to other signals, where W is the trace width
- Maintain perpendicularity between DMC signals routing, for different DMC signals routed in adjacent layers. This configuration reduces crosstalk, as signals on adjacent layers will not be parallel to each other
- Avoid test points on the DDR signals, as they create stubs which can act as EMI sources. Instead, use vias for probing. It is also acceptable to use JEDEC recommended methods that test vendors offer for diagnostics



To simplify routing, entire byte lanes can be swapped, but it should be ensured that all DQ, DQS, DM signals are substituted with each other (For example, DQ (7-0)  $\leftrightarrow$  DQ (15-8), DMC\_LDQS  $\leftrightarrow$  DMC\_UDQS, /DMC\_LDQS  $\leftrightarrow$  /DMC\_UDQS, DMC\_UDM  $\leftrightarrow$  DMC\_LDM).

Within a byte lane, data bits can be swapped, except for the lowest order bit (for example, DQ0 should be connected to DQ0 of the processor if lane swapping is not done). Swapping of address lines is not allowed.

## Trace Length-Matching Criteria

The routing of all the DDR interface signals must be length-matched to avoid ‘Setup’ and ‘Hold time’ violations due to propagation delay.

The length-matching criteria are as follows:

- Match the trace length of all address (DMC\_A [nn], DMC\_BA[n]) and command (DMC\_CKE, DMC\_CS[n], DMC\_ODT, DMC\_RAS, DMC\_RESET, DMC\_WE) signals within +/- 40 mils relative to the DMC\_CK signal
- Match the trace length of all data (DMC\_DQ [nn]) and data mask (DMC\_UDM, DMC\_LDM) signals within +/- 40 mils relative to their corresponding DQS signal. For example, match the trace length of the lower order data byte (DMC\_DQ00 - DMC\_DQ07) and the corresponding data mask (DMC\_LDM) signals with the lower order strobe (DMC\_LDQS) signal
- Match the trace length of differential signals such as clock (DMC\_CK and /DMC\_CK) and DQS pairs (DMC\_LDQS and /DMC\_LDQS, DMC\_UDQS and /DMC\_UDQS) within +/- 10 mils. For example, match the trace length of the DMC\_CK and /DMC\_CK signals within


+/- 10 mils relative to each other

- The maximum allowed trace length for DDR signals is 2 inches

## VTT Termination


Use the following guidelines for VTT termination. These guidelines can differ from vendor to vendor.

- For DDR3/3L, VTT termination is recommended by JEDEC, as this mitigates signal reflection. The primary purpose of a VTT island is to prevent reflections at the memory device. Removing the VTT termination results in signal reflections. The removal can lead to higher than nominal voltages at the memory address or command input pins, which can damage or reduce the lifetime of the memory. Check with the appropriate memory vendor for device-specific information
- Implement VTT termination for the address and command lines as shown in *Figure 1 VTT Termination for Address and Command Line*, taken from *EV-21593 SOM@ Schematic, Rev A, April 2020. Analog Devices, Inc.*



*Figure 1 VTT Termination for Address and Command Line*

The DMC\_CK and /DMC\_CK signals must be terminated using a differential termination scheme as shown in [Figure 2](#) DMC clock differential termination



*Figure 2 DMC clock differential termination*

- VTT termination does not play a major role for the ADSP-2159x/SC59x SHARC+® Processor. It is mainly a requirement from the memory device. Any alternative that prevents reflections on the address or command bus is an acceptable substitute for VTT termination at the processor
- Separate VTT and VREF islands by a minimum of 150 mils if placed on the same PCB layer. Placing the islands on different layers is preferred
- Place VTT islands as close as possible to the memory device
- VTT islands require at least two additional decoupling capacitors (4.7µF) and two bulk capacitors (100µF) at each end as shown in [Figure 3](#) VTT Supply and Decoupling Scheme
- VTT island surface trace must have a minimum width of 150 mil minimum. A width of 250 mil is preferred
- Perform a decoupling analysis of the VTT planes

## DMC Power (VDD\_DMC) Decoupling

Use the following guidelines for DMC power decoupling:

- The DMC interface should have enough decoupling on the VDD\_DMC rail and the memory power rail to avoid data

corruption.

- Refer to the DDR memory data sheet or consult the DDR memory vendor to identify the decoupling capacitor requirement for the DDR memory power rails
- A critical parameter is Idd7, which defines the peak current during multi-bank operations and depends on the speed grade and ambient temperature of the DDR memory
- Place all the decoupling capacitors very close to the VDD\_DMC power rail and use solid power and ground planes
- Ensure that the power and ground planes are adjacent to each other to provide the shortest return path and better power integrity
- Isolate the DDR power planes from other supply planes. If this is not possible, separate them as much as possible and avoid overlapping them
- Place individual power and ground vias from every power and ground pin of the ADSP-2159x/SC59x SHARC+® Processor and the memory device to its associated plane
- Place decoupling capacitors for the VDD\_DMC power rail as close as possible to the actual power pins. This is very important because DDR signal slew rates are aggressive. Placing these capacitors close to the pin is mandatory. Provide dedicated power and ground vias for each decoupling capacitor pin, wherever possible
- Ideally, the trace length from the power via to the processor pad should not exceed 30 mils. The maximum trace length from each power via to its decoupling capacitor is 60 mils. The maximum trace length from each power via to its power ball pad is 35 mils
- Placement of the mid-bulk bypass



between the DMC\_VREF supply paths from the memory to the processor

- Place the C (100 pF)-R (2 kΩ) portion of the RCR network as close as possible to the ADSP-2159x/SC59x SHARC+® Processor DMC\_VREF pin
- Use a small package, preferably the

0402 size, for the 100 pF capacitor to guarantee a high self-resonant frequency

- Route the entire RCR network on one layer with no vias in the traces




Figure 4 DMC\_VREF Filtering Network




Figure 5 Recommended VREF Supply Circuit

## Memory-Side Recommendations for VREF Supply

Use the following guidelines for DMC\_VREF

supply placement on the memory side. The requirements apply to both DDR3 and DDR3L.

- DDR3 memory has two VREF pins: VREFCA and VREFDQ. VREFCA serves as the reference for clock, address,

command, and control signals. VREFDQ serves as the reference for strobe, data, and data mask signals

- VREFCA and VREFDQ can have a common supply source but should be “STAR” routed and decoupled at the dedicated DRAM pins
- Place two decoupling capacitors, 0.1  $\mu$ F and 0.01  $\mu$ F, for each VREF pin (VREFCA and VREFDQ)
- Place the 0.01  $\mu$ F capacitor closer to the DRAM pin, followed by the 0.1  $\mu$ F capacitor
- Keep the length from the decoupling capacitor to the DRAM supply pin as short as possible. Maintain the trace width based on the peak current requirement of the DDR. [Figure 5 Recommended VREF Supply Circuit](#), shows the recommended VREF supply circuit for a DDR3 memory device

## Routing Guidelines for other High-Speed Interfaces

Use the following recommendations for the high-speed peripherals (QSPI, Link Port, and SPORT) signals routing.

- The recommendation for maximum trace length is 4 inches

- The trace length should be matched within +/- 3 mils, between the clock and all other signals. This ensures that all the signals are fulfilling the required timings
- The clock signal should be routed 3 times the trace width, away from all other signals. This safeguards the clock signal from noise coupling

## VDD\_DMC voltage, Drive Strength and ODT recommendation

- The VDD\_DMC nominal voltage shall be 1.39V for DDRL. (VDD\_DMC minimum voltage is 1.34V and maximum voltage is 1.44V)
- The recommended Drive Strength of ADSP-2159x/SC59x SHARC+<sup>®</sup> Processor operating at 800 MHz DDR clock is 90 ohms for DQ/DQS/DM/Clk, 100 ohms for ADDR/CMD and ODT is 75 ohms
- The recommended Drive Strength of DDR memory operating at 800 MHz DDR clock is 40 ohms and ODT is 120 ohms.

## References

[1] ADSP-2156x Board Design Guidelines for Dynamic Memory Controller (EE-418). Rev 2, September 2020

[2] EV-21593 SOM<sup>®</sup> Schematic, Rev A, April 2020. Analog Devices, Inc.

## Document History

Revision	Description
<i>Rev 1 – April 14, 2022 by Deepak SH, Nishant Singh</i>	Initial Release