

SELECTED ITEM DRAWING



Unless otherwise
specified
DIMENSIONS ARE
IN INCHES (MM)

TOLERANCES:
.XX +/- 0.010
.XXX +/- 0.005
.XXXX +/- 0.002
ANGLES +/- .5 DEG

Drawing
practices
per **ASME**
Y14.100

25.5 GHz to 27 GHz,
VCO with Divide-By-16 Frequency Output

SIZE
A

DRAWING NUMBER
SID000072

SID000072 **Rev. A**
Information furnished by Analog Devices is believed to be accurate and reliable.
However, no responsibility is assumed by Analog Devices for its use, nor for any
infringements of patents or other rights of third parties that may result from its use.
Specifications subject to change without notice. No license is granted by implication or
otherwise under any patent or patent rights of Analog Devices. Trademarks and
registered trademarks are the property of their respective companies.

1. SCOPE

1.1. Scope

This drawing establishes the requirements for the 25.5 GHz to 27 GHz, GaAs, InGaP, HBT, MMIC, VCO with Divide-By-16 Frequency Output, assembled hermetically in the LSH6 package, to be screened in accordance with MIL-PRF-38535, Class Level S, to the requirements specified in 4.1, 4.2, and 4.3 herein.

1.2. Analog Devices Part Number

Generic Part Number

ADH739S

Screened Part Number

HMC8442LSH6

2. APPLICABLE DOCUMENTS

2.1. Government Documents

Unless otherwise specified, the following drawings and standards, of the issue in effect on the date of the accepted purchase order, in the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, shall form a part of this drawing to the extent specified herein.

DEPARTMENT OF DEFENSE TEST METHOD STANDARD

MIL-STD-883

Microcircuits

DEPARTMENT OF DEFENSE PERFORMANCE SPECIFICATIONS

MIL-PRF-38535

Integrated Circuits (Microcircuits) Manufacturing, General Specification For

2.2. Non-Government Documents

The following documents, of the issue in effect on the date of the purchase order, form a part of this drawing to the extent specified herein:

Analog Devices Inc.

[ADI Standard Space Products Program](#) – ASD-Lite.

HMC739LP4 / 739LP4E Data Sheet

Commercial Product Datasheet

v03.0309 (Reference Only)

3. REQUIREMENTS

3.1. General Requirements

The devices delivered shall comply to this specification.

3.2. Design Construction and Physical Dimensions

The design construction and physical dimensions shall be as defined in Figure 1 herein.

3.3. Traceability

Each delivered device shall be traceable to the wafer lot and wafer number. Inspection lot records shall be maintained to provide traceability to the specific wafer and wafer lot from which the chips originated as well as traceability to package and materials.

3.4. Burn-In and Life Test Circuit

The burn-in and life test circuit and conditions shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test methods 1005 and 1015 per MIL-STD-883.

4. QUALITY ASSURANCE PROVISIONS

4.1. Wafer Lot Acceptance Testing

The wafer lot acceptance testing shall consist of Class Level S inspections per MIL-STD-883 TM 5007.

4.2. Flight Screening Requirements

Flight screening requirements shall be per MIL-STD-883 TM 5004 for Class level S microcircuits.

4.2.1. Electrical Test Requirements

Electrical test requirements are defined in Table I herein.

4.2.2. Electrical Performance Characteristics

Electrical performance characteristics are specified on Table II herein.

4.2.3. Burn-In Delta Requirements

Pre and Post Burn-In Electrical test and delta parameters shall consist of the tests specified in Table III herein.

4.3. Quality Conformance Inspection (QCI)

Group B and Group D tests shall be performed per MIL-STD-883 TM 5005 for Class level S microcircuits.

4.3.1. Post Steady State Life Electrical Test

Post steady state life electrical tests shall consist of the tests specified per Table II tested at room temperature only.

Devices must meet delta parameter requirements in accordance with Table III herein.

5. MIL-PRF-38535 ASD-LITE EXCEPTIONS

The manufacturing flow described in the ADI STANDARD SPACE PRODUCTS PROGRAM is to be considered a part of this specification.

5.1. Wafer Fabrication

Foundry information is available upon request.

5.2. Flight Screening Flow

Non-Destruct Bond Pull: Not performed.

Reverse Bias Burn-In: Not applicable.

5.3. Group B

Subgroup 2: Resistance to solvents is not applicable.

5.4. Group D

Subgroup 5: Not applicable.

Subgroup 7: Not applicable.

Subgroup 8: Not applicable.

Subgroup 9: Not applicable.

6. PREPARATION FOR DELIVERY

The preparation for delivery, packaging, preservation, ESD protection and handling shall be in accordance with MIL-PRF-38535.

6.1. Part Marking

Devices shall be marked as specified on Figure 1 herein.

6.2. Inspection Data Requirements

The following data shall accompany each shipment.

- a. A Certificate of Conformance (C of C) certifies that the lot(s) meets all requirements of this specification.
- b. Wafer Lot Acceptance data including photos from SEM Inspection defined in 4.1 herein.
- c. Summary of electrical test requirements defined in 4.2 herein.
- d. Summary of QCI results defined in 4.3 herein.
- e. Failure Analysis with photos (If applicable)
- f. A cover sheet indicating the following purchasing information:
 1. Customer purchase order number.
 2. Analog Devices part number.
 3. Part lot identification codes.
 4. Date & quantity shipped.

TABLE I: ELECTRICAL TEST REQUIREMENTS

Test Requirement	Subgroups (in accordance with MIL-PRF-38535, Table III)
Interim Electrical Parameters	1, 4
Final Electrical Parameters	1, 4 <u>1/2</u> /
Group A Electrical Parameters	1, 2, 3, 4, 5, 6
Group B End-Point Electrical Parameters	1, 4 <u>2</u> /
Group D End-Point Electrical Parameters	1, 4

TABLE I Notes:

1/ PDA applies to Table I subgroup 1 and Table III delta parameters.

2/ See Table III for delta parameters

TABLE II: ELECTRICAL PERFORMANCE CHARACTERISTICS (-40 °C, +25 °C AND +85 °C)

Parameter	Test Conditions <u>1/</u> Unless otherwise specified	Group A Subgroups	Limits		Units
			Min	Max	
Frequency Range Fo	Vtune = 1 V	4, 5, 6		25.5	GHz
	Vtune = 13 V	4, 5, 6	27		GHz
Output Power RFOUT	Vtune = 1 V and Vtune = 13 V	4	3	14	dBm
		5, 6	1	16	dBm
Output Power RFOUT/16	Vtune = 1 V and Vtune = 13 V	4	-7	-1	dBm
		5, 6	-9	+1	dBm
SSB Phase Noise @ 100 kHz Offset	Vtune = 5 V	4		-85	dBc/Hz
		5, 6		-80	dBc/Hz
Supply Current (Icc(RF) + Icc(DIG))		1	160	250	mA
		2, 3	140	250	mA

TABLE II Note:

1/ Test limits between -40 °C and +85 °C with Vcc(RF) = Vcc(DIG) = +5.4 V.

TABLE III: BURN-IN/LIFE TEST DELTA LIMITS 1/2/3/


Parameter	Test Conditions	Delta Limits	Units
Output Power RFOUT	Per Table II	± 1.2	dB
Output Power RFOUT/16		± 1.2	dB
Supply current ($I_{cc}(RF) + I_{cc}(DIG)$)		± 10	%

TABLE III Notes:

1/ Delta test is performed at $T_A = +25\text{ }^{\circ}\text{C}$ only.

2/ Table II limits will not be exceeded.

3/ Deltas calculated at pre/post 240 hours and post 240 hour / post1000 hours.



NOTES:

1. PACKAGE BODY MATERIAL: ALUMINA, WHITE
2. FINISH: ELECTROLESS Au PLATING 40–100 μ IN THK. OVER ELECTROLESS NICKEL PLATING 100 TO 250 μ IN THK. PLATING THICKNESS MEASURED ON POINT "P".
3. DIMENSIONS ARE IN INCHES [MILLIMETERS].
4. LEAD SPACING TOLERANCE IS NON-CUMULATIVE, DIMENSIONS LOCATED ABOUT $\overline{-A-}$ AND $\overline{-B-}$ WITHIN .005".
5. CHARACTERS TO BE INK OR LASER MARKED WITH .018" MIN TO .030" MAX HEIGHT REQUIREMENTS. UTILIZE MAXIMUM CHARACTER HEIGHT BASED ON LID DIMENSIONS AND BEST FIT. LOCATE APPROX. AS SHOWN.
6. ALL GROUND LEADS AND GROUND PADDLE MUST BE SOLDERED TO PCB RF GROUND.
7. REFER TO ADI APPLICATION NOTE FOR SUGGESTED PCB LAND PATTERN.

PIN #	FUNCTION	PIN #	FUNCTION	PIN #	FUNCTION	PIN #	FUNCTION
1	VCC(RF)	5	GND	9	GND	13	GND
2	Vtune	6	RFOUT/16	10	GND	14	RF OUT
3	GND	7	GND	11	GND	15	GND
4	GND	8	VCC(DIG)	12	GND	16	GND

Figure 1 – Device Outline for the HMC8442LSH6

ORDERING GUIDE

Model	Temperature Range	Package Description	Package Option
HMC8442LSH6	–40 °C to +85 °C	16-Lead Ceramic Hermetic Leadless Chip Carrier	LSH6 (EH-16-2)

Revision History

Revision History		
Rev	Description of Change	Date
A	Initial release.	01/28/2025