


NOTES: UNLESS OTHERWISE SPECIFIED

- 1. ALL RESISTOR ARE IN OHMS, 0402; AND ALL CAPACITORS ARE IN MICROFARAD, 0402.
- 2. INSTALL SHUNTS ON JP1 PIN 1 & 2, JP2 PIN 3 & 4.

<p align="center">CUSTOMER NOTICE</p> <p>LINEAR TECHNOLOGY HAS MADE A BEST EFFORT TO DESIGN A CIRCUIT THAT MEETS CUSTOMER-SUPPLIED SPECIFICATIONS; HOWEVER, IT REMAINS THE CUSTOMER'S RESPONSIBILITY TO VERIFY PROPER AND RELIABLE OPERATION IN THE ACTUAL APPLICATION. COMPONENT SUBSTITUTION AND PRINTED CIRCUIT BOARD LAYOUT MAY SIGNIFICANTLY AFFECT CIRCUIT PERFORMANCE OR RELIABILITY. CONTACT LINEAR TECHNOLOGY APPLICATIONS ENGINEERING FOR ASSISTANCE.</p> <p>THIS CIRCUIT IS PROPRIETARY TO LINEAR TECHNOLOGY AND SUPPLIED FOR USE WITH LINEAR TECHNOLOGY PARTS.</p>		CONTRACT NO.		1630 McCarthy Blvd. Milpitas, CA 95035 Phone: (408)432-1900 Fax: (408)434-0507 LTC Confidential-For Customer Use Only	
		APPROVALS		TITLE: SCHEMATIC	
DRAWN: KIM T.		CHECKED:	HIGH VOLTAGE SYNCHRONOUS STEP-DOWN CONTROLLER		
APPROVED:		ENGINEER: DAVID C.	SIZE	DWG NO.	REV
DESIGNER:			A	DC720A-2 * LT3800EFE	A
DATE: Friday, March 18, 2005		SHEET 1 OF 1			