


FEATURES

- Update Rates to 150MHz
- Low Glitch
- Complete Composite Inputs
- Single +5V Power Supply
- TTL-Compatible Inputs
- Directly Drives 75Ω to Ground

APPLICATIONS

- Raster Scan Displays
- Color Graphics
- Analytical Instrumentation
- TV Video Reconstruction



OBSOLETE

GENERAL DESCRIPTION

The HDG-0807/0407 D/A Converters are extensions of the technology and capabilities of the HDG-Series high-speed raster scan D/A converters. They offer the user increased flexibility because of their ability to operate on a single +5V power supply, and their compatibility with TTL signals.


The units are available in two resolutions, or levels, of Gray Scale output. The HDG-0407 accepts four bits (16 levels) of digital input; and the HDG-0807 is an eight-bit (256 levels) device.

All versions have complete composite controls, including self-contained, digitally-controlled sync and blanking; and a reference

white control input to help assure compatibility with EIA Standards RS-170, RS-330, and RS-343-A. Performance is enhanced even more with a 10% bright input capability.

Output impedance is 75Ω and the full-scale output current is capable of developing standard video levels across video loads. An output current mirror shifts the output to ground reference while attenuating power supply noise by means of common-mode rejection.

Model numbers with "BW" suffixes are housed in 24-pin non-hermetic ceramic dual-in-line packages. Versions with "BD" suffixes are housed in hermetically-sealed ceramic DIP packages.



HDG-0407/0807 Composite Waveform

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices.


Route 1 Industrial Park; P.O. Box 280; Norwood, Mass. 02062
Tel: 617/329-4700
West Coast 714/641-9391
Mid-West 312/653-5000
Texas 214/231-5094
TWX: 710/394-6577

SPECIFICATIONS (typical @ +25°C with nominal power supplies unless otherwise noted)

Parameter	Units	HDG-0407BD/BW	HDG-0807BD/BW
RESOLUTION	Bits	4	8
LEAST SIGNIFICANT BIT (LSB) WEIGHT			
Voltage (adjustable)	mV	40	2.5
Current (adjustable)	μA	1067	67
ACCURACY (GS = Gray Scale; FS = Full-Scale)			
Linearity	± % GS	3.2	0.2
Differential Linearity	± % GS, max	3.2	0.2
Zero Offset (Initial)			
Voltage	mV, max	50	*
Monotonicity		Guaranteed	*
TEMPERATURE COEFFICIENTS			
Linearity	ppm/°C (max)	15 (30)	*
Gain	ppm/°C (max)	350 (1,000)	*
Zero Offset	mV/°C (max)	1.0 (2.0)	*
DYNAMIC CHARACTERISTICS - GS OUTPUT¹			
Settling Time	% GS;	6.4	0.4
1 LSB Mid-scale Voltage Change	ns (max)	8 (10)	14 (16)
0V to FS GS Voltage Change	ns (max)	10 (12)	15 (18)
Slew Rate	V/μs	250	*
Rise Time	ns	2.2	*
Glitch Impulse ²	mV-s	50	*
DIGITAL DATA INPUTS			
Logic Compatibility		TTL	*
Coding		Binary (BIN)	*
Logic Levels ³			
"1"	V (min/max)	(+3.8/+5.0)	*
"0"	V (min/max)	(0/+3.0)	*
Loading (each bit)		5pF and 2kΩ to +5V	*
Data Update Rate	MHz (Guaranteed)	50 (45)	*
STROBE INPUT			
Logic Compatibility		TTL	*
Logic Levels			
"1"	V (min/max)	(+2.5/+5.0)	*
"0"	V (min/max)	(0/+1.5)	*
Loading		1pF and 2.2kΩ to +4.4V	*
Setup Time (Data)	ns, min	3	*
Hold Time (Data)	ns, min	3	*
Propagation Delay	ns (max)	8	*
10% BRIGHT, REFERENCE WHITE, COMPOSITE SYNC, AND COMPOSITE BLANKING INPUTS			
Logic Compatibility		TTL	*
Logic Levels			
"1"	V (min/max)	(+3.8/+5)	*
"0"	V (min/max)	(0/+3.5)	*
Loading		5pF and 2kΩ to +5V	*
SPEED PERFORMANCE - CONTROL INPUTS			
Settling Time to 10% of Final Value for:			
10% Bright	ns (max)	15	*
Reference White	ns (max)	15	*
Composite Sync	ns (max)	15	*
Composite Blanking	ns (max)	15	*
SETUP CONTROL			
+5V	mV (IRE Units)	0 (0)	*
Open	mV (IRE Units)	53.25 (7.5)	*
ANALOG OUTPUT			
GS Voltage p-p ⁴	mV (± 4%)	600	637.5
Compliance	V	-3 to +3	-3 to +3
Internal Impedance	Ω (min/max)	75 (71/79)	*
OUTPUT - REFERENCE WHITE⁵ (Assumes Setup is Open, Which is Equivalent to 7.5 IRE Units)			
Voltage			
Logic "1"	mV (± 4%)	Normal Operation	*
Logic "0"			
10% Bright @ "0"	mV	1046.75	*
10% Bright @ "1"	mV	975.75	*

OUTLINE DIMENSIONS

Dimensions shown in inches and (mm).



PIN DESIGNATIONS

(As Viewed from Bottom)

Pin	Function	Pin	Function
24	ANALOG GROUND	1	+5V
23	REFERENCE WHITE	2	DIGITAL GROUND
22	COMPOSITE BLANKING	3	BIT 1 (MSB)
21	10% BRIGHT	4	BIT 2
20	SETUP	5	BIT 3
19	COMPOSITE SYNC	6	BIT 4
18	ANALOG OUTPUT	7	STROBE
17	+5V	8	BIT 5
16	+5V	9	BIT 6
15	+5V	10	BIT 7
14	+5V	11	BIT 8 (LSB)
13	GLITCH ADJUST	12	+5V


NOTES: For HDG-0407 units, Pin 6 is LSB; Pins 8, 9, 10 and 11 are present but not used. For both units, connect Pins 2 and 24 together and to low-impedance ground plane as close to case as possible. +5V must be applied to all designated pins.

Parameter	Units	HDG-0407BD/BW	HDG-0807BD/BW
OUTPUT - 10% BRIGHT⁶			
Voltage			
Logic "1"	mV (± 4%)	0	*
Logic "0"	mV (± 4%)	71	*
OUTPUT - COMPOSITE SYNC^{6,7}			
Voltage			
Logic "1"	mV (± 4%)	0	*
Logic "0"	mV (± 4%)	285	*
OUTPUT - COMPOSITE BLANKING^{6,7} (Assumes Setup is Open)			
Voltage			
Logic "1"	mV (± 4%)	0	*
Logic "0"	mV (± 4%)	90.75	53.25
POWER REQUIREMENTS			
+5V to ±0.25V	mA (max)	185 (225)	185 (225)
Power Supply			
Rejection Ratio	%/V	0.025/0.25	0.025/0.25
Power Dissipation	mW (max)	925 (1125)	925 (1125)
TEMPERATURE RANGE			
Operating (Case)	°C	-25 to +85	*
Storage	°C	-55 to +150	*
THERMAL RESISTANCE			
Junction to Air, θ_{ja} (free air)	°C/W, max	45	*
Junction to Case, θ_{jc}	°C/W, max	12	*
PRICES (1-9)		48/45	61/55

For applications assistance, phone Computer Labs Division at (919) 668-9511

NOTES

- ¹ Settling to GS percentage includes FS and MSB transitions. Inherent 3ns register delay (50% points) is not included.
 - ² Glitch can be reduced with glitch adjustment.
 - ³ Internal 2k pull-up resistors help assure compatibility with logic levels of multiple TTL families.
 - ⁴ LSB value used for calibration causes Gray Scale output to be 637.5mV rather than 643mV shown in idealized composite waveform; both values are well within the output and EIA Standard RS-170 tolerances.
 - ⁵ Effect on analog output of logic "0" at Reference White input depends on 10% Bright signal input.
 - ⁶ 10% Bright, Composite Sync, and Composite Blanking outputs shown add to Gray scale analog output at Pin 18 and are measured with respect to sync level (V_s) shown in waveform.
 - ⁷ Composite Sync or Composite Blanking control signals reset input registers. Composite Sync or Composite Blanking should not be operated simultaneously with Reference White, which sets input registers.
 - ⁸ Maximum junction temperature = 150°C.
 - * Specification same as HDG-0407.
- Specifications subject to change without notice.



HDG-0807 Block Diagram

THEORY OF OPERATION

Refer to the block diagram of the HDG-0807 D/A Converter and the HDG-0407/0807 composite output waveform.

The digital input bits represent the Gray Scale values (the discrete levels between Reference Black and Reference White) in a composite video signal. For HDG-0407 units, there are 16 (2^4) of these levels; and for the HDG-0807, 256 (2^8) levels.

Input bits are applied to Pins 3-6 and Pins 8-11 for the HDG-0807; for the HDG-0407, only Pins 3-6 are used.

The output analog signal (at Pin 18) will be a function of these digital inputs. The output will also be affected by the TTL levels at the control inputs of 10% Bright, Reference White, Composite Sync, and Composite Blanking; and the level of the control signal (expressed in terms of IRE units) at the Setup input.

The total effect of these combined signals can be illustrated in a truth table format if arbitrary values are assigned for Gray scale inputs, and various combinations of control inputs are selected.

Refer to Table I.

Analog Devices uses 2.5mV for weighting the LSB during calibration of the converter, which causes the full scale 637.5mV output of the HDG-0807 to be different from the ideal 643mV output shown in the composite waveform in the RS-170 standard.

DIGITAL INPUTS VS. ANALOG OUTPUT								10% BRIGHT	REF. WHITE	BLANK. INE	COMP. SYNC	ANALOG OUTPUT IN mV (HDG-0807)
BIT 1	BIT 2	BIT 3	BIT 4	BIT 5	BIT 6	BIT 7	BIT 8					
1	1	1	1	1	1	1	1	0	1	1	1	1046.75
1	1	1	1	1	1	1	1	1	1	1	1	975.75
1	0	0	0	0	0	0	0	0	1	1	1	729.25
0	0	0	0	0	0	0	0	0	1	1	1	409.75
0	0	0	0	0	0	0	0	1	1	1	1	338.25
X	X	X	X	X	X	X	X	0	0	1	1	104.75
X	X	X	X	X	X	X	X	1	0	1	1	97.75
X	X	X	X	X	X	X	X	0	1	0	1	338.25 ²
X	X	X	X	X	X	X	X	0	1	0	1	285 ³
X	X	X	X	X	X	X	X	0	1	0	0	124.25 ²
X	X	X	X	X	X	X	X	0	1	0	0	71 ³
X	X	X	X	X	X	X	X	1	1	0	0	53.25 ²
X	X	X	X	X	X	X	X	1	1	0	0	0 ³

NOTES
¹Values are for Gray Scale output of HDG-0807 measured with respect to Sync level. HDG-0407 Gray Scale output is 37.5mV less than 8-bit output.
²Setup (Pin 20) to +5V. (0 IRE units)
³Setup (Pin 20) open. (7.5 IRE units)

Table I. Digital Inputs vs. Analog Output

APPLICATIONS

The HDG-0407 and HDG-0807 are specifically designed for operation in raster scan graphics applications, in which digital input data are being changed at a relatively high rate.

The D/A output is generally ac-coupled to the monitor, which eliminates the changing dc offset associated with the thermal drift of the level shift circuits. This offset drift, which is a function of output level, is held to a maximum of 50mV and will not affect dynamic video levels.

For optimum performance, ground pins 2 and 24 should be connected together and to a large ground plane near the unit. As indicated in the footnotes on the pin designations table, +5V must be applied to all pins which are called out to receive it.

The performance of the HDG devices can be enhanced with external bypass capacitors which will supplement the internal components. Low-frequency bypassing should be provided with 1μF (or larger) tantalum capacitors between the +5V supply pins and ground. High-frequency bypassing can be provided with ceramic capacitors of 0.1μF or larger. All bypass capacitors should be tied as closely as possible to the hybrid power supply pins.

A 200Ω potentiometer between +5V and ground with the center arm connected to Pin 13 changes the threshold of the internal

This disparity does not cause any problems in using the device, since both the ideal value and the actual value are well within the tolerances of the output and the RS-170 standard.

Referring again to the block diagram, the Strobe input applied to the HDG D/A clocks the input registers when the strobe signal makes the transition from a logic "0" to a logic "1". The purpose of the registers is to remove time skew from the digital input bits and minimize perturbations or "glitches" in the analog output signal.

A logic "0" applied to either the Composite Sync or Composite Blanking input resets the input registers to 00 000 000. A logic "0" signal applied to the Reference White input sets the input registers, thereby overriding the video input word. When this occurs, the analog output of the converter goes to 1046.75mV or to 975.75mV, depending upon whether or not the 10% Bright signal is also operated.

When Composite Blanking is operated, the analog output will go to a Reference Black value of 338.25mV less some amount, as determined by the voltage at Setup. The 53.25mV example used in the Specifications section of the data sheet is based on the Setup input floating, which is equivalent to 7.5 IRE units. (For this example, the analog output would be 285mV.)

current switches; this can reduce the amount of glitch from the typical 50pV-s to a lesser value when required.

For best performance, standard 24-pin hybrid sockets should be avoided. Individual pin sockets are preferable for evaluating devices and are available from Analog Devices; in final designs, the D/A should be soldered directly into the printed circuit board without sockets.

If it is necessary to route digital signals and/or strobe signals for distances greater than one inch (2.54cm), microstrip techniques should be used. Otherwise, the performance of the D/A converter may be affected adversely.

ORDERING INFORMATION

There are two versions of the 4-bit converter, and two versions of the 8-bit device; all units operate over a temperature range of -25°C to +85°C. For 4-bit operation, order the HDG-0407BD or HDG-0407BW; for 8-bit converters, the model numbers are HDG-0807BD or HDG-0807BW. In these model numbers, the "D" in the suffix indicates a ceramic, hermetically-sealed DIP; and the "W" indicates a non-hermetic ceramic DIP.

Versions are available screened to military requirements; contact the factory for details. It is also possible to order units with synchronous functions on a "special order" basis; detailed information is available from the factory.