

RELIABILITY REPORT





RELIABILITY DATA
LTC1514/1515 / LT1786 / LTC945 / LT926 / LTC3900/3901

8/21/2006

• OPERATING LIFE TEST

PACKAGE TYPE	SAMPLE SIZE	OLDEST DATE CODE	NEWEST DATE CODE	K DEVICE HOURS ⁽¹⁾ AT +125°C	NUMBER OF ⁽²⁾ FAILURES
SOIC/SOT/MSOP	125	9714	9827	68.77	0
SSOP/TSSOP	78	0421	0421	78.00	0
	203			146.77	0

• PRESSURE COOKER TEST AT 15 PSIG, +121°C

PACKAGE TYPE	SAMPLE SIZE	OLDEST DATE CODE	NEWEST DATE CODE	K DEVICE HOURS	NUMBER OF FAILURES
SOIC/SOT/MSOP	673	9811	0621	132.89	0
	673			132.89	0

• TEMP CYCLE FROM -65°C to +150°C

PACKAGE TYPE	SAMPLE SIZE	OLDEST DATE CODE	NEWEST DATE CODE	K DEVICE CYCLES	NUMBER OF FAILURES
SOIC/SOT/MSOP	799	9722	0621	286.00	0
	799			286.00	0

• THERMAL SHOCK FROM -65°C to +150°C

PACKAGE TYPE	SAMPLE SIZE	OLDEST DATE CODE	NEWEST DATE CODE	K DEVICE CYCLES	NUMBER OF FAILURES
SOIC/SOT/MSOP	598	9722	0621	139.40	0
	598			139.40	0

(1) Assumes Activation Energy = 0.7 Electron Volts

(2) Failure Rate Equivalent to +55°C, 60% Confidence Level = 80.64 FITS

(3) Mean Time Between Failures in Years = 1,415

Note: 1 FIT = 1 Failure in One Billion Hours.