

INDEX

SUBJECT INDEX

ANALOG DEVICES PARTS INDEX

SUBJECT AND AUTHOR INDEX

A

- Active crossover, active filter, 8.113-116
- Active filter, active crossover, 8.113-116
- Active and Passive Electrical Wave Filter Catalog (TTE, Inc.), 12.39
- AD620 Instrumentation Amplifier Data Sheet:
 - RF Interference, 1.92
- AD625 Instrumentation Amplifier Data Sheet:
 - Other Considerations (RFI Protection, 1.92)
- Adams, R.W., 8.156; 14.36
- ADC:
 - 6-bit, fullscale converter, characteristics, 12.8
 - 8-bit,
 - dual,
 - flash converter, 13.3
 - block diagram, 13.3
 - ENOB, 12.19
 - external voltage reference, 13.5
 - internal voltage reference, 13.4
 - performance, 13.2
 - SNR, 12.19
 - FFT testing, 16.10
 - flash converter, 13.6-7
 - bit error rate, 12.38
 - block diagram, 15.20
 - demultiplexing output data, 13.9-10
 - dynamic performance, 15.21
 - input circuit, 12.20
 - output data, 13.6-7
 - fullscale converter, characteristics, 12.8
 - high speed, 13.9
 - subranging, block diagram, 12.22
- 10-bit,
 - FFT testing, 16.10
 - flash converter,
 - block diagram, 15.22
 - performance, 13.2
 - fullscale converter, characteristics, 12.8
 - high speed, frequency vs. SFDR, 12.16
 - subranging, digitally corrected, two-stage, 12.24
- 12-bit,
 - 3-volt operation, 6.37
 - 8-bit, 13.8
 - 8-channel,
 - sampling,
 - serial output, 6.43
 - specifications, 6.44
 - evaluation board, 16.2
 - FFT output, 12.10; 15.6
 - FFT testing, 16.10, 12
 - Hanning window function, 16.15
 - MathCad FFT output, 16.15-16
 - flash converter, pipelined
 - architecture, 13.8
 - fullscale converter, characteristics, 12.8
 - high speed, frequency vs. SFDR, 12.16
 - key features, 6.37
 - monolithic sampling,
 - ENOB, 12.11
 - S/N+D, 12.11
 - sampling, 6.46
 - SHA, 4.6
 - SFDR, 9.13; 15.14
 - signal sampling effects, 15.6
 - single channel,
 - sampling,
 - circuit, 6.45
 - features, 6.45
 - subranging,
 - digitally corrected, 12.23
 - three-stage, 12.24-25
 - transient response, 12.30-31
- 14-bit,
 - antialiasing filter, 15.5
 - block diagram, 15.2
 - drive amplifier, circuit, 15.4
 - FFT output, 15.19
 - FFT testing, 16.10
 - flash converter, diagram, 15.20
 - fullscale converter, characteristics, 12.8
 - high speed, 9.5
 - frequency vs. SFDR, 12.16
 - SFDR, 12.14-15
 - quad driver, 15.5
 - sampling, 6.46
 - analog I/O ports, 6.46-47
 - SFDR, 15.2-3
 - SFDR versus input frequency, 15.17-18
 - SHA, 15.16
 - SNR, 15.2-3
 - subranging, recursive, 12.25-26
 - test configuration, hold-mode SFDR, 15.18
 - track-and-hold, 15.17-18
- 16-bit,
 - block diagram, 13.11
 - characteristics, 13.11
 - in CODEC, 14.30
 - CODEC, 8.4-5
 - effective bit performance, 13.12
 - FFT output, 13.12
 - fullscale converter, characteristics,

- 12.8
 - hybrid sampling,
 - autocalibration, 13.24
 - FFT output, 13.25
 - Autozero function, 13.26
 - block diagram, 13.24
 - FFT output, 13.25
 - temperature effects, 13.25
 - precision sampling, 13.10-25
 - data output,
 - parallel, 13.26-27
 - serial, 13.26, 28
 - DSP, data output, 13.26-28
 - parallel interface, 13.26-27
 - serial interface, 13.28
 - sampling, 13.12
 - autocalibrating, 13.14-15
 - analog ground sense, 13.16
 - with drive amplifier, 13.20-21
 - ENOB, 13.17
 - equivalent input circuit, 13.18
 - equivalent input noise, 13.17
 - S/N+D, 13.17
 - equivalent input noise, 13.13
 - input and reference interface, 13.14
 - noise sources, 13.13
 - sigma-delta,
 - third order,
 - comb filter, 14.18-19
 - description, 14.16-21
 - differential drive, 14.21
 - digital filter,
 - group delay, 14.19
 - settling time, 14.19
 - filter output, 14.17-18
 - filter response characteristics, 14.18
 - FIR filter, 14.18-19
 - specifications, 14.17
 - V.32 modem signal port, 18.18-19
 - block diagram, 18.18
 - specifications, 18.19
 - 18-bit,
 - dual,
 - sigma-delta,
 - block diagram, 14.22
 - description, 14.22-25
 - differential driver, 14.25
 - digital filter,
 - characteristics, 14.24
 - response, 14.24
 - noise shaping, 14.23
 - specifications, 14.23
 - sigma-delta,
 - audio, 8.128-133
 - block diagram, 8.129
 - differential driver, 8.133
 - filter design, 8.130
 - filter response, 8.131
 - key specifications, 8.129
 - switched capacitor, 8.132
 - 22-bit,
 - quad sigma-delta, 6.47-48
 - circuit, 6.48
 - features, 6.48
 - 24-bit, sigma-delta, 6.40
 - analog multiplexer, 12.31
 - antialiasing filter, 12.5-8
 - aperture delay time, 12.28
 - aperture jitter, 12.29-30
 - ENOB, 12.30
 - SNR, 12.30
 - audio, 14.22-25
 - bench testing,
 - ac linearity using histograms, 16.8-9
 - decimation, 16.7
 - DSP techniques, 16.7-9
 - PC-based system, 16.8
 - bit error rate, 12.33-38
 - high frequency testing, analog input, 12.36
 - input frequencies, 12.37
 - low frequency testing, analog input, 12.36
 - random noise, 12.33
 - testing, 12.35
- bit sizes, 12.8-9
- characteristics, 12.12
- clipping, 10.28
- CODEC, 8.4-5
- coherent sampling, requirements, 16.11
- decoupling, 13.39
- distortion,
 - analysis, 12.16
 - discontinuity, 12.16-17
 - transfer characteristics, 12.16
- drive amplifier, characteristics, 13.2
- dynamic range, 12.7-17
- autocalibration, 15.9
- dither signals, 15.6-9
- error correction, 15.8
- dynamic testing, 12.9
- dynamic transfer,
 - analog evaluation, 16.4-7
 - beat frequency test, 16.4-7
 - Nyquist input, 16.6
- effective aperture delay time, 12.28
- measurement, 12.28
- ENOB, 12.11, 13
- error codes, 12.33
- evaluation board, 16.1
- FFT, 12.13
- noise measurement, 12.14
- FFT output, 12.10
- FFT testing, 16.9-16
- coherent, 16.10-11

- frequency bin width, 16.9-10
- mathematical software, 16.9
- QuickBasic routines, 16.17-19
- flash converter,
 - block diagram, 13.3
 - dynamic performance, 13.2
 - ENOB, 12.19
 - equivalent input circuit, 12.20
 - error sources, 12.17-21
 - external voltage reference, 13.5
 - harmonic distortion, 12.19
 - input protection, Schottky diodes, 13.31-32
 - interface circuit, 13.4
 - internal voltage reference, 13.4
 - latched data output, 13.6-7
 - latency, 13.7
 - output data,
 - latency, 13.7
 - pipeline delay, 13.7
 - pipeline delay, 13.7, 8-9
 - quadrature receiver application, 13.3
 - signal-dependent capacitance, 12.20
 - SNR, 12.19
 - thermometer code, 12.17-18
 - timing diagram, 13.6
 - latency, 13.7
 - pipeline delay, 13.7, 8-9
 - three clock-cycle latency, 13.9
 - total harmonic distortion, 12.21
- full-power bandwidth, 12.12-13
- grounding, 13.38
- high resolution, 15.1
- high speed,
 - 3-terminal regulator as supply, 13.31
- demultiplexing output, 13.9-10
- drive amplifier, 13.2-8
 - characteristics, 13.2
- input protection, 13.29-31
 - clamp circuit, 13.29
- latchup, 13.29
 - protection, 13.30
- output data, 13.6-8
- overdrive, 13.29
- overvoltage, power supply sequencing, 13.30
- slow memory storage, 13.10
- supply sequencing damage, protection, 13.30
- input,
 - Gaussian wideband noise, 15.7
 - SHA, 4.1
- interfacing, requirements, 13.1
- intermediate frequency, sampling rate, 15.13
- Mathcad routines, 16.20-22
- metastability, 12.33-38
- multi-bit,
 - sigma-delta, 14.33-34
 - first-order, diagram, 14.34
 - summary, 14.34-35
 - noise, 12.33
 - non-sigma-delta, data acquisition, 14.18
 - Nyquist sampling, 12.1
 - on-chip SHA, 4.7
 - overvoltage recovery time, 12.32
 - peak harmonious component, 12.13
 - peak spurious, 12.13
 - PGA, gain controlled by serial interface, 3.14
 - precision, low noise, voltage reference, 13.22
 - quantization theory basics, 12.10
 - recursive subranging, 12.25-26
 - resolution, 12.7-17
 - sampling, 4.1
 - aperture jitter, 13.32-33
 - clock generator circuit, 13.34
 - clock signal, 13.32-34
 - ENOB, 12.9
 - phase jitter, 13.32
 - precision low-jitter, 13.34
 - SNR, 12.11
 - sampling rate, 12.5-8
 - serial output, 6.40-41
 - advantages, 6.40
 - settling time, 12.30-31
 - SFDR, 9.14; 12.13
 - definition, 12.15
 - and frequency, 12.15
 - from input signal, 12.14
 - SHA,
 - block diagram, 15.20
 - driving flash converter, 15.21
 - function, 15.15-16
 - timing optimization, 15.19
 - sigma-delta, 14.1-35
 - antialiasing filter, decimation, 14.2-3
 - audio, 14.22-25
 - bandpass, 15.23
 - digital filter, 15.25
 - ENOB, 15.24
 - experimental, summary, 15.25
 - fourth-order, structure, 15.24
 - noise shaping, 15.23
 - charge-balance, 6.5
 - conversion time, 6.7
 - decimation, 14.10-13, 13
 - digital filter,
 - measured group delay, 14.18-19
 - settling time, 14.18-19
 - digital filtering, 14.10-13, 13
 - direct intermediate frequency-to-
 - digital conversion, 15.22-25
 - effective resolution, 6.9

- filter setting, conversion and settling time, 6.8
 - finite impulse filter, 14.2-3, 12
 - first order,
 - diagram, 14.5
 - noise shaping, 14.8-9
 - SNR versus oversampling, 14.8-9
 - higher-order, characteristics, 14.32
 - idling pattern, 14.13-14
 - infinite impulse filter, 14.12
 - MASH,
 - characteristics, 14.32-33
 - diagram, 14.32
 - three-stage, 14.31-33
 - modulator, 14.4-9
 - equivalent input circuit, 14.25
 - frequency domain linearized model, 14.7
 - higher order, 14.15-16
 - idling pattern, 14.14-15
 - repetitive bit pattern, 14.14
 - switched-capacitor architecture, 14.19-20
 - waveforms, 14.6
 - noise shaping filter, 14.7-8
 - Nyquist sampling, 14.2-3
 - oversampling, 14.2-4
 - benefits, 14.4
 - PGA function, 6.6
 - quantization noise shaping, 14.5-9
 - distribution, 14.8
 - second order,
 - diagram, 14.8-9
 - noise shaping, 14.8-9
 - SNR versus oversampling, 14.8-9
 - signal conditioning transducer input, 6.1-31
 - analog input structure, 6.14
 - anti-aliasing filter, 6.12-14
 - applications, 6.25-31
 - calibration, 6.20-24
 - characteristics, 6.1
 - connections, 6.16
 - conversion errors, 6.15
 - differences, 6.3
 - digital filter frequency response, 6.7
 - effective resolution, 6.9-10
 - features, 6.3
 - high integration, 6.2
 - microprocessor interface, 6.27
 - noise, 6.9-11, 18-19
 - optimizing, 6.12
 - noise limitations, 6.8
 - noise-free codes, 6.11
 - operation theory, 6.5
 - overvoltage protection, 6.17
 - sensor applications, 6.4
 - serial interface, 6.25-26
 - voltage reference, 6.17
 - weigh scale, 6.25
 - third order,
 - description, 14.16-21
 - SNR versus oversampling, 14.8-9
 - tonal considerations, 14.13-14
 - traditional, noise shaping, 15.23
 - voltage reference, 5.15-16
 - dynamic load effects, 5.17
 - noise, 5.17
 - stability, 5.20-21
 - single supply, 6.32-39
 - characteristics, 6.32
 - data acquisition system, 6.38-39
 - input range limit, supply voltage, 6.34
 - input scaling, 6.35
 - voltage reference, 6.36
 - SNR, 12.8-9
 - and frequency, 12.15
 - spectral analysis,
 - Minimum 4-Term Blackman-Harris
 - window,
 - 16.13
 - two-tone IMD testing, 16.13
 - weighting function, 16.13
 - wide dynamic range, 15.1-5
 - windowing function, 16.13-14
 - static transfer,
 - analog evaluation, 16.2-4
 - DAC output, 16.3
 - error, 16.4
 - triangular wave, 16.3
 - sub-Nyquist sampling, 12.1
 - subranging,
 - block diagram, 12.22
 - digital correction, 12.23-24
 - error sources, 12.27
 - error sources, 12.22-27
 - linearity errors, 12.27
 - successive approximation, voltage reference, dynamic transient load, 5.21
 - theoretical quantization noise, 12.8-9
 - transient response, 12.30-31
 - and VGA, 15.26-31
 - video, 4:1 multiplexer, 11.22
 - voltage reference, 5.16; 13.21-23
- ADSP-2100 Family User's Manual, 18.42
- Akazawa, Yukio, 12.39
- Aliasing:
 - description, 12.3-4
 - frequency domain effects, 12.5
 - time domain effects, 12.4
- Amplifier:
 - isolation,
 - 3-port, 1.82
 - characteristics, 1.83

- family, 1.84
- motor control current sense, 1.84
- transformer-isolated, 1.82-84
- latch-up, 1.73-74
- output, phase reversal, 1.72, 74
- paralleling, precision line driver, 1.74-76
- precision weight-scale, signal conditioning, 1.6-7
- programmable gain, see: PGA
- sample and hold, see: SHA
- single supply RTD, linearized, 1.9-10
- Amplifier Applications Guide (1990), 15.40
- Amplifier Applications Guide (1992), 6.49; 10.33
- Analog circuit:
 - high performance, prototyping, 13.45-47
 - socket prohibition, 13.44-45
- Analog multiplexer, data acquisition system, 12.31
- Analog signal:
 - aliasing, 12.3
 - discrete time sampling, 12.2-5
 - multiplexed, 2.1-4
 - switched, 2.1-4
- Analog switch:
 - characteristics, 2.2
 - CMOS, 2.1
 - ac parameter, 2.14-15
 - charge injection, effects, 2.15
 - model, 2.14
 - adjacent, equivalent circuit, 2.9
 - advantages, 2.3-4
 - anatomy, 2.9-18
 - applying, 2.20-25
 - dynamic performance, 2.21
 - minimizing gain error and providing isolation, 2.25
 - minimizing on resistance, 2.22-23
 - noninverting solution, 2.25
 - minimizing on resistance versus temperature, 2.24
 - multiplex buffer into ADC, 2.25
 - parasitic capacitance, 2.22
 - switching time, 2.20
 - unity gain inverter with switched input, 2.21
 - on condition, dc performance, 2.10
 - crosstalk,
 - equivalent circuit, 2.17
 - performance, 2.17
 - diode protection, 2.6-7
 - error sources, 2.9-18
 - junction-isolated, diagram, 2.5
 - latchproof versus overvoltage protection, 2.8
 - latchup, diode protection, 2.6-7
 - off condition, dc performance, 2.10
 - off isolation, 2.13-14
 - off isolation versus frequency, 2.13
 - overcurrent, diode protection, 2.6-7
 - parasitic components, ac performance, 2.11
 - parasitic latchup, 2.4-8
 - performance, 2.9-18
 - series-pass capacitance, 2.11-12
 - settling time, 2.18
 - time constants required, 2.18
 - transfer accuracy versus frequency, 2.12
- LC2MOS,
 - trench-isolation,
 - advantages, 2.19-20
 - structure, 2.20
- Analog system, voltage references, 5.1-22
- Andreas, D., 8.156; 14.36
- Andrews, James R., 16.23
- ANSI Standard 268-15 (Revision 1987, amendments 1989, 1990, 1991), 8.17
- Antialiasing filter, and oversampling, 14.3
- Aperture jitter:
 - definition, 12.29
 - effects, 12.29
 - on ENOB, 13.32-33
 - on SNR, 13.32-33
 - ENOB, 12.30
 - SNR, 12.30
- Application circuit, EMI reduction, 1.29-33
- Asta, Dan, 15.39
- Audio buffer amplifier:
 - capacitive load compensation, external "in-loop," 8.69-70
 - internal, 8.68
 - passive, 8.66-67
 - high current, 8.63-65
 - unity gain stand-alone, 8.63
 - THD+N versus frequency, 8.65
- Audio circuit:
 - diagram, 8.51
 - line level stages, 8.50-92
 - amplifiers, 8.50
 - drivers, 8.50
 - receivers, 8.50
 - transformers, 8.51
 - transformers, 8.51
- Audio line amplifier, 8.50
 - current boosted, composite, 8.82
- Audio line buffer, 8.63-92
- Audio line driver, 8.50, 63-92
 - amplifier, test circuit, 8.71
 - capacitive loading, 8.65-66
 - current boosted, 8.79-81
 - composite, 8.81-82
 - THD+N versus frequency, 8.82
 - THD+N versus frequency, 8.80

- differential, 8.83-86
 - cross-coupled, 8.85-86
 - THD+N versus frequency, 8.86
 - "inverter-follower," 8.83-85
 - THD+N versus frequency, 8.84
- high current, 8.63-65
- "inverter-follower", pseudo-differential, 8.85
- overcompensation, 8.66
- paralleled output, 8.75-77
- single-ended, 8.70-71, 73-77
 - consumer equipment, 8.73-75
 - THD+N versus frequency, 8.75
- transformer coupled, 8.87-91
 - with feedback, 8.88-91
- steel core,
 - with feedback, THD+N versus frequency, 8.91
 - THD+N versus frequency, 8.89
 - with tertiary feedback, 8.89
 - THD+N versus frequency, 8.88
- voltage follower amplifier, THD+N versus frequency, 8.71-73
- wide dynamic range ultra low distortion, 8.77-78
 - THD versus frequency, 8.78
- Audio line level stage, 8.50-92
- Audio line receiver, 8.50, 52-62
 - "all inverting," 8.58-59
 - circuit, 8.58
 - THD+N versus frequency, 8.61
- alternate balanced, 8.58
- balanced, 8.56
 - common mode error versus frequency, 8.60
 - performance, 8.59-61
 - push-pull feedback, 8.57
 - THD+N versus frequency, 8.60
- balanced feedback differential, 8.57
- differential amplifier, 8.52
- simple, load balance, 8.56
- simple line receiver, 8.52-55
 - common mode rejection versus frequency, 8.54-55
 - components, 8.53
 - implementation, 8.55-56
- Audio signal:
 - applications, 8.1-156
 - preamplifier, See: Preamp
- Audio system:
 - digital, see: Digital audio
 - DSP, see: Digital audio
 - speaker crossover, 8.101-124
 - component quality, 8.106
 - crossover design, 8.106-116
 - filters, 8.102
 - impedance compensation, 8.103-106
 - semi-inductor, 8.104
 - Zobel network, 8.103-104
 - order, 8.102-103
 - physics, 8.101-103
 - resonance compensation, 8.105
 - series networks, 8.105
 - speaker design,
 - active crossover,
 - calculations, 8.120-123
 - design, 8.115-116
 - frequency response, 8.123
 - highpass filter, 8.122
 - lowpass filter, 8.120
 - network design, 8.113-116, 123
 - Sallen-Key design, 8.120
 - voltage-controlled voltage source, 8.120
 - allpass filter, 8.116
 - bi-wiring, 8.113
 - Butterworth response, 8.116
 - crossover network, active versus passive, 8.114-115
 - D'Appolito configuration, 8.107
 - impedance matching networks, 8.109
 - impedance measurement, 8.107
 - Linkwitz-Riley response, 8.116
 - midrange compensation circuit, 8.112
 - midrange impedance, 8.110
 - resonance compensation, 8.111
 - Zobel compensation, 8.111
 - passive crossover, calculations, 8.118-119
 - passive crossover network components, 8.107-108
 - resonance compensation, network design, 8.108
 - Sallen-Key implementation, 8.116
 - three-way, 8.106-116
 - tweeter compensation circuit, 8.113
 - woofer compensation circuit, 8.112
 - woofer impedance, 8.110
 - Zobel compensation, network design, 8.108
 - Audio voltage-amplifier:
 - gain stage,
 - dc servo control, 8.93-97
 - inverting, dc servo control, 8.96-97
 - non-inverting, dc servo control, 8.93-95
 - Augstadt, H., 8.62

B

- Bahl, Il, 1.92
- Baldwin, Eugene E., 16.23
- Bandwidth, and risetime, 9.2-3
- Barrow, J., 8.92
- Baseband sampled data system, key elements, 12.1

- Baxendall, P., 8.40
 Beat frequency test:
 block diagram, 16.5
 flash converter ac nonlinearities, 16.7
 Nyquist input, 16.6
 Bell, Barry A., 16.23
 Bennett, W.R., 16.23
 Bhartia, P., 1.92
 Bingham, John, 18.42
 Birt, David, 8.62
 BJT-input devices, collector current,
 changes, 1.45-46
 Blackman, R.B., 16.23
 Blood, William R., Jr., 11.43
 Bohn, Dennis, 8.117
 Borbely, Erno, 8.98-99
 Bore, G., 8.17
 Borlase, Walter, 8.62
 Boser, B., 14.36
 Bowers, D., 8.98
 Boyd, I., 18.42
 Bradley, F., 8.40
 Breakall, (), 8.100
 Broderson, (), 16.24
 Brokaw, A. Paul, 1.92; 5.22; 8.92
 Bryant, James, 4.1; 6.49
 Bryant, James M., 1.1, 93; 8.92; 15.1, 22,
 40
 Buffer:
 early,
 description, 10.22
 hybrid, 10.23
 op amp, high speed, 10.10
 ultralow distortion,
 endpoint linearity, 10.24
 frequency response, 10.25
 harmonic distortion, 10.25
 settling time, 10.25
 specifications, 10.24
 Bullock, Robert M. III, 8.117
 Buxton, Joe, 1.1; 3.1; 6.1; 8.92; 10.33;
 11.43
- C**
- Cable:
 capacitance, 11.4
 coaxial, attenuation, 11.9
 driving, video frequencies, 11.8-11
 long,
 capacitance, amplifier phase margin
 degradation, 1.18
 floating shield, 1.15-16
 grounded shield,
 earth ground, 1.19
 experiments, 1.15-21
 ground loops, 1.19
 low noise, 1.20
 near-end grounding, 1.21
 oscillation, 1.17
 RF noise coupling, 1.17
 RF/EMI noise shunting, 1.18
 signal ground, 1.19
 noise coupling, 1.16
 noise shielding, 1.13-21
 unshielded, 1.15
 shielding, improper grounding, noise,
 1.14-15
 Cabot, Richard, 8.62
 Calhoun, George, 18.42
 Calibration:
 coefficients, 6.23
 calculation, 6.24
 terms, 6.24
 system-offset, 6.21
 Capacitive loads, in-the-loop compensation,
 11.6
 Capacitor, decoupling, eliminated, 13.23
 Caves, J.T., 16.24
 Cellular mobile telephone, 18.22
 disadvantages, 18.22-23
 frequency division multiple access,
 18.22
 Cellular radio:
 frequency reuse, 18.23
 frequency spectrum allocation, United
 States, 18.24
 Charpentier, A., 8.156; 14.36
 Chessman, M., 8.98
 Childress, H., 8.100
 Chin, Mike, 8.117
 Choosing and Using MRL Calibration
 Tapes, 8.49
 Clarke, Bob, 15.26
 CODEC:
 audio,
 DESKPRO computer, 8.149
 interfacing, ISA computer bus, 8.149
 key features, 8.148
 sigma-delta, 14.29-30
 decoder, 14.31
 encoder, 14.31
 features, 14.30
 voiceband, 14.30
 stereo,
 16-bit,
 parallel-port, 8.148
 serial port, 8.150
 multimedia and business audio
 applications, 8.147-151
 parallel-port interface, 8.151
 serial DSP interface, 8.150
 serial-port interface, 8.151
 Coleman, Brendan, 16.23
 Colloms, M., 8.40
 Colotti, James J., 16.23

Common-mode rejection ratio, see: CMRR
 Communications, signal computing applications, 18.1-42

Compact disc player:

- 20-bit 8X oversampled, THD+N performance, 8.139
- audio DAC, 8.140-141
 - electronics, 8.134-139
- first generation, reconstruction electronics, 8.135
- read electronics, 8.134
- second generation, 18-bit 8X

oversampled,

- reconstruction electronics, 8.135, 137
- third generation,
 - 18-bit 8X oversampled, antialiasing filter, 8.137
 - 20-bit 8X oversampled, reconstruction electronics, 8.138
- oversampling and filter design, 8.136

Computer, DESKPRO, CODEC, 8.149

Control/measurement, process diagram, 7.2

Converter:

- MASH, 14.31-33
- multi-bit, sigma-delta, characteristics, 14.34
- sigma-delta, summary, 14.34-35
- single-bit, sigma-delta, characteristics, 14.34

Copper microstrip, characteristics, 11.40

Cosier, G., 18.42

Counts, L., 1.92; 8.62

Coussens, P.J.M., 19.23

Crosstalk, 1.24-25

Curl, John, 8.99-100

D

DAC:

- 10-bit,
 - DDS modulator, 17.16-17
 - in DDS system, 17.13
 - low-glitch/high SFDR, 17.16
 - glitch impulse area, midscale waveform, 17.4
 - low-glitch, 17.13
 - low-glitch/high SFDR, 17.16
- 12-bit,
 - architecture, segmentation, 17.7-8
 - fullscale output, 17.8
 - midscale glitch impulse, 17.8
- 14-bit, 6.46-47
- 16-bit,
 - in CODEC, 14.30
 - multiplying, 3.9
- 18-bit,
 - audio,
 - block diagram, 8.140

key specifications, 8.143

segmentation, 8.143

dual, 8.136-137

20-bit,

- audio, 8.138
 - digital offset and segmentation, 8.145
 - key specifications, 8.146
 - THD+N performance, 8.139
 - THD+N versus frequency, 8.146

architectures, 8.140-146

audio,

- audio, reduction by digital offset, diagram, 8.144

compact disc player, electronics, 8.134-139

glitch,

- minimum signal-dependent, 8.142
- reduction by digital offset, 8.144-146
- reduction by segmentation, 8.142-143

BiMOS, current switch, 8.141

CMOS,

audio applications, 8.140-141

current-steering, 8.140-141

decoupling, 13.39

deglitching, 14.27

segmentation, 14.27

grounding, 13.38

high speed,

applications, 17.1

bipolar, architectures, 17.6

in DDS system, low-glitch/high SFDR, 17.14

deglitching with SHAs, 17.18-19

direct digital synthesis, 17.1

glitch impulse area, 17.3-5

definition, 17.3-4

effects, 17.5

waveforms, 17.3-4

glitch reduction, 17.6

ideal configuration, 17.7

segmentation, 17.7-8

graphics display systems, 17.1

harmonic distortion, 17.5

instrumentation, 17.1

maximum dynamic range design, 17.6-8

midscale glitch, 17.15

net glitch impulse area, 17.4-5

performance, 17.15

reconstruction,

output, 17.18-19

$\sin(x)/x$ frequency rolloff effect, 17.18-19

settling time, 17.2-3

definition, 17.2-3

- waveforms, 17.2
 - SFDR, 17.5
- multi-bit, sigma-delta, summary, 14.34-35
- RAMDAC, 17.1
- sigma-delta, 14.1, 26-28
 - analog smoothing filter, 14.29
 - concepts, 14.26
 - diagram, 14.28
 - modulator, 14.28
- VIDEODAC, 17.1
- voltage reference, 5.16
- Danyk, D., 8.99
- Data acquisitions system:
 - integrated,
 - advantages, 6.42
 - on chip, 6.41-49
 - programmability, 6.42
- Dattorro, J., 8.156; 14.36
- Davis, Gary, 8.156
- DDS system:
 - digital dither injection,
 - to increase SFDR, 17.17-18
 - to randomize quantization noise, 17.17-18
 - driving 10-bit DAC, 17.13
 - evaluation board, 17.13-14
 - flexible, diagram, 17.10
 - modulator, 17.16-17
 - phase accumulator system, 17.11
 - diagram, 17.11-12
 - SFDR, 17.12
 - simple, diagram, 17.9
 - wide dynamic range, 17.9-17
- Decimation, 14.10-13
 - discrete time signal, 14.11-12
- Del Signore, B.P., 14.36
- Demrow, Robert, 8.62
- Dickason, Vance, 8.117
- Diden, Jan, 8.100
- Dielectric absorption, charge retention, 4.4
- Difference amplifier:
 - video,
 - active feedback,
 - common-mode rejection ratio, 11.28
 - frequency response, 11.28
 - specifications, 11.28
- Digital audio:
 - applications, 8.125-140
 - components, 8.126
 - mixing, 8.127
 - performance specifications, 8.128
 - recording standards, 8.127
 - studio techniques, 8.125
- Digital conversion, intermediate frequency, undersampling, 15.9-21
- Digital filtering, 14.10-13
 - effects on shaped quantization noise, 14.10-11

- Digital receiver:
 - baseband sampling, 15.9-10
 - block diagram, 15.9-10
 - intermediate frequency sampling, 15.10-11
- Digital signal processing, see: DSP
- Diode clamp, leakage, bias current, 1.71
- Direct digital synthesis, see: DDS
- Doernberg, Joey, 16.23
- Dostal, Jiri, 8.92; 10.33; 11.43
- DSP, audio system, see: Digital audio
- DSP Applications Using the ADSP-2100 Family, 18.42
- Duff, David, 12.39
- Duncan, Ben, 8.40, 98-99

E

- Eckbauer, F., 14.36
- Edge connector, characteristics, 11.37
- Effective number of bits, see: ENOB
- EIA RS-170, black-and-white television specification, 11.13
- Electric motor:
 - ac induction, 19.3-6
 - dynamic model, 19.10
 - block diagram, 19.11
 - ac vector processor, 19.6-7
 - control,
 - importance, 19.5
 - nature, 19.5
 - types, 19.6
 - variable voltage variable frequency, 19.6-7
 - implementation, 19.7
 - control circuits, 19.1-23
 - dc permanent magnet, 19.4
 - GAMANA, 19.16-18
 - GAMANA GMCDS, 19.20
 - GAMANA VT, 19.18-20
 - limitations, 19.3
 - rotating magnetic field, 19.4
 - rotor flux, 19.4
 - types, 19.2
 - vector control, 19.1, 13
 - advantages, 19.7-8, 22
 - rotation coprocessor, 19.6-7, 9
 - type, 19.8-12
 - high performance dynamic control, 19.10-12
 - slip control, 19.8-9
 - vector processor, block diagram, 19.15
- Electric vehicle, vector control, 19.20
- Electromagnetic interference, see: EMI
- EMI/RFI:
 - noise,
 - filtering, 1.21-55
 - generation, 1.21-55
 - protection, 1.21-55

Engelhardt, E., 14.36
Erdi, George, 8.40, 98

F

Fair, David, 8.1, 147
Faraday Cage, 1.35
Faraday shield, 1.24-25, 35
 grounding, 1.35
Fast Fourier transform, see: FFT
Ferguson, Paul F. Jr., 8.156; 14.36; 15.40
Feucht, D.L., 1.92
FFT bins, average noise vs. broadband
 quantization noise level, 16.9-10
FFT testing:
 coherent, 16.12
 Mathcad routines, 16.20-22
 output, troubleshooting, 16.16-22
 QuickBasic routines, 16.17-19
 sinewave cycles,
 integral number, 16.11-12
 nonintegral number, 16.13
 software, windowing function, 16.15
Filter:
 antialiasing,
 effects on system dynamic range, 12.6
 Nyquist frequency, 12.6
 specifications, 12.6
 Butterworth, 12.6
 differential LC, noise reduction,
 13.40- 41
 elliptic, 12.6
 characteristics, 12.7
 sampling rate, 12.7-8
Finite impulse filter, 14.12
Finnie, Matthew, 19.1
First-order system, pulse and frequency
 response, 9.3
Fisher, J., 14.36
Fitchen, F., 8.17, 49
Flash converter:
 bit error rate, 12.38
 block diagram, 12.18
 comparator thermometer code output,
 12.18
 ENOB, 12.19
 equivalent input circuit, 12.19
 harmonic distortion, 12.19
 high speed, error sources, 12.17-21
 metastable comparator output, error
 codes, 12.34
 primary error sources, 12.21
 signal-dependent capacitance, 12.19
 SNR, 12.19
 total harmonic distortion, 12.21
Fleming, Tarlton, 15.39
Flett, Fred P., 19.1, 23
Frederiksen, Thomas M., 10.33; 11.43

Freeman, D.K., 18.42
Frequency-voltage converter:
 circuit, 1.88
 isolation device, 1.86-88
 linearity, 1.89
Fu, Dennis, 19.23

G

Galand, C., 18.42
Galo, Gary, 8.100
GAMANA:
 chipset/software development system,
 19.16-18
 motion development system, 19.16-17
 advanced motion control engine, 19.17
GAMANA GMCDs, computer-aided design
 package, 19.20
GAMANA VT: Vector Control Tutorial and
 Software Simulator, 19.23
GAMANA VT:
 microprocessor-based vector control,
 19.18-20
 rotor reference frame architecture,
 19.19
 software partitioning, 19.19
Ganesan, A., 8.156; 14.36
Garcia, Adolfo, 1.1, 93; 5.22; 7.1; 8.17,
 52, 62, 92
Garde, P., 8.117
Ghausi, M.S., 16.24
Gilbert, Barrie, 8.98; 15.26, 40
Gittleman, R., 8.98
Gold, Bernard, 16.24
Gratzek, Tom, 15.39
Gray, G.A., 16.24
Grey, Paul R., 1.92
Groshong, Richard, 15.39
Grounding, preferred circuitry, 13.39-40
Groupe Speciale Mobile, see: GSM
GSM system:
 baseband input/output port,
 block diagram, 18.36
 specifications, 18.36, 38
 baseband receive port,
 block diagram, 18.40-41
 for Japanese digital cellular
 telephone, 18.41
 specifications, 18.40-41
 for U.S. digital cellular telephone,
 18.40
 baseband transmit port,
 block diagram, 18.39
 specifications, 18.39
 for U.S. digital cellular telephone,
 18.39
 diagram, 18.26
 discontinuous transmission (DTX),
 18.26, 28-33

- functions,
 - comfort noise insertion, 18.29
 - silence descriptor, 18.29
 - voice activity detection, 18.28-29
 - mixed signal processor, DSP
 - architecture, benchmarks, 18.32
 - Pan-European digital cellular telephone system, 18.26-41
 - speech CODEC, 18.27-28
 - speech compression, 18.28
 - speech encoder, 18.27
 - linear predictive coding, 18.27
 - long term prediction, 18.27
 - regular pulse excitation, 18.27
 - speech encoder, 18.26
 - up/down conversion, 18.34-41
 - block diagram, 18.34
 - frequency/time allocations, 18.35
- H**
- Hallgren, B., 8.99
 - Hanning Window:
 - frequency response, 16.14
 - sidelobe attenuation, 16.15
 - time and frequency representation, 16.14
 - Harms, Wilfred F., 8.117
 - Harris, Frederick J., 16.23
 - Harris, Steven, 14.36
 - Haspeslagh, J., 18.42
 - Hauser, Max W., 14.36
 - Hayt, W.H., 1.92
 - Heise, B., 14.36
 - Hellwig, K., 18.42
 - Henry, Tim, 11.43
 - Higgins, Richard J., 16.24; 18.42
 - High accuracy circuit, RFI rectification, prevention, 1.55
 - High speed amplifier:
 - architecture, 10.2-6
 - current feedback, 10.6-7
 - equivalent circuit, 10.3
 - current feedback circuit, 10.2, 7
 - optimized unity-gain closed-loop buffers, 10.2
 - voltage feedback circuit, 10.3
 - loop gain, 10.3
 - High speed buffer amplifier, 10.22-25
 - High Speed Design Seminar (1990), 5.22; 9.15; 10.33; 11.43; 12.39; 13.48; 16.24
 - High speed signal:
 - accuracy considerations, 1.3
 - amplifier, selection criteria, 10.1
 - applications, dynamic ranges, 9.6
 - audio applications, 8.1-156
 - dynamic range, requirements, 9.6
 - error sources, and absolute accuracy, 1.4
 - impedance, 9.3-5
 - levels, 9.3-5
 - noise, 1.3; 9.3-5
 - precision sensor, error sources, 1.1-4
 - resolution, least significant bit weights, 1.1
 - S/N+D, 9.7
 - see also: Sensor, precision
 - sensor, output conditioning, 1.4-12
 - total harmonic distortion, 9.7-9
 - transmission,
 - coaxial cable connector, 11.38
 - edge connector, 11.37
 - impedance, 11.37-42
 - microstrip lines, 11.38-40
 - strip lines, 11.41-42
 - wire-over-ground plane, 11.38
 - High speed system:
 - applications, 9.1
 - design, 9.4
 - dynamic range, 9.5-6
 - comparisons, 9.7
 - definition, 9.6
 - impedance levels, 9.5
 - SFDR, 9.14
 - High-frequency system, dynamic range, comparisons, 9.7
 - Hill, Allen, 15.1, 9; 16.1
 - Hilton, Howard, 15.39
 - Hodges, David A., 16.23, 24
 - Hofer, Bruce, 8.62, 92
 - Hofmann, R., 18.42
 - Hogan, Steve, 8.17
 - Hoge, W., 8.17
 - Holman, Tom, 8.99
 - Howland circuit, cross-coupled, 8.85
 - HP Journal, 16.23
 - HP Product Note 5180A-2, 16.23
- I**
- IEC Magnetic Tape Sound Recording & Reproducing Systems, 8.49
 - IEC Publication 98 (1964), Amendment 4, 8.40
 - IEEE Standard for Performance Measurements of A/D and D/A Converters for PCM Television Circuits, 11.43
 - IEEE Trial-Use Standard for Digitizing Waveform Recorders, 16.24
 - In-amp, see: Instrumentation amplifier
 - Infinite impulse filter, 14.12
 - Ingle, Vinay K., 18.42
 - Input overvoltage:
 - characteristics, 1.57
 - conduction, types, 1.57
 - current limiting, 1.57
 - protection, 1.56-74

- Instrumentation amplifier:
input overvoltage, protection, 1.56-74
paralleling, precision line driver, 1.75
as preamp, in microphone, 8.13
precision line driver, stacked,
performance, 1.75
RFI rectification, 1.38, 40-41
reducing, 1.51-55
base-emitter bypassing, 1.53
capacitor by-pass, 1.52-53
filters, 1.51-52
other, 1.54
sensitivity, 1.37-42
stacked, transient response, 1.75
- Intermediate frequency signal:
aliasing, 15.13
sampling rate, 15.14
digital conversion,
bandpass techniques, 15.22-25
undersampling applications, 15.9-21
sampling, 15.9-10
- Intermodulation distortion:
calculation, 9.12
second- and third-order, 9.10-13
1dB compression point, 9.10
intercept points, 9.10-12
- Irons, Fred H., 15.39
- J**
- Jantzi, S.A., 15.40
Jenkins, A., 8.98
Jensen, Deane, 8.62, 92
Jones, Ralph, 8.156
Jung, Walter G., 1.93; 8.1, 17, 40, 52, 62,
92, 98-100; 10.33; 11.1, 3, 6-7, 12, 19,
24, 33, 35, 43
- K**
- Kampmann, F., 8.99
Kannenberg, W., 8.62
Kapoor, A., 8.98
Kaufman, M., 8.40, 92; 10.33; 11.43
Kaufman, Sid, 16.23
Kerr, Richard J., 17.20
Kester, W.A., 11.43; 16.24
Kester, Walt, 1.92; 8.1, 125; 15.26, 31;
16.1; 17.1
Kester, Walter A., 9.1, 15; 10.1; 11.1, 8,
12, 17, 24, 27, 37; 12.1; 13.1; 14.1; 15.1,
6, 9; 18.22
Kirsten, Jeff, 15.39
Kitchin, C., 1.92
Klonowski, P., 1.92
Koch, R., 14.36
Koonce, G.R., 8.117
Korn, G., 8.40
- Korn, T., 8.40
- L**
- Laker, K.R., 16.24
Lee, Hae-Seung, 16.23
Lee, Wai Laing, 8.156; 14.36
Lee, W.L., 8.156; 14.36
Line receiver:
balanced, high-precision, 1.76-79
precision, performance, 1.79
Lipshitz, S., 8.40
Look-up table, 15.9
Losmandy, B., 8.98
Lyons, Richard G., 15.39
- M**
- McCoy, R., 8.40
Macovski, Albert, 15.40
Mahoney, Matthew, 16.24
Mangelsdorf, Christopher W., 12.39
Marsh, Richard, 8.40, 99
Mathcad, FFT testing, windowing function,
16.15-16
Matsuya, Y., 14.36
Matsuzawa, A., 12.39
Measurement/control, process diagram, 7.2
Meehan, Pat, 16.23
Meraner, David J., 8.117
Meyer, Robert G., 1.92
Microcode, for interfacing 68HC11 with
AD771X family, 6.29-31
Microcontroller:
in digital signal conditioner, 7.6-9
built-in routines, 7.7
Microphone, preamplifier, See: Preamp,
microphone
Microstrip line:
capacitance, 11.39
dielectric thickness, 11.39
impedance, 11.40
Mid-frequency system, dynamic range,
comparisons, 9.7
Minimum 4-Term Blackman-Harris win-
dow, comparisons, 16.15
Mixed signal, CMOS, advantages, 2.2
Mixed Signal Design Seminar (1991), 4.8;
6.49; 13.48; 14.36
Mixed Signal Design Seminar (1992), 18.42
Mixed signal hardware multiplier, 19.6-7,
9-14
block diagram, 19.14
vector transformations, 19.13
Mixed signal processor:
DSP architecture, 18.30-31
analog input/output interface, 18.31
block diagram, 18.30

- GSM benchmarks, 18.32
 - specifications, 18.31
 - Mixed signal system:
 - circuit prototyping, 13.46-47
 - evaluation boards, 13.46
 - mounting components, 13.47
 - signal routing, 13.47
 - supply decoupling, 13.47
 - wiring, 13.46
 - signal routing, 13.42
 - Mixed-signal IC:
 - decoupling, 13.39
 - grounding, 13.38
 - Mobile radio:
 - analog, frequency division multiple access, 18.24
 - digital,
 - code division multiple access, 18.25-26
 - overview, 18.22-26
 - time division multiple access, 18.25-26
 - Modem:
 - CCITT standards, 18.11
 - chipset development kit, 18.20-21
 - definition, 18.8
 - full-duplex, 18.10
 - half-duplex, 18.10
 - modulation methods, 18.11
 - V.32,
 - block diagram, 18.13
 - characteristics, 18.12
 - integrated modem, 18.18-19
 - overview, 18.12-13
 - receiver, 18.16-17
 - block diagram, 18.16
 - compensation, 18.17
 - echo cancellation, 18.17
 - Viterbi decoding, 18.17
 - transmitter, 18.13-16
 - block diagram, 18.14
 - pulse-shaping filter impulse response, 18.15
 - signal constellation, 18.15
 - Modulator, higher order loop considerations, 14.16
 - Morley, Nick, 18.42
 - Morrison, Ralph, 1.92; 13.48
 - MOSFET transistor, voltage-controlled resistance, 2.3
 - Motchenbacher, C., 8.17, 49
 - Multiplexing:
 - analog switch, 2.22
 - charge coupling, dynamic settling noise, 2.16
 - diode protection, 2.7
 - principles, 2.1
 - Multistage converter, sigma-delta, noise shaping, 14.31-33
 - Multistage noise shaping, see: MASH
 - Murden, Frank, 15.39
- ## N
- Nahman, Norris S., 16.23
 - Nicholas, Henry T. III, 17.20
 - Noise:
 - ADC,
 - sigma-delta,
 - gain and filter variables, 6.9-10
 - noise optimizing, 6.12
 - cable, improper grounding, 1.14
 - EMI/RFI, 1.21-55
 - application circuit, 1.29-33
 - capacitively-coupled,
 - Faraday shield, 1.24-25
 - reducing, 1.24-25
 - circuit susceptibility, reduction, 1.34
 - common impedance,
 - power supplies, 1.24
 - reduction, 1.23-24
 - conducted, 1.23
 - coupling mechanisms, 1.21-23
 - capacitive, 1.22
 - impedance mismatch, 1.22
 - inductive, 1.22
 - electric field, 1.34-35
 - electromagnetic radiation, 1.36
 - Faraday shield, 1.35
 - field attenuator, 1.34-35
 - low-pass filter, 1.27
 - types, 1.28
 - magnetic field, 1.35
 - magnetically-coupled, reducing, 1.26-27
 - mutual inductance, 1.23
 - near-field interference, 1.24
 - crosstalk, 1.24-25
 - passive components, 1.27-29
 - reduction,
 - bandwidth limiting, 1.31
 - capacitor RTD as filter, 1.31
 - capacitors, 1.31
 - long cable, using resistors and capacitors, 1.32
 - RC filter, 1.30-31
 - using capacitor and strain gauge resistance, 1.33
 - shielding, review, 1.34-36
 - shielding and filtering, 1.29
 - sources, 1.22
 - system susceptibility, reduction, 1.33
 - Noise shaping:
 - first order, 14.8-9
 - second order, 14.8-9

NTSC:

- color generation, composite signal, 11.15
- color television specification, 11.13
- color video line, 11.13
- comparison with PAL, 11.15
- field timing diagram, 11.14
- signal characteristics, 11.15
- video signal, sync tip clamping, 11.33

Nyquist frequency, 16.6

- and antialiasing filter, 12.6

Nyquist sampling, quantization noise, 14.4**Nyquist's criteria, 12.2-3****O****Op amp:**

- active feedback, 11.29-32
 - basic topology, 11.29
 - characteristics, 11.30-34
 - closed loop connection, 11.30
 - instrumentation, gain, 11.31
 - video cable receiver/driver, 11.32
 - video loop-through connection, 11.33
- bipolar,
 - low distortion, 13.18
 - noise calculations, 13.20
 - specifications, 13.19
 - total harmonic distortion, 13.19
 - voltage noise, 13.19
- capacitive loading,
 - characteristics, 11.4
 - in-the-loop compensation, 11.6
 - internal compensation, 11.7-8
 - bandwidth, 11.8
 - noise gain, 11.2
 - stability, 11.2
- capacitor driving, pulse response, 11.11
- coaxial cable driving, pulse response, 11.10-11
- current feedback,
 - bandwidth, 11.2
 - capacitive loading, 11.5
 - characteristics summary, 10.21
 - closed loop gain equation, 10.8
 - CMRR, 10.17
 - comparison with voltage feedback, 10.7-21
 - decoupling,
 - harmonic distortion, 10.16
 - pulse response, 10.17
 - distortion, 10.11
 - equivalent circuit, 10.7
 - gain and phase response, 10.9
 - gain-of-two, 10.11
 - inverting input, stray capacitance, 10.18
 - inverting mode transfer function, 10.7-8

- open-loop series, 11.5
- PSRR, 10.17
 - transimpedance open loop gain, 10.6-7
- current paths, 1.61
- dc model, 10.27-29
- device/topology distortion, 8.70-73
- diffused resistors, 1.60
- driver noise, reduction, 15.5
- dual,
 - high CMRR, 1.77
 - high-precision balanced line driver, 1.76-79
 - in paralleled output line driver, 8.75-77
 - circuit, 8.76
 - THD+N versus frequency, 8.76
 - precision line receiver, 1.77
 - large signal transient response, 1.78
 - performance, 1.79
 - RFI rectification, 1.41
- feedback network, equivalent circuit, 1.50
- FET input, single supply, features, 1.11-12
- gain-bandwidth product, 10.4
- high speed,
 - characteristics, 10.14
 - comparison, 10.7-21
 - dynamic performance, 13.2
 - gain-of-two, 10.10
 - comparison, 10.11
 - inverting vs. noninverting, performance, 10.15
 - level shifting, 10.29-32
 - noise models, 10.26-27
 - null pins, 10.32
 - offset voltage, 10.32
 - printed circuit layout, guidelines, 10.15
 - prototype layout, 10.19-20
 - RMS output noise estimation, 10.27
- input overvoltage,
 - built-in protection, 1.72
 - characteristics, 1.58
 - curve tracer, 1.59
 - diode clamp, leakage, bias current, 1.71
 - effects, 1.68
 - limit, series resistor, 1.68
 - no input resistors, 1.62
 - protection, 1.56-74
 - diode clamp, 1.69-70
 - resistors, 1.69
 - zener diode breakdown, 1.66
- input protection diodes, 1.60-61
- inverting,
 - capacitive loading, 11.6

- level shifter, 10.30
 - low distortion drive amplifier, 15.3-4
 - N-type substrate, 1.65
 - noise resistance, 8.5
 - non-unity gain, inverting mode, 10.6
 - noninverting,
 - capacitive loading, 11.6
 - level shifter, 10.31
 - offset, effect on system accuracy, 1.2
 - offset voltage, model, 10.28
 - output, charge coupling, dynamic settling noise, 2.16
 - output circuit, induced rectification, reducing, 1.51
 - output impedance, rectification sensitivity, 1.49
 - output noise spectral density, 15.4
 - p-channel JFET input, 1.63-64
 - RFI rectification, 1.38, 40-41
 - reducing, 1.48-55
 - low-pass filter, 1.48
 - sensitivity, 1.37-42
 - series resistor, effects, 1.70
 - single, RFI rectification, 1.40
 - single supply, data acquisition system, FFT output, 6.39
 - transimpedance, see: Op amp, current feedback unity gain bandwidth,
 - frequency, 10.4
 - noise gain, 10.5
 - signal gain, 10.5
 - video line driver, 11.19
 - voltage feedback,
 - capacitive loading, 11.3
 - characteristics, 10.14, 21
 - closed loop gain equation, 10.8
 - comparison with current feedback, 10.7-21
 - distortion, 10.11
 - equivalent circuit, 10.3
 - frequency response, 10.12
 - gain-of-two, 10.11
 - inverting mode transfer function, 10.7-8
 - inverting vs. noninverting, 10.12
 - log-log Bode plot, 10.4
 - noise gain, 10.4
 - open-loop series, 11.3
 - settling time, 10.13
 - signal gain, 10.4
 - as unity-gain buffer, 10.23
 - wideband, 9.9
 - wideband, capacitive loading, 11.1-8
 - wideband buffer, voltage reference, 13.23
 - zener diode, 1.66
 - Opto-isolator:
 - characteristics, 1.85
 - construction, optical fibers, 1.85
 - with frequency-voltage and voltage-frequency converters, 1.89
 - function, 1.81
 - higher voltage barrier, 1.85
 - Otala, Matti, 8.98
 - Ott, Henry W., 1.92; 8.62; 13.48
 - Oversampling:
 - antialiasing filter requirements, 14.3
 - benefits, 14.4
 - quantization noise, 14.4
 - Overvoltage:
 - effects, 1.68
 - recovery time, 12.32
- ## P
- PAL:
 - color subcarrier, 11.14
 - comparison with NTSC, 11.15
 - signal characteristics, 11.15
 - Pandit, Shrikant, 19.23
 - Parasitic latchup, 2.4-8
 - Parasitic SCR latchup, 2.4-8
 - mechanism, 2.4-5
 - Parzefall, F., 14.36
 - PCB:
 - edge connections, 13.43
 - layout, signal routing, 13.43
 - multiple ground pins, 13.44
 - socket prohibition, 13.44-45
 - Pease, Robert A., 13.48
 - Personal sound system:
 - architecture, 8.153
 - audio chipset, 8.152-155
 - PGA:
 - accuracy, 3.8-9
 - applications, 3.2
 - bias current error, 3.8
 - binary gain,
 - accuracy, 3.10
 - performance, 3.11
 - design considerations, 3.4-5
 - differential input, circuit, 3.13
 - dynamic circuit range, 3.3
 - gain programming, 3.3
 - instrumentation, single supply, 3.13-14
 - location, 3.2
 - low noise, 3.7
 - monolithic,
 - software programmable, 3.6
 - characteristics, 3.6
 - on resistance, 3.4-5
 - software programmable, 3.12
 - variable gain, 3.2
 - Phase jitter, definition, 12.29
 - Phased-array ultrasound system:
 - beamforming, 15.33-34
 - analog, 15.34

- digital, 15.34
 - gain, 15.35
 - Phonograph, preamplifier, See:
 - Preamp, phonograph
 - Photodetector:
 - single supply, 1.10-12
 - circuit, 1.11
 - Pilko, G., 8.99
 - Pohlmann, Ken, 8.156
 - Pontis, George, 8.92
 - Power supply:
 - switching-mode,
 - characteristics, 13.35
 - decoupling, 13.36-37
 - preferred circuitry, 13.39-40
 - differential LC filter, 13.40-41
 - external filter, 13.36
 - Faraday shields, 13.35
 - filtering, 13.35-36
 - ground planes, 13.37-38
 - grounding, preferred circuitry, 13.39-40
 - noise, 13.35
 - single-point ground, 13.37
 - star ground, 13.37
 - diagram, 13.38
 - Power supply rejection ratio, see: PSRR
 - Preamp:
 - audio, RIAA, 8.18-40
 - general considerations, 8.1-2
 - microphone, 8.1-17
 - electret microphone interface, 8.4-5
 - single-ended single-supply high-impedance, 8.2-4
 - transformer-coupled low-impedance, 8.5-10
 - circuit, 8.6
 - THD+N versus frequency, 8.8-9
 - transformerless input low-impedance, 8.13-16
 - circuit, 8.13
 - gain, 8.14
 - radiofrequency interference, 8.15
 - THD+N versus gain, 8.15-16
 - very low noise transformer coupled, 8.10-12
 - circuit, 8.10
 - gain, 8.11
 - THD+N versus frequency, 8.12
 - phonograph, 8.1
 - RIAA, 8.18-40
 - active feedback, 8.23-31
 - ac coupled, 8.31
 - accuracy, 8.30
 - dc coupled, 8.28
 - equalization curve, 8.18
 - equalizer,
 - capacitors, 8.23
 - circuit topologies, 8.23-24
 - manufacturing tolerance, 8.22
 - networks, 8.21-23
 - resistors, 8.23
 - selection tolerance, 8.22
 - topology-related parasitics, 8.22
 - hybrid-equalized differential input servo-controlled, 8.34-37
 - accuracy, 8.36
 - idealized frequency response, 8.20
 - low frequency rolloff, 8.19
 - passively equalized, 8.32-34
 - accuracy, 8.34
 - circuit, 8.32
 - RIAA,
 - bipolar-input, 8.29
 - equalizer,
 - active feedback, 8.24
 - amplification, 8.24-25
 - FET-input, 8.29
 - hybrid equalized, 8.27
 - moving coil, 8.37-39
 - single-ended, gain, 8.38
 - passively equalized, 8.26
 - tape, 8.1, 41-49
 - circuit, 8.43
 - optimizing, 8.47-48
 - equalizer, scaling coefficients, 8.46
 - playback, 8.41-43
 - post-emphasis, 8.41
 - circuit, 8.45
 - time constants, 8.44
 - "two time constant" design, 8.43-46
 - very large time constant, 8.46-47
 - Precision line driver, paralleling amplifiers, 1.74-76
 - Precision signals, transmitting, noisy environment, 1.74-79
 - Printed-circuit board, see: PCB
 - Proakis, John G., 18.42
 - Programmable gain amplifier, see: PGA
- Q**
- QuickBasic, FFT testing, windowing function, 16.15
- R**
- Rabiner, Lawrence, 16.24
 - Radar receiver, SFDR, 15.15
 - Radio frequency interference, see: RFI
 - Raganathan, V.T., 19.23
 - Ramirez, Robert W., 16.23
 - Random-number generator, 15.7
 - Rebold, T.A., 15.39

- Reidy, John, 16.23
 Remote sensor, input protection, 1.13-36
 Resistor, series, effects, 1.70
 Resistor temperature detector, see: RTD
 RFI rectification:
 analytic approach, 1.42-47
 BJT-input devices, 1.42-47
 analysis, 1.47
 definition, 1.37; 10.18
 FET-input devices, 1.42-47
 analysis, 1.47
 HF modulation, 1.43
 high accuracy circuits, prevention, 1.55
 input-stage, sensitivity, 1.37-55
 instrumentation amps, 1.39
 observations, 1.39
 op amp,
 reducing, 1.48-55
 low-pass filter, 1.48
 sensitivity, 1.42
 versus BJT, 1.46
 RGB to NTSC/PAL encoder, diagram, 11.16
 RIAA Standard Recording and Reproducing
 Characteristic, Bulletin E1, 8.40
 Rich, Alan, 1.92; 8.92
 Risetime, and bandwidth, 9.2-3
 Riskin, Jeff, 8.62
 Rose, John F., 15.39
 Rosso, M., 18.42
 RTD:
 amplifier, single supply linearized, 1.9-10
 as source of cable noise, 1.14-15
 experiments, 1.14-15
 Ruscak, Stephen, 15.39
- S**
- Sallaerts, D., 18.42
 Sample and hold amplifier, see: SHA
 Sampling clock generation, 13.32-34
 Sampling rate:
 frequency versus signal bandwidth, 15.12
 minimum, antialiasing, 15.11
 Samuelli, Henry, 17.20
 Schoenwetter, Howard K., 16.23
 Schottky diodes, 13.29
 Schreier, R., 15.40
 Schweber, Bill, 18.1
 SECAM, color subcarrier, 11.14
 Sensor:
 precision, signal conditioning, 1.4-12
 signal conditioning,
 high impedance transducer, 1.5
 low impedance low voltage transducer, 1.5
 SFDR, definition, 9.13
- SHA:
 application, 4.1
 capacitor droop, 4.3-6
 DAC deglitcher, 17.18-19
 dielectric absorption, 4.4-5
 dynamic performance,
 characteristics, 4.2
 feedthrough, 4.3
 high accuracy, circuitry, 4.1-8
 hold capacitor,
 accuracy, 4.5
 low dielectric absorption, 4.4
 low leakage, 4.4, 6
 noninverting, guard shield, 4.6
 performance, 15.16
 precautions, 4.2
 settling time, 4.3
 track and hold circuit, 4.3
 virtual ground, guard shield, 4.7
 Shannon's information theorem, 12.2-3
 Sheingold, Dan, 1.92; 16.23
 Shielding:
 EMI/RFI,
 field attenuator, 1.34-35
 review, 1.34-36
 Sigma-delta converter:
 decimation, 14.1-2
 digital filtering, 14.1-2
 noise shaping, 14.1-2
 oversampling, 14.1-4
 Signal computing:
 applications, 18.3
 audio chipsets and algorithms, 8.152-153
 communications applications, 18.1-42
 digital telephone answering machine, 18.21-22
 DSP, 18.1-2
 DSP data compression, 8.154
 DSP-based signal processing, 8.152-153
 hardware, 18.3-4
 analog input/output interface, 18.4
 block diagram, 18.4
 digital signal processor, 18.4
 signal processing algorithm, 18.4
 industrial applications, 18.6-8
 business model, 18.7
 modem, high performance, 18.8-17, 20
 signal computing applications, realtime, 18.1-2
 software,
 layered structure, 18.5
 open architecture, 18.5-6
 Signal conditioner:
 analog,
 circuit, 7.3
 design, 7.2-3
 digital,

- analog linearization, 7.43-45
- analog offset compensation, 7.38-40
- application,
 - thermocouple, 7.21-26
 - cold-junction compensation, 7.21-24
 - temperature sensor, 7.22
 - thermistor, 7.22
- block diagram, 7.5
- calibration, 7.19-20
 - asynchronous port, 7.20
- characteristics, 7.3-4
- chopper stabilized amplifier, 7.38
- circuit, 7.6
 - algorithms, 7.38-51
- cold-junction compensation, 7.48-50
 - analog, 7.49
 - block diagram, 7.49
 - digital, 7.49
- configuration,
 - asynchronous port, 7.15
 - hard-wired, 7.16
 - software-driven, 7.16
- conversion mode, 7.17-19
 - continuous, 7.17
 - rate, 7.18-19
 - triggered, 7.17-18
- device, 7.4-5
- digital linearization, 7.45-48
 - piecewise linear approximation, 7.45-47
 - segmented polynomial splines, 7.46-48
 - single polynomial, 7.46-47
- digital offset compensation, 7.39
- digital span calibration, 7.40-41
- embedded microcontroller, 7.6-9
 - control software, 7.6-7
- evaluation board, 7.36-37
 - circuit, 7.37
- features, 7.5
- gain greater than unity, correction, 7.42-43
- industrial applications, 7.30-34
 - equivalent circuit, 7.32
 - hostile environment, 7.31
 - isolated thermocouple, 7.31
 - overvoltage protection, 7.33-34
- layout, 7.35
- multiple gain, compensation, 7.42
- power supply, 7.34-35
 - switching regulator, 7.34-35
- RTD applications, 7.28-30
 - configuration, 7.29
 - issues, 7.30
- RTD lead resistance compensation, 7.50-51
- RTD linearization, 7.43
- sensor interfaces, 7.7-8
 - span and offset compensation, 7.40
 - temperature drift compensation, 7.7
 - thermocouple linearization, 7.44
 - voltage input,
 - configuring, 7.26-28
 - issues, 7.28
 - digitizing, 7.1-52
- Signal port, device, 18.18-20
- Signal transmission:
 - differential,
 - balanced driver and receiver, 11.24
 - floating driver and single-ended receiver, 11.24-25
 - noise rejection, 11.25
 - single-ended driver and differential receiver, 11.24-25
 - high speed, differential, 11.24-26
- Signal-to-noise plus distortion, see: S/N+D
- Signal-to-noise ratio, see: SNR
- Signals, precision, transmitting, noisy environment, 1.74-79
- Silicon controlled rectifier, see: SCR
- Sin(x)/x frequency rolloff effect, 17.18-19
- Sluyter, R.J., 18.42
- Small, R.H., 8.117
- Snelgrove, W. Martin, 15.40
- SNR, high speed signal, 9.7-9
- Socket:
 - disadvantages, 13.44-45
 - precautions, 13.44-45
- Sodini, C.G., 8.156; 14.36
- Sokal, N., 8.98
- Southcott, C.B., 18.42
- Speaker:
 - crossover, 8.101-124
 - impedance, 8.103
- Spurious free dynamic range, see: SFDR
- Star ground, diagram, 13.38
- Stephens, M., 8.17
- Steyskal, Hans, 15.39
- Stout, D., 8.40, 92; 10.33; 11.43
- Strain-gauge bridge, voltage reference, 5.14-15
- Strip line:
 - capacitance, 11.41
 - line width and spacing, 11.41
 - spacing, 11.42
 - transmission, 11.41
- Sulzer, Mike, 8.99
- Swanson, E.J., 14.36
- Sync stripper, composite sync, 11.35-36
- Sync tip dc restorer, 11.33-35
 - circuit, 11.34
 - video, 11.33-35
- System layout, signal routing, noise minimizing, 13.42
- System-offset calibration, 6.21

T

Tant, M.J., 16.24
 Tape, preamplifier, See: Preamp, tape
 Tape preamplifier, see: Preamp, tape
 Telephone answering machine:
 digital,
 design kit, 18.21-22
 features, 18.22
 Telephone channel:
 block diagram, 18.9
 imperfections, 18.9
 voiceband,
 digital signal modulation, 18.10
 echo, 18.10
 Television:
 color processing,
 composite signal, 11.14-15
 luminance, 11.14-15
 monochrome, specification, 11.13
 NTSC system, composite color signal,
 11.14-15
 picture, frame fields, 11.13
 standard interlace format, 11.12
 Temperature, sensor, digital signal
 conditioner application, 7.21-26
 Temperature sensor/controller:
 block diagram, 1.7
 circuit temperature control, 1.8
 signal conditioning, 1.7-8
 TGA:
 compensation ramp slope, in ultrasound
 burst, 15.36
 per-patient calibration, 15.33
 transducer output, 15.33
 in ultrasound system, 15.32
 ultrasound system, control voltage,
 15.36
 THD+N, see: Total harmonic distortion plus
 noise
 THD, see: Total harmonic distortion
 Thermocouple:
 detector, resistors, 7.26
 digital signal conditioner application,
 7.21-26
 measuring, 7.25
 Thermometer, amplifier, single supply
 RTD, 1.9
 Time gain amplifier, see: TGA
 Todd, C., 8.17
 Total harmonic distortion:
 definition, 9.8
 from signal-dependent input
 capacitance, 12.21
 high speed signal, 9.7-9
 Total harmonic distortion plus noise,
 definition, 9.8
 Transducer:
 accuracy, 1.81

connections, 6.16

isolation, 1.80-91

digitizing, 1.90

summary, 1.91

uses, 1.80

Transmission line:

coaxial cable connector, 11.38

edge connector, 11.37

impedance, maintenance, 11.37-42

microstrip lines, 11.38-40

strip lines, 11.41-42

wire-over-ground plane, 11.38

Tukey, J.W., 16.23

U

Ultrasound system:

block diagram, 15.31-32

imaging, 15.32

interaction with human tissue, 15.32-38

phased array, see: Phased-array

ultrasound system

preamplifier,

low noise, 15.37

performance, 15.38

TGA, 15.32

compensation ramp slope, 15.36

wide dynamic range, 15.31-38

Undersampling, theory, 15.10, 12

V

Variable gain amplifier, see: VGA

Vary, P., 18.42

VCA:

analog multiplier, 15.27

gain, 15.28

exponential amplifier, 15.28

frequency response, 15.27

Vector control:

advantages, 19.22

applications, 19.21

chipsets/algorithms, 19.20-21

Vector rotation coprocessor, 19.6-7, 9-14

VGA:

4-quadrant multiplier, block diagram,
15.26

wide dynamic range, 15.26-31

Video image:

frame fields, 11.13

interlacing, 11.12

Video line driver, 11.19-23

2:1 multiplexer,

channel switching time, 11.21

off channel feedthrough, 11.21

circuit,

2:1 multiplexer, 11.20-21

4:1 multiplexer, 11.22

- disable mode, 11.20
 - good performance, 11.19
 - high performance, 11.20
 - very high performance, 11.22-23
 - Video line receiver:
 - active feedback amplifier, 11.27-33
 - circuit, 11.26
 - differential, 11.27
 - Video signal:
 - basic principles, 11.12-13
 - composite,
 - chrominance information, 11.17
 - color intensity, 11.17
 - color saturation, 11.17
 - differential gain, 11.17
 - differential phase, 11.17
 - differential gain and phase, 11.17-19
 - measurement, 11.18
 - processing, 11.12-36
 - sync stripping, 11.35-37
 - Video sync stripper, circuit, 11.35-37
 - Video sync tip dc restorer, 11.33-35
 - Viterbi decoding, 18.17
 - Voice encoding, standards, 18.27
 - Voiceband signal port:
 - input/output, 18.33
 - DSP processor, 18.32-33
 - sigma-delta CODEC, 18.33
 - Voltage reference:
 - accuracy, 5.1
 - ADC, sigma-delta, 6.17-19
 - bandgap, 5.2-3
 - buried zener, 5.2-3
 - characteristics, 5.4
 - drift, 5.4-7
 - accuracy, 5.6-7
 - driving ADC and DAC, 5.16
 - high resolution system, 5.1-22
 - load transients, bypass capacitor, 5.18
 - long-term stability, 5.1
 - low noise discrete bandgap, 5.9-10
 - circuit, 5.10
 - design equations, 5.10
 - performance, 5.10
 - low power high output, 5.13-15
 - noise, 5.1, 7-8; 6.18-19
 - limiting bandwidth, 5.7-8
 - output trimming, 5.4-5
 - stability, large capacitive loads, 5.19
 - for strain-gauge bridge, 5.14-15
 - temperature effects, 5.1
 - ultra low noise, 5.11-12
 - circuit, 5.11
 - filter, 5.11
 - loading and drift, 5.12
 - low pass filter, 5.12
 - unlimited capacitive load, characteristics, 5.19
 - very heavy load, 5.13-22
 - buffer, 5.13
 - drift, 5.13
 - Voltage-controlled amplifier, see: VCA
 - Voltage-frequency converter:
 - characteristics, 1.87
 - charge-balance, 1.86-87
 - isolation device, 1.86-87
 - linearity, 1.89
- ## W
- Wainwright Instruments, Inc., 13.48
 - Waltman, Ron, 12.39
 - Weaver, Lindsay A., 17.20
 - Webb, Richard C., 15.39
 - Weeks, Pat, 16.23
 - Weems, David B., 8.117
 - Welland, D.R., 14.36
 - White, D, 8.99
 - Whitmore, Jerry, 2.1
 - Whitney, Dave, 8.98; 11.1, 12, 33, 35
 - Wideband noise, quantization noise randomization, 15.7
 - Wideband signal, fidelity, measures, 9.2
 - Williams, Jim, 13.48
 - Windowing function, Hanning Window, 16.13
 - Wireless Communications Symposium, Technical Papers (1993), 18.42
 - Witte, Robert A., 9.15
 - Wong, James, 1.1; 2.1; 4.1; 5.1
 - Woodward, Charles E., 12.39
 - Wooley, Bruce, 14.36
 - Wurcer, Scott, 8.40, 49, 62, 92
- ## X
- X-AMP, 15.28
 - dual exponential amplifier, features, 15.29-30
 - gain, from control voltage, 15.29
 - noise, 15.31
 - operation, 15.29-31
 - single channel, 15.28
- ## Z
- Zener diode, breakdown, 1.66
 - Zeoli, G.W., 16.24
 - Zobel network, 8.103-104
 - Zumbahlen, Hank, 8.1, 101, 117

ANALOG DEVICES PART INDEX

A

- AD1B60, 7.1-52
- AD20msp500-Series, 18.19-21
- AD20msp614, 8.152-155
- AD20msp700, 18.21
- AD28msp01, 18.18-20
- AD28msp02, 14.29-30; 18.32-33
- AD2S80A, 19.13, 17
- AD2S100, 19.6-7, 9-14, 16-21
- AD2S110, 19.12-14
- AD202, 1.84
- AD203, 1.84
- AD204, 1.84
- AD208, 1.84
- AD210, 1.82-84
- AD365, 1.54
- AD521, 1.54
- AD522, 1.54
- AD524, 1.53, 71-72
- AD526, 3.6-7
- AD574, 4.6
- AD580, 6.36; 13.5
- AD581, 5.4
- AD584, 5.4
- AD586, 13.21-23
- AD587, 5.7-8, 11-12; 13.21
- AD588, 1.14, 18; 5.9-10
- AD589, 1.33
- AD590, 1.32
- AD592, 1.31, 32; 7.22
- AD598, 6.38
- AD600, 15.28-31, 35, 37
- AD602, 15.28-31, 35, 37
- AD620, 1.32-33, 39, 53, 83-84
- AD621, 1.74-75
- AD624, 1.32, 53
- AD625, 1.39-40, 53; 3.11-12; 8.34-35
- AD626, 1.53, 72; 5.15
- AD645, 1.40
- AD650, 1.86-89
- AD676, 13.14-18, 20-21, 21, 26-27; 14.18
- AD677, 6.40; 13.16-18, 21, 28; 14.18
- AD679, 12.25-26
- AD680, 1.32; 5.4, 15; 6.36; 7.37; 14.21
- AD705, 1.40; 8.94-97
- AD706, 8.10
- AD707, 13.4
- AD708, 1.41, 76-77; 13.5
- AD711, 1.40, 63; 8.55, 93, 95, 123
- AD712, 1.41, 63; 8.37, 55, 93; 14.21
- AD713, 8.93
- AD720, 11.16-17
- AD741, 13.29
- AD743, 1.40
- AD744, 1.40; 8.35, 37, 39, 55, 66, 81, 93; 13.14
- AD745, 8.33, 43, 45, 47-48
- AD746, 1.41; 8.55, 93
- AD776, 6.33, 40; 13.28; 14.16-21
- AD780, 5.4, 18-21; 6.19, 26, 35-36; 13.14, 21-23
- AD797, 1.40; 3.7-9; 5.11-12; 6.11; 8.10-12, 37-39, 63, 77-78, 123; 13.18-20; 15.38
- AD810, 8.63; 11.20-22
- AD811, 8.12, 39, 55, 63-64, 79-82, 87; 11.5, 22-23, 34, 36; 15.26-27
- AD817, 8.63, 68, 72; 11.7-8
- AD818, 8.63, 72; 11.7, 19, 26
- AD820, 1.10-12; 6.34, 39; 8.2-5, 32, 35, 37, 94-96
- AD822, 8.2-5, 95
- AD826, 11.7
- AD827, 1.41; 11.7; 13.14
- AD828, 11.7
- AD829, 1.40; 8.63, 66, 68
- AD830, 11.27-33, 29-32
- AD834, 15.26-27
- AD840, 8.63
- AD845, 1.40; 8.29, 63, 66-67, 72, 79, 87, 89-90; 10.31-32; 11.3-5; 13.14, 16, 20-21, 23
- AD846, 8.63
- AD847, 8.63, 68, 123; 11.7-8; 13.14
- AD848, 11.7
- AD849, 11.7
- AD872, 9.14; 12.30-31; 13.8-9
- AD1382, 13.24
- AD1385, 13.24-26
- AD1674, 4.6-7
- AD1848, 6.33; 8.4, 147-151, 152-153
- AD1849, 6.33, 40; 8.4, 147-151
- AD1861, 8.140-143
- AD1862, 8.138, 144-146
- AD1865, 8.136-137
- AD1876, 6.40
- AD1878, 6.33, 40; 8.128
- AD1879, 6.33, 40; 8.128-133; 13.28; 14.1, 16, 22-25, 31-32
- AD7001, 18.37-38
- AD7002, 18.35-36
- AD7008, 17.16-17
- AD7010, 18.41
- AD7011, 18.38-39
- AD7013, 18.40
- AD7502, 3.12

SYSTEM APPLICATIONS GUIDE

AD7701, 6.40
AD7703, 6.40
AD7710, 3.14; 5.20; 6.1-4, 8-14, 16,
18, 20, 22, 25, 33, 40
AD7711, 6.1-4, 33, 40
AD7712, 6.1-4, 33, 40
AD7713, 6.1-4, 33, 40
AD7716, 6.47-48
AD7846, 3.9-10
AD7868, 6.46
AD7869, 6.46-47
AD7872, 6.40
AD7874, 19.17-18
AD7880, 5.15; 6.33
AD7883, 6.33, 36-38
AD7884, 13.11-12, 12-14, 21, 26-27;
14.18
AD7885, 13.12, 12-14, 21; 14.18
AD7890, 6.33, 40, 43-44
AD7891, 6.33
AD7892, 6.33
AD7893, 6.33, 40-41, 44-45
AD9002, 12.37-38; 15.20-21
AD9014, 9.5; 12.14-15; 15.1-5, 16,
18; 16.10
AD9020, 13.2
AD9022, 12.10-12, 24-25; 15.14-15,
19; 16.1-2, 15-16
AD9028, 12.20; 13.2
AD9032, 13.9
AD9038, 12.20; 13.2
AD9040, 12.23-24; 15.35
AD9048, 13.6-7
AD9058, 12.19; 13.3-6
AD9060, 13.2; 15.21-22
AD9100, 15.15-19; 17.18
AD9101, 15.16, 19-22; 17.18
AD9617, 10.9-12, 15-20; 11.9-11;
13.2, 4, 31; 15.4-5
AD9618, 13.5
AD9620, 10.23-25
AD9621, 10.13-14
AD9622, 9.8-9, 11-12; 10.10-15, 10-16
AD9623, 10.13-14
AD9624, 10.13-14
AD9696, 13.34
AD9712B, 17.7-8, 18
AD9713B, 17.8, 13-14, 18
AD9720, 17.4-5, 15-16, 18
AD9721, 17.13, 15-16, 18
AD9955, 17.11-13, 15-16
AD96685, 13.34
ADAT-DSI01, 18.19-21
ADC-170, 6.40-41
ADDS-CSDK-100, 18.21-22
ADG411, 2.19
ADG412, 2.16; 3.7-8
ADG511, 2.14, 17, 19; 3.13-14; 6.38

ADG512, 2.14; 6.38
ADLU-EUP01, 8.155
ADLU-EUP02/-Q, 8.154
ADMK-100, 18.20-21
ADMK-610, 8.154
ADSP-21msp50, 18.30-31
ADSP-2100 family, 8.149
ADSP-2101, 8.150; 13.26-28; 14.31;
18.16; 19.17-20
ADSP-2105, 6.27; 8.150; 14.31;
19.17-18
ADSP-2111, 8.150; 14.31
ADSP-2115, 8.150, 152-153
ADSP-2116, 18.16
AMP-01, 1.39-40, 53
AMP-02, 1.39, 54, 71-72
AMP-03, 1.54, 72
AMP-04, 1.9, 31, 39-40, 54; 3.13-14;
5.14
AMP-05, 1.54

B

BUF-03, 8.63-64; 10.22-23
BUF-04, 8.55, 63-64, 79-81

D

DAC-8412, 19.17-18

M

MAT-04, 5.9-10

O

OP-07, 1.1-2
OP-20, 1.40
OP-27, 1.40, 61-62, 68-69; 8.7, 29;
13.22-23
OP-37, 8.7, 33, 43, 47-48
OP-41, 8.95
OP-42, 1.40, 63-64; 8.69; 11.6
OP-80, 1.40
OP-90, 1.40, 72, 86; 5.14; 6.34
OP-97, 8.94-97
OP-160, 11.7
OP-177, 1.2-3, 31, 32-33, 40, 59-61,
64; 2.25; 5.10
OP-200, 1.40, 41
OP-213, 1.6, 14, 18, 41, 66-67,
69-70; 2.16; 3.9-10; 6.11, 34
OP-249, 1.41; 8.37, 55, 93
OP-270, 8.7, 29
OP-275, 1.41; 8.3, 6-8, 9, 13, 30-31,
55, 59, 61, 63, 70-76, 83-84, 133;

14.25
OP-282, 1.41, 63
OP-290, 1.41; 6.34
OP-295, 1.9, 41, 64-66; 6.34, 36, 38
OP-297, 1.40, 41
OP-470, 8.7
OP-490, 6.34

R

REF-01, 1.31
REF-03, 1.31; 6.36
REF-43, 1.9, 31, 86; 5.4; 6.36
REF-195, 1.6; 5.4, 13-15

S

SSM-2015, 8.16
SSM-2016, 8.16
SSM-2017, 8.13, 15-16, 37
SSM-2131, 8.29, 33, 55, 63
SSM-2134, 8.6-9, 29
SSM-2135, 8.2-4
SSM-2139, 8.32-33, 43, 47-48, 55
SSM-2141, 1.72; 8.55-56, 59, 61;
11.24
SSM-2142, 8.85-86; 11.24
SSM-2143, 1.72; 8.55-56; 11.24

T

TMP-01, 1.7-8, 85-86

