

インターフェース セレクション・ガイド



アナログ・デバイセズのインターフェース・ソリューションをお選びください!

このガイドには、アナログ・デバイセズと旧リニアテクノロジーの両方のインターフェース・ソリューションを収録しています。統合されたポートフォリオでは、フィールド・バスとペリフェラル通信から、バッファ、アクセラレータ、マルチプレクサなどの I²C 全般、IO リンク・トランシーバまで、幅広いソリューションを提供しています。

アナログ・デバイセズのインターフェース・デバイス向け設計ソリューションには、キーパッド・コントローラ、レベル変換器、高電圧保護製品(チャンネル保護、故障保護、過電圧保護)、ラッチアップ・プルーフ・スイッチとマルチプレクサがあります。

旧リニアテクノロジーのインターフェース製品には、最速データ・レート、高ノード数、低電圧電源に容易に対応できる幅広い業界標準通信デバイスがあります。長距離通信を可能にする RS-485 トランシーバや、チップ間通信を向上する I²C/SMBus デジタル・インターフェース・デバイスを用意しています。

アナログ・デバイセズはデータ伝送の課題を解決し、インターフェースをコンパクトで信頼できるソリューションとして提供します。

幅広いアプリケーション

アナログ・デバイセズの革新的なインターフェース・ソリューションは 10 年以上に渡り、以下のようなアプリケーションで使用されています。

- ▶ プロセス制御
- ▶ モーター駆動
- ▶ 工業用フィールド・バス
- ▶ 計測器
- ▶ 通信インフラストラクチャ
- ▶ 車載システム
- ▶ 太陽光／風力エネルギー
- ▶ 電源／レギュレーション・システム
- ▶ 医療機器
- ▶ 計量
- ▶ 照明およびビル制御
- ▶ 充電システム
- ▶ 工業用 IoT

障害保護 RS-485 トランシーバ / Fault Protected RS-485 Transceivers

Part Number	Max Data Rate	Duplex	Number of Nodes	Driver/Receiver Enable	ESD		Fail-Safe	Supply (V)	Max Temp (°C)	Packages
					HBM (kV)	IEC				
ADM3095E	2.5 Mbps	Half	256	•	±15	Level 4	Idle, open, short	3.0 to 5.5	125	16-lead SOIC
LT1785A	250 kbps	Half	128	•	±15	Level 4	Idle, open, short	4.75 to 5.25	125	8-lead SOIC, 8-lead PDIP
LT1791A	250 kbps	Full	128	•	±15	Level 4	Idle, open, short	4.75 to 5.25	125	14-lead SOIC, 14-lead PDIP
LTC2862A-1/ LTC2862A-2	20 Mbps/250 kbps	Half	224	•	±40	Level 4	Idle, open, short	3.0 to 5.5	125	8-lead SOIC, 8-lead DFN
LTC2863-1/ LTC2863-2	20 Mbps/250 kbps	Full	256	•	±15		Idle, open, short	3.0 to 5.5	125	8-lead SOIC, 8-lead DFN
LTC2864-1/ LTC2864-2	20 Mbps/250 kbps	Full	256	•	±15		Idle, open, short	3.0 to 5.5	125	14-lead SOIC, 10-lead DFN
LTC2865 ¹	20 Mbps/250 kbps	Full	256	•	±15		Idle, open, short	3.0 to 5.5	125	12-lead MSOP, 12-lead DFN
LTC2876	20 Mbps	Half	200	•	±52		Idle, open, short	3.0 to 5.5	125	8-lead MSOP, 8-lead DFN
LTC2877	20 Mbps	Half	200	•	±52		Idle, open, short	3.0 to 5.5, VL 1.65 to V _{CC}	125	10-lead MSOP, 10-lead DFN

3.3 V RS-485 トランシーバ / 3.3 V RS-485 Transceivers

Part Number	Max Data Rate	Duplex	Number of Nodes	Driver/Receiver Enable	ESD	Fail-Safe	Supply (V)	Max Temp (°C)	Packages
					HBM (kV)				
ADM3065E	50 Mbps	Half	128	•	±12	Idle, open, short	3.0 to 5.5	125	8-lead MSOP, 8-lead SOIC
ADM3070E	250 kbps	Full	256	•	±15	Idle, open, short	3.0 to 3.6	125	14-lead SOIC
ADM3071E	250 kbps	Full	256	•	±15	Idle, open, short	3.0 to 3.6	125	8-lead SOIC
ADM3072E	250 kbps	Half	256	•	±15	Idle, open, short	3.0 to 3.6	125	8-lead SOIC
ADM3073E	500 kbps	Half	256	•	±15	Idle, open, short	3.0 to 3.6	125	14-lead SOIC
ADM3074E	500 kbps	Full	256	•	±15	Idle, open, short	3.0 to 3.6	125	8-lead SOIC
ADM3075E ¹	500 kbps	Half	256	•	±15	Idle, open, short	3.0 to 3.6	125	8-lead SOIC
ADM3076E	16 Mbps	Full	256	•	±15	Idle, open, short	3.0 to 3.6	125	14-lead SOIC
ADM3077E	16 Mbps	Full	256	•	±15	Idle, open, short	3.0 to 3.6	125	8-lead SOIC
ADM3078E	16 Mbps	Half	256	•	±15	Idle, open, short	3.0 to 3.6	125	8-lead SOIC
ADM3483	250 kbps	Half	32	•	—	Open	3.0 to 3.6	85	8-lead SOIC
ADM3483E	250 kbps	Half	32	•	±15	Open	3.0 to 3.6	85	8-lead SOIC
ADM3485	10 Mbps	Half	32	•	—	Open	3.0 to 3.6	85	8-lead SOIC
ADM3485E	12 Mbps	Half	32	•	±15	Open	3.0 to 3.6	85	8-lead SOIC
ADM3486E	2.5 Mbps	Half	32	•	±15	Open	3.0 to 3.6	85	8-lead SOIC
ADM3488	250 kbps	Full	32	•	—	Open	3.0 to 3.6	85	8-lead SOIC
ADM3488E	250 kbps	Full	32	•	±15	Open	3.0 to 3.6	85	8-lead SOIC
ADM3490	10 Mbps	Full	32	•	—	Open	3.0 to 3.6	85	8-lead SOIC
ADM3490E	12 Mbps	Full	32	•	±15	Open	3.0 to 3.6	85	8-lead SOIC
ADM3491	10 Mbps	Full	32	•	—	Open	3.0 to 3.6	85	14-lead SOIC
ADM3491E	12 Mbps	Full	32	•	±15	Open	3.0 to 3.6	85	14-lead SOIC
ADM3493	250 kbps	Half	256	•	—	Open	3.0 to 3.6	85	8-lead SOIC
LTC1480	2.5 Mbps	Half	32	•	±3.5	Open	3.0 to 3.6	85	8-lead SOIC, 8-lead PDIP
LTC2850 ¹	20 Mbps	Half	256	•	±15	Idle, open, short	3.0 to 3.6	125	8-lead SOIC, 8-lead MSOP, 8-lead DFN
LTC2851	20 Mbps	Full	256	•	±15	Idle, open, short	3.0 to 3.6	125	8-lead SOIC, 8-lead MSOP, 8-lead DFN
LTC2852 ¹	20 Mbps	Full	256	•	±15	Idle, open, short	3.0 to 3.6	125	14-lead SOIC, 10-lead MSOP, 10-lead DFN
LTC2854 ¹	20 Mbps	Half	256	•	±25	Idle, open, short	3.0 to 3.6	125	10-lead DFN
LTC2855	20 Mbps	Full	256	•	±15	Idle, open, short	3.0 to 3.6	125	12-lead DFN, 16-lead SSOP_N

¹ 車載アプリケーション認定モデルが利用可能です。詳細については、製品ページをご参照ください。

5.0 V RS-485 トランシーバ / 5.0 V RS-485 Transceivers

Part Number	Max Data Rate	Duplex	Number of Nodes	Driver/Receiver Enable	ESD	Fail-Safe	Supply (V)	Max Temp (°C)	Packages
					HBM (kV)				
ADM1485	30 Mbps	Half	32	•	—	Open	4.75 to 5.25	85	8-lead SOIC, 8-lead MSOP, 8-lead PDIP
ADM1486	30 Mbps	Half	50	•	—	Open	4.75 to 5.25	85	8-lead SOIC
ADM1487E	2.5 Mbps	Half	128	•	±15	Open	4.75 to 5.25	85	8-lead SOIC
ADM1490E	16 Mbps	Full	32	•	±8	Open	4.75 to 5.25	85	8-lead MSOP, 8-lead SOIC
ADM1491E	16 Mbps	Full	32	•	±8	Open	4.75 to 5.25	85	14-lead SOIC, 10-lead MSOP
ADM3065E	50 Mbps	Half	128	•	±12	Idle, open, short	3.0 to 5.5	125	8-lead MSOP, 8-lead SOIC
ADM483	250 kbps	Half	32	•	—	Open	4.75 to 5.25	85	8-lead SOIC
ADM483E	250 kbps	Half	32	•	±15	Open	4.5 to 5.5	85	8-lead SOIC
ADM485	5 Mbps	Half	32	•	—	Open	4.75 to 5.25	85	8-lead SOIC, 8-lead MSOP, 8-lead PDIP
ADM4850	115 kbps	Half	256	•	—	Open, short	4.75 to 5.25	85	8-lead LFCSP, 8-lead SOIC, 8-lead MSOP
ADM4851	500 kbps	Half	256	•	—	Open, short	4.75 to 5.25	85	8-lead SOIC, 8-lead LFCSP
ADM4852	2.5 Mbps	Half	256	•	—	Open, short	4.75 to 5.25	85	8-lead SOIC, 8-lead MSOP, 8-pad LFCSP
ADM4853 ¹	10 Mbps	Half	256	•	—	Open, short	4.75 to 5.25	85	8-lead SOIC, 8-lead MSOP, 8-lead LFCSP
ADM4854	115 kbps	Full	256	•	—	Open, short	4.75 to 5.25	85	8-lead SOIC
ADM4855	500 kbps	Full	256	•	—	Open, short	4.75 to 5.25	85	8-lead SOIC
ADM4856	2.5 Mbps	Full	256	•	—	Open, short	4.75 to 5.25	85	8-lead SOIC
ADM4857	10 Mbps	Full	256	•	—	Open, short	4.75 to 5.25	85	8-lead SOIC
ADM485E	2.5 Mbps	Half	32	•	±15	Open	4.75 to 5.25	85	8-lead SOIC
ADM487E ¹	250 kbps	Half	128	•	±15	Open	4.75 to 5.25	85	8-lead SOIC
ADM488	250 kbps	Full	32	•	—	Open	4.5 to 5.5	85	8-lead SOIC, 8-lead PDIP
ADM488A	250 kbps	Full	32	•	—	Open	4.5 to 5.5	85	8-lead SOIC, 8-lead MSOP
ADM489	250 kbps	Full	32	•	—	Open	4.5 to 5.5	85	14-lead PDIP, 14-lead SOIC, 16-lead TSSOP
ADM489A	250 kbps	Full	32	•	—	Open	4.5 to 5.5	85	14-lead SOIC, 10-lead MSOP
LTC1481	2.5 Mbps	Half	32	•	±10	Open	4.75 to 5.25	85	8-lead SOIC, 8-lead PDIP
LTC1482	4 Mbps	Half	32	•	±15	Idle, open, short	4.75 to 5.25	85	8-lead MSOP, 8-lead PDIP, 8-lead SOIC
LTC1483	150 kbps	Half	32	•	±10	Open	4.75 to 5.25	85	8-lead SOIC, 8-lead DIP
LTC1484	4 Mbps	Half	32	•	±15	Idle, open, short	4.75 to 5.25	85	8-lead MSOP, 8-lead PDIP, 8-lead SOIC
LTC1485	10 Mbps	Half	32	•	±10	Open	4.75 to 5.25	85	8-lead SOIC, 8-lead PDIP
LTC1487	250 kbps	Half	256	•	±10	Open	4.75 to 5.25	70	8-lead SOIC, 8-lead PDIP
LTC1685	52 Mbps	Half	50	•	±4	Idle, open, short	4.75 to 5.25	85	8-lead SOIC
LTC1686	52 Mbps	Full	50	•	±4	Idle, open, short	4.75 to 5.25	85	8-lead SOIC
LTC1687	52 Mbps	Full	50	•	±4	Idle, open, short	4.75 to 5.25	85	14-lead SOIC
LTC1690	5 Mbps	Full	32	•	±15	Idle, open, short	4.75 to 5.25	85	8-lead MSOP, 8-lead SOIC, 8-lead PDIP

¹ 車載アプリケーション認定モデルが利用可能です。詳細については、製品ページをご参照ください。

5.0 V RS-485 トランシーバ(続き) / 5.0 V RS-485 Transceivers (Continued)

Part Number	Max Data Rate	Duplex	Number of Nodes	Driver/Receiver Enable	ESD	Fail-Safe	Supply (V)	Max Temp (°C)	Packages
					HBM (kV)				
LTC2856-1/ LTC2856-2	20 Mbps/250 kbps	Half	256	•	±15	Idle, open, short	4.5 to 5.5	125	8-lead MSOP, 8-lead DFN
LTC2857-1/ LTC2857-2	20 Mbps/250 kbps	Full	256		±15	Idle, open, short	4.5 to 5.5	125	8-lead MSOP, 8-lead DFN
LTC2858-1/ LTC2858-2	20 Mbps/250 kbps	Full	256	•	±15	Idle, open, short	4.5 to 5.5	125	10-lead MSOP, 10-lead DFN
LTC2859 ¹	20 Mbps/250 kbps	Half	256	•	±15	Idle, open, short	4.5 to 5.5	125	10-lead DFN
LTC2861	20 Mbps/250 kbps	Full	256	•	±15	Idle, open, short	4.5 to 5.5	85	12-lead DFN, 16-lead SSOP_N
LTC490	2.5 Mbps	Full	32		±2	Open	4.75 to 5.25	85	8-lead SOIC, 8-lead PDIP
LTC491	2.5 Mbps	Full	32	•	±2	Open	4.75 to 5.25	85	14-lead SOIC, 14-lead PDIP

デュアルおよびクワッド RS-485 ドライバとレシーバ / Dual and Quad RS-485 Drivers and Receivers

Part Number	Drivers	Receivers	Max Data Rate	Driver/Receiver Enable	ESD (kV)	Fail-Safe	Supply (V)	Max Temp (°C)	Packages
ADM4168	2	2	10 Mbps	•	±15	Open	4.5 to 5.5	85	16-lead TSSOP
LTC1518	0	4	52 Mbps	•	±4	Idle, open, short	4.75 to 5.25	85	16-lead SOIC
LTC1519	0	4	52 Mbps	•	±4	Idle, open, short	4.75 to 5.25	85	16-lead SOIC
LTC1520	0	4	50 Mbps	•	±4	—	4.75 to 5.25	70	16-lead SOIC
LTC1688	4	0	100 Mbps	•	±4	—	3.0 to 5.25	85	16-lead SOIC
LTC1689	4	0	100 Mbps	•	±4	—	3.0 to 5.25	85	16-lead SOIC
LTC486	4	0	10 Mbps	•	±2	—	4.75 to 5.25	85	16-lead SOIC_W, 16-lead PDIP
LTC487	4	0	10 Mbps	•	±2	—	4.75 to 5.25	85	16-lead SOIC_W, 16-lead PDIP
LTC488	0	4	10 Mbps	•	±2	Open	4.75 to 5.25	85	16-lead SOIC_W, 16-lead PDIP
LTC489	0	4	10 Mbps	•	±4	Open	4.75 to 5.25	85	16-lead SOIC_W, 16-lead PDIP

絶縁型 RS-485 トランシーバ / Isolated RS-485 Transceivers

Part Number	Insulation Rating (kV rms)	Full Duplex	Half Duplex	Max Data Rate	Integrated Isolated Power	Isolated Power Output	Integrated Transformer Driver	Power Supply (V)		Max Temp (°C)	Packages
								Logic Side	Bus Side		
ADM2481	2.5		•	500 kbps				3.0 to 5.0	4.75 to 5.25	85	16-lead SOIC_W
ADM2482E	2.5	•	•	16 Mbps			•	3.0 to 5.5	3.0 to 3.6	85	16-lead SOIC_W
ADM2483	2.5		•	500 kbps				2.7 to 5.5	4.75 to 5.25	85	16-lead SOIC_W
ADM2484E	5	•	•	500 kbps				3.0 to 5.5	3.0 to 3.6	85	16-lead SOIC_W
ADM2485	2.5		•	16 Mbps			•	2.7 to 5.5	4.75 to 5.25	85	16-lead SOIC_W
ADM2486	2.5		•	20 Mbps				2.7 to 5.5	4.75 to 5.25	85	16-lead SOIC_W
ADM2487E	2.5	•	•	500 kbps			•	3.0 to 5.5	3.0 to 3.6	85	16-lead SOIC_W
ADM2490E	5	•	•	16 Mbps				2.7 to 5.5	4.75 to 5.25	105	16-lead SOIC_W
ADM2491E	5	•	•	16 Mbps				3.0 to 5.5	4.5 to 5.5	85	16-lead SOIC_W
ADM2582E	2.5	•	•	16 Mbps	•			3.0 to 5.5		85	20-lead SOIC W
ADM2587E	2.5	•	•	500 kbps	•			3.0 to 5.5		85	20-lead SOIC W
ADM2682E	5	•	•	16 Mbps	•			3.0 to 5.5		85	16-lead SOIC_IC
ADM2687E	5	•	•	500 kbps	•			3.0 to 5.5		85	16-lead SOIC_IC
ADM2795E	5		•	2.5 Mbps				1.7 to 5.5	3.0 to 5.5	125	16-lead SOIC_W
LTC1535	2.5	•	•	250 kbps			•	4.5 to 5.5	4.5 to 7.5	85	28-lead SOIC
LTM2881-3 ²	2.5	•	•	20 Mbps	•	1 W (5 V)		3.0 to 3.6		105	32-ball BGA, 32-pad LGA
LTM2881-5 ²	2.5	•	•	20 Mbps	•	1 W (5 V)		4.5 to 5.5		105	32-ball BGA, 32-pad LGA
LTM2885 ²	6.5	•	•	20 Mbps	•	1 W (5 V)		4.5 to 5.5		105	42-ball BGA

¹ 車載アプリケーション認定モデルが利用可能です。詳細については、製品ページをご参照ください。² ロジック電源電圧範囲 (V_L または V₀) 1.6 V ~ 5.5 V

RS-232 トランシーバ / RS-232 Transceivers

Part Number	Drivers/Receivers	Data Rate	ESD (kV)	Driver Disable	Rx Active in Shutdown	Shutdown Mode	Supply (V)	Max Temp (°C)	Packages
AD7306	3/2	100 kbps					4.75 to 5.25	85	24-lead PDIP, 24-lead SOIC_W
ADM101E ¹	1/1	460 kbps	±15		1	•	4.5 to 5.5	85	10-lead MSOP
ADM1181A	2/2	230 kbps	±15				4.5 to 5.5	85	16-lead PDIP, 16-lead SOIC_W
ADM1385	2/2	460 kbps			2	•	3.0 to 3.6	85	20-lead SSOP
ADM202	2/2	120 kbps					4.5 to 5.5	70	16-lead PDIP, 16-lead SOIC_W, 16-lead SOIC
ADM202E	2/2	230 kbps	±15				4.5 to 5.5	85	16-lead SOIC, 16-lead PDIP, 16-lead TSSOP, 16-lead SOIC_W
ADM206	4/3	120 kbps			0	•	4.5 to 5.5	85	24-lead PDIP, 24-lead SSOP, 24-lead SOIC_W
ADM206E	4/3	230 kbps	±15		0	•	4.5 to 5.5	85	24-lead SOIC_W
ADM207	5/3	120 kbps					4.5 to 5.5	85	24-lead PDIP, 24-lead SOIC_W, 24-lead SSOP
ADM207E	5/3	230 kbps	±15				4.5 to 5.5	85	24-lead PDIP, 24-lead SSOP, 24-lead SOIC_W, 24-lead TSSOP
ADM208	4/4	120 kbps					4.5 to 5.5	85	24-lead PDIP, 24-lead SOIC_W, 24-lead SSOP
ADM208E	4/4	230 kbps	±15				4.5 to 5.5	85	24-lead PDIP, 24-lead SSOP, 24-lead TSSOP, 24-lead SOIC_W
ADM211	4/5	120 kbps			0	•	4.5 to 5.5	85	28-lead SOIC_W, 28-lead SSOP
ADM211E	4/5	230 kbps	±15		0	•	4.5 to 5.5	85	28-lead TSSOP, 28-lead SOIC_W, 28-lead SSOP
ADM213	4/5	120 kbps			2	•	4.5 to 5.5	85	28-lead SOIC_W, 28-lead SSOP
ADM213E	4/5	230 kbps	±15		2	•	4.5 to 5.5	85	28-lead SOIC_W, 28-lead SSOP, 28-lead TSSOP
ADM2209E	6/10	920 kbps	±15		2	•	3.15 to 13.2	85	38-lead TSSOP
ADM222	2/2	200 kbps			0	•	4.5 to 5.5	85	18-lead PDIP, 18-lead SOIC_W
ADM232A	2/2	200 kbps					4.5 to 5.5	85	16-lead SOIC, 16-lead SOIC_W, 16-lead PDIP
ADM232L	2/2	120 kbps					4.5 to 5.5	85	16-lead SOIC_W, 16-lead PDIP
ADM233L	2/2	120 kbps					4.75 to 5.25	85	20-lead PDIP
ADM237L	5/3	120 kbps					4.75 to 5.25	85	24-lead PDIP, 24-lead SOIC_W
ADM238L	4/4	120 kbps					4.5 to 5.5	85	24-lead PDIP, 24-lead SOIC_W
ADM241L	4/5	120 kbps			0	•	4.5 to 5.5	85	28-lead SSOP, 28-lead SOIC_W
ADM242	2/2	200 kbps			2	•	4.5 to 5.5	85	18-lead PDIP, 18-lead SOIC_W
ADM3101E	1/1	460 kbps	±15				3.0 to 5.5	85	12-lead LFCSP_WQ, 16-lead QSOP
ADM3202	2/2	460 kbps	±15				3.0 to 5.5	85	16-lead SOIC_W, 16-lead SOIC, 16-lead TSSOP, 16-lead PDIP

¹ 車載アプリケーション認定モデルが利用可能です。詳細については、製品ページをご参照ください。

² ロジック電源電圧範囲 (V_L または V_{DD}) 1.6 V ~ 5.5 V

RS-232 トランシーバ(続き) / RS-232 Transceivers (Continued)

Part Number	Drivers/ Receivers	Data Rate	ESD (kV)	Driver Disable	Rx Active in Shutdown	Shutdown Mode	Supply (V)	Max Temp (°C)	Packages
ADM3222	2/2	460 kbps			2	•	3.0 to 3.6	85	18-lead PDIP, 20-lead SSOP, 20-lead TSSOP, 18-lead SOIC_W
ADM3232E	2/2	460 kbps	±15				3.0 to 5.5	85	16-lead SOIC, 16-lead SOIC_W, 16-lead TSSOP
ADM3307E	5/3	1 Mbps	±15		1	•	2.7 to 3.6	85	32-lead LFCSP, 28-lead TSSOP
ADM3310E	3/5	460 kbps	±15		2	•	2.7 to 3.6	85	32-lead LFCSP, 28-lead TSSOP
ADM3311E	3/5	460 kbps	±15		1	•	2.7 to 3.6	85	32-lead LFCSP, 28-lead SSOP, 28-lead TSSOP
ADM3312E	3/3	460 kbps	±15		1	•	2.7 to 3.6	85	32-lead LFCSP, 24-lead TSSOP
ADM3315E	3/3	460 kbps	±15		1	•	2.7 to 3.6	85	32-lead LFCSP, 24-lead TSSOP
ADM5170	8/0	116 kbps			0	•	9.0 to 15.0	85	28-lead PDIP, 28-lead PLCC
ADM560	4/5	116 kbps			2	•	3.0 to 3.6	70	28-lead SOIC_W, 28-lead SSOP
ADM561	4/5	116 kbps			0	•	3.0 to 3.6	70	28-lead SSOP, 28-lead SOIC_W
LT1032	4/0	250 kbps	±2			•	4.75 to 5.25	85	16-lead SOIC_W, 14-lead PDIP
LT1039A	3/3	250 kbps	±15		1	•	4.75 to 5.25	85	18-lead SOIC_W, 18-lead PDIP
LT1039A-16	3/3	250 kbps	±15				4.75 to 5.25	85	16-lead SOIC, 16-lead PDIP
LT1080	2/2	120 kbps	±2			•	4.5 to 5.5	85	18-lead SOIC_W, 18-lead PDIP
LT1081	2/2	120 kbps	±2				4.5 to 5.5	85	16-lead SOIC_W, 16-lead PDIP
LT1130A	5/5	250 kbps	±10				4.75 to 5.25	85	28-lead SOIC_W, 28-lead PDIP
LT1131A	5/4	250 kbps	±10	•		•	4.75 to 5.25	70	28-lead SOIC_W, 28-lead PDIP
LT1132A	5/3	250 kbps	±10				4.75 to 5.25	85	24-lead SOIC_W, 24-lead PDIP
LT1133A	3/5	250 kbps	±15				4.75 to 5.25	85	24-lead SOIC_W, 24-lead PDIP
LT1134A	4/4	250 kbps	±10				4.75 to 5.25	85	24-lead SOIC_W, 24-lead PDIP
LT1135A	5/3	250 kbps	±10				4.75 to 5.25	70	20-lead SOIC_W, 20-lead PDIP
LT1136A	4/5	250 kbps	±10	•		•	4.75 to 5.25	70	28-lead SOIC_W, 28-lead PDIP
LT1137A	3/5	250 kbps	±15	•		•	4.75 to 5.25	85	28-lead SSOP, 28-lead SOIC_W, 28-lead PDIP
LT1138A	5/3	250 kbps	±10	•		•	4.75 to 5.25	85	28-lead SSOP, 28-lead SOIC_W, 28-lead PDIP_W
LT1139A	4/4	250 kbps	±10			•	4.75 to 5.25	70	24-lead SOIC_W, 24-lead PDIP
LT1140A	5/3	250 kbps	±10	•		•	4.75 to 5.25	70	24-lead SOIC_W, 24-lead PDIP
LT1141A	3/5	250 kbps	±10	•		•	4.75 to 5.25	70	24-lead SOIC_W, 24-lead PDIP
LT1180A	2/2	250 kbps	±10			•	4.5 to 5.5	85	18-lead SOIC_W, 18-lead PDIP
LT1181A	2/2	250 kbps	±10				4.5 to 5.5	85	16-lead SOIC_W, 16-lead PDIP

RS-232 トランシーバ(続き) / RS-232 Transceivers (Continued)

Part Number	Drivers/ Receivers	Data Rate	ESD (kV)	Driver Disable	Rx Active in Shutdown	Shutdown Mode	Supply (V)	Max Temp (°C)	Packages
LT1237	3/5	250 kbps	±15	•	1	•	4.75 to 5.25	70	28-lead SSOP, 28-lead SOIC_W, 28-lead PDIP_W
LT1280A	2/2	250 kbps	±10			•	4.5 to 5.5	85	18-lead SOIC_W, 18-lead PDIP
LT1281A	2/2	250 kbps	±10				4.5 to 5.5	85	16-lead SOIC_W, 16-lead PDIP
LT1330	3/5	250 kbps	±10	•	1	•	V _{CC} 4.75 to 5.25, VL 3.0 to 5.0	70	28-lead SSOP, 28-lead SOIC_W, 28-lead PDIP_W
LT1331	3/5	250 kbps	±10	•	1	•	3.0 to 6.0	70	28-lead SSOP, 28-lead SOIC_W, 28-lead PDIP_W
LT1342	3/5	250 kbps	±10	•		•	V _{CC} 4.75 to 5.25, VL 3.0 to 5.0	70	28-lead SSOP, 28-lead SOIC_W, 28-lead PDIP_W
LT1381	2/2	250 kbps	±10				4.5 to 5.5	85	16-lead SOIC, 16-lead PDIP
LT1537	3/5	250 kbps	±5	•		•	4.75 to 5.25	70	28-lead SSOP, 28-lead SOIC_W
LT1780	2/2	250 kbps	±15			•	4.5 to 5.5	85	18-lead SOIC_W, 18-lead PDIP
LT1781	2/2	250 kbps	±15				4.5 to 5.5	85	16-lead SOIC, 16-lead SOIC_W, 16-lead PDIP
LTC1327	3/5	120 kbps	±10			•	3.0 to 3.6	70	28-lead SSOP, 28-lead SOL, 28-lead PDIP
LTC1337	3/5	120 kbps	±10			•	4.75 to 5.25	70	28-lead SSOP, 28-lead SOIC_W, 28-lead PDIP_W
LTC1338	5/3	120 kbps	±10	•		•	4.75 to 5.25	85	28-lead SSOP, 28-lead SOL, 28-lead PDIP
LTC1347	3/5	120 kbps	±10		5	•	4.75 to 5.25	70	28-lead SSOP, 28-lead SOIC_W, 28-lead PDIP_W
LTC1348	3/5	120 kbps	±10	•	5	•	3.0 to 5.5	85	28-lead SSOP, 28-lead SOIC_W
LTC1349	3/5	120 kbps	±10		2	•	4.75 to 5.25	85	28-lead SSOP, 28-lead SOIC_W, 28-lead PDIP_W
LTC1350	3/5	120 kbps	±10		2	•	3.0 to 3.6	85	28-lead SSOP, 28-lead SOIC_W, 28-lead PDIP_W
LTC1382	2/2	120 kbps	±10			•	4.5 to 5.5	85	18-lead SOIC_W, 18-lead PDIP
LTC1383	2/2	120 kbps	±10				4.5 to 5.5	85	16-lead SOIC, 16-lead PDIP
LTC1384	2/2	120 kbps	±10		2	•	4.5 to 5.5	85	20-lead SSOP, 18-lead PDIP, 18-lead SOIC_W
LTC1385	2/2	120 kbps	±10	•		•	3.0 to 3.6	85	20-lead SSOP, 18-lead SOIC_W, 18-lead PDIP
LTC1386	2/2	120 kbps	±10				3.0 to 3.6	85	16-lead SOIC
LTC2801	1/1	250 kbps	±10	•	1	•	1.8 to 5.5	85	12-lead DFN
LTC2802	1/1	1 Mbps	±10	•	1	•	1.8 to 5.5	85	12-lead DFN
LTC2803	2/2	250 kbps	±10	•	2	•	1.8 to 5.5	85	16-lead DFN
LTC2803-1	2/2	250 kbps	±10	•		•	1.8 to 5.5	85	16-lead SSOP_N
LTC2804	2/2	1 Mbps	±10	•	2	•	1.8 to 5.5	85	16-lead DFN
LTC2804-1	2/2	1 Mbps	±10	•		•	1.8 to 5.5	85	16-lead SSOP_N

絶縁型 RS-232 トランシーバ / Isolated RS-232 Transceivers

Part Number	Insulation Rating (kV rms)	ESD Protection (kV)	Max Data Rate (kbps)	Number Tx	Number Rx	Integrated Isolated Power	Isolated Power Output	Supply Voltage	Aux Channel (Mbps)	Max Temp (°C)	Packages
ADM3251E	2.5	15	460	1	1	•		4.5 to 5.5		85	20-lead SOIC_W
ADM3252E	2.5	15	460	2	2	•		3.0 to 5.5		85	44-ball BGA
LTM2882-3	2.5	10	1000	2	2	•	1 W (5 V)	3.0 to 3.6	10	105	32-ball BGA, 32-lead LGA
LTM2882-5	2.5	10	1000	2	2	•	1 W (5 V)	4.5 to 5.5	10	105	32-ball BGA, 32-lead LGA

マルチプロトコル・トランシーバ / Multiprotocol Transceivers

Part Number	Drivers/Receivers	Supported Data Rate				ESD (kV)	Termination	DCE or DTE	Signals	Additional Signals	Supply (V)	Max Temp (°C)	Packages
		RS-232/RS-562	RS-422/RS-485	V.35 (Async) (Mbps)	V.35 (Sync) (Mbps)								
LTC1321	2/2	120 kbps	10 Mbps			±10				4.75 to 5.25	85	24-lead SOL, 24-lead PDIP	
LTC1322	4/4	120 kbps	10 Mbps			±10				4.75 to 5.25	85	24-lead SOL, 24-lead PDIP	
LTC1323	2/3	120 kbps	2 Mbps			±10		Data, control		4.75 to 5.25	70	28-lead SSOP, 24-lead SO_W, 16-lead SO_N	
LTC1334	4/4	120 kbps	5 Mbps			±10				4.75 to 5.25	85	28-lead SSOP, 28-lead PDIP_W, 28-lead SO_W	
LTC1335	4/4	120 kbps	10 Mbps			±10				4.75 to 5.25	85	24-lead SOL, 24-lead PDIP	
LTC1343	4/4			8	4	±2		DTE or DCE	Data, clock, or control	LL, RL, TM	85	44-lead SSOP_W	
LTC1344						±2	•			4.75 to 5.25	85	24-lead SSOP	
LTC1344A						±2	•			4.75 to 5.25	85	24-lead SSOP	
LTC1345	3/3			10	5	±10		DTE or DCE	Data, clock		85	28-lead PDIP_W, 28-lead SO_W	
LTC1346A	3/3			10	5	±10		DTE or DCE	Data, clock		70	24-lead SO_W	
LTC1387	2/2	120 kbps	150 kbps/ 5 Mbps			±6				4.75 to 5.25	85	20-lead SSOP, 20-lead SO_W	
LTC1543	3/3	100 kbps	10 Mbps	10	5	±2		DTE or DCE	Data, clock		85	28-lead SSOP	
LTC1544	4/4	100 kbps	10 Mbps	10	5	±2		DTE or DCE	Control	LL	85	28-lead SSOP	
LTC1545	5/5	100 kbps	10 Mbps	10	5	±2		DTE or DCE	Control	LL, RL, TM	85	36-lead SSOP	
LTC1546	3/3	100 kbps	10 Mbps	10	5	±2	•	DTE or DCE	Data, clock		85	28-lead SSOP	
LTC2844	4/4	100 kbps	10 Mbps	10	5	±1		DTE or DCE	Control	LL	3.0 to 3.6/ 4.75 to 5.25	85	28-lead SSOP
LTC2845	5/5	100 kbps	10 Mbps	10	5	±1		DTE or DCE	Control	LL, RL, TM	3.0 to 3.6/ 4.75 to 5.25	85	36-lead SSOP, 38-lead QFN
LTC2846	3/3	100 kbps	10 Mbps	10	5	±2	•	DTE or DCE	Data, clock		3.0 to 3.6/ 4.75 to 5.25	85	36-lead SSOP
LTC2847	3/3	100 kbps	10 Mbps	10	5	±1	•	DTE or DCE	Data, clock		4.75 to 5.25	85	38-lead QFN
LTC2870	2/2	500 kbps	20 Mbps			±26	•	DTE or DCE			3.0 to 5.5, VL 1.7 to Vcc	85	28-lead QFN, 28-lead TSSOP
LTC2871	2/2	500 kbps	20 Mbps			±16	•	DTE or DCE			3.0 to 5.5, VL 1.7 to Vcc	85	38-lead QFN, 38-lead TSSOP
LTC2872	4/4	500 kbps	20 Mbps			±16	•	DTE or DCE			3.0 to 5.5, VL 1.7 to Vcc	85	38-lead QFN
LTC2873	1/1	1 Mbps/ 250 kbps	20 Mbps			±26	•	DTE or DCE			3.0 to 5.5	125	24-lead QFN

LVDS(低電圧差動信号)ドライバ/レシーバ / LVDS Drivers-Receivers (Low Voltage Differential Signaling)

Part Number	Max Data Rate (Mbps)	Drivers/Receivers	Fail-Safe	ESD (kV)	Voltage Supply (V)	Max Temp (°C)	Packages
ADN4661	600	1/0	Open, short	±15	3.0 to 3.6	85	8-lead SOIC
ADN4662	400	0/1	Open, short	±15	3.0 to 3.6	85	8-lead SOIC
ADN4663	600	2/0	Open, short	±15	3.0 to 3.6	85	8-lead SOIC
ADN4664	400	0/2	Open, short	±15	3.0 to 3.6	85	8-lead SOIC
ADN4665	400	4/0	Open, short	±15	3.0 to 3.6	85	16-lead TSSOP, 16-lead SOIC
ADN4666	400	0/4	Open, short	±8	3.0 to 3.6	85	16-lead SOIC, 16-lead TSSOP
ADN4667 ¹	400	4/0	Open, short	±15	3.0 to 3.6	85	16-lead TSSOP, 16-lead SOIC
ADN4668	400	0/4	Open, short	±15	3.0 to 3.6	85	16-lead SOIC, 16-lead TSSOP

M-LVDS(マルチポイント LVDS)トランシーバ / M-LVDS Transceivers (Multipoint Low Voltage Differential Signaling)

Part Number	Max Data Rate (Mbps)	Duplex	Number of Nodes	ESD (kV)	Interface Features	Shutdown	Voltage Supply (V)	Max Temp (°C)	Packages
ADN4690E	100	Half	32	±15	M-LVDS Rx Type 1	•	3.0 to 3.6	85	8-lead SOIC
ADN4691E	200	Half	32	±15	M-LVDS Rx Type 1	•	3.0 to 3.6	85	8-lead SOIC
ADN4692E	100	Full	32	±15	M-LVDS Rx Type 1	•	3.0 to 3.6	85	14-lead SOIC
ADN4693E	200	Full	32	±15	M-LVDS Rx Type 1	•	3.0 to 3.6	85	14-lead SOIC
ADN4694E	100	Half	32	±15	M-LVDS Rx Type 2	•	3.0 to 3.6	85	8-lead SOIC
ADN4695E	100	Full	32	±15	M-LVDS Rx Type 2	•	3.0 to 3.6	85	14-lead SOIC
ADN4696E	200	Half	32	±15	M-LVDS Rx Type 2	•	3.0 to 3.6	85	8-lead SOIC
ADN4697E	200	Full	32	±15	M-LVDS Rx Type 2	•	3.0 to 3.6	85	14-lead SOIC

LVDS アイソレータ / LVDS Isolators

Part Number	Max Data Rate (Mbps)	Max Prop Delay (ns)	Number of Channels	Inputs		Insulation Rating (kV rms)	Working Voltage (V rms/V peak)	Special Features	Max Temp (°C)	Packages
				Side 1	Side 2					
ADN4650	600	4.5	2	2	0	5	300/424	—	125	20-lead SOIC_W, 20-lead SSOP
ADN4651	600	4.5	2	1	1	5	300/424	Fail safe	125	20-lead SOIC_W, 20-lead SSOP
ADN4652	600	4.5	2	1	1	5	300/424	Fail safe	125	20-lead SOIC_W, 20-lead SSOP

コントローラ・エリア・ネットワーク(CAN)トランシーバ / Controller Area Network (CAN) Transceivers

Part Number	Max Data Rate (Mbps)	Number of Nodes	Fault Protection (V)	ESD (kV)	Common-Mode Voltage (V)	Voltage Supply (V)	Max Temp (°C)	Packages
ADM3051	1	110	±24	4	-7.0 to +12.0	4.5 to 5.5	125	8-lead SOIC
LT1796	0.125	256	±60	15 Level 4	-7.0 to +12.0	4.75 to 5.25	85	8-lead SOIC, 8-lead PDIP
LTC2875	4	166	±60	25	-36.0 to +36.0	3.0 to 3.6 or 4.5 to 5.5	125	8-lead SOIC, 8-lead DFN

絶縁型 CAN トランシーバ / Isolated CAN Transceivers

Part Number	Fault Protection (V)	Insulation Rating (kV rms)	High Voltage Bus Side Regulator	Max Data Rate (Mbps)	Integrated Isolated Power	Isolated Power Output	Power Supply (V)		Max Temp (°C)	Packages
							Logic Side	Bus Side		
ADM3052	±36	5	•	1	•		3.0 to 5.5	11 to 25	85	16-lead SOIC_W
ADM3053	±36	2.5		1	•		4.5 to 5.5		85	20-lead SOIC_W
ADM3054 ¹	±36	5		1			3.0 to 5.5	5	125	16-lead SOIC_W
LTM2889-3 ²	±60	2.5		4	•	0.75 W (adj 3 V to 5 V)	3.0 to 3.6		125	32-ball BGA
LTM2889-5 ²	±60	2.5		4	•	(adj 3 V to 5 V)	4.5 to 5.5		125	32-ball BGA

¹ 車載アプリケーション認定モデルが利用可能です。詳細については、製品ページをご参照ください。

² ロジック電源電圧範囲 (V_L または V₀) 1.6 V ~ 5.5 V

I²C バッファと立ち上がり時間アクセラレータ / I²C Buffers and Rise Time Accelerators

Part Number	Hot Swappable	Rise Time Accelerator	Bidirectional Level Translation (V)	Stuck Bus Disconnect/ Recovery	Enable	Ready	V _{CC2}	GPIO or Fault	HBM ESD (kV)	Bus Frequency	Max Temp (°C)	Packages
LTC4300A-1 ¹	•	•	2.7 to 5.5		•	•			±2	400	85	8-lead MSOP
LTC4300A-2 ¹	•	• ³	2.7 to 5.5				•		±2	400	85	8-lead MSOP
LTC4300A-3 ¹	•	•	2.7 to 5.5		•		•		±2	400	85	8-lead MSOP, 8-lead DFN
LTC4301 ¹	•		2.7 to 5.5		•	•			±10	400	85	8-lead MSOP, 8-lead DFN
LTC4301L ¹	•		1 to 2.7/5.5 ⁴		•	•			±10	400	85	8-lead MSOP, 8-lead DFN
LTC4302-1 ¹	•	• ³	2.7 to 5.5		•			•	±2	400	85	10-lead MSOP
LTC4302-2 ¹	•	• ³	2.7 to 5		•		•	•	±2	400	85	10-lead MSOP
LTC4303 ¹	•	•	2.7 to 5.5	•	•	•			±15	400	85	8-lead MSOP, 8-lead DFN
LTC4304 ¹	•	• ³	2.7 to 5.5	•	•	•		•	±15	400	85	10-lead MSOP, 10-lead DFN
LTC4307 ¹	•	•	2.7 to 5.5	•	•	•			±5	400	85	8-lead MSOP, 8-lead DFN
LTC4307-1 ¹	•		2.7 to 5.5		•	•			±5	400	85	8-lead MSOP, 8-lead DFN
LTC4308	•	•	1.8 to 2.3/5.5 ⁵	•	•	•			±6	400	85	8-lead MSOP, 8-lead DFN
LTC4309	•	• ²	1 to 2.3/5.5 ⁶	•	•	•	•	•	±6	400	85	16-lead SSOP_N, 12-lead DFN
LTC4310-1 ¹	•	•	3 to 5.5	•	•	•			±5	100	85	10-lead MSOP, 10-lead DFN
LTC4310-2 ¹	•	•	3 to 5.5	•	•	•			±5	400	85	10-lead MSOP, 10-lead DFN
LTC4311 ¹		•			•				±8	400	85	6-lead DFN, 6-lead SC70
LTC4313-1/ LTC4313-2	•	•	3.3 to 5.0	•	•	•			±4	400	85	8-lead MSOP, 8-lead DFN
LTC4313-3	•		1.5 to 5.5	•	•	•			±4	400	85	8-lead MSOP, 8-lead DFN
LTC4315 ¹	•	• ³	1.5 to 5.5	•	•	•	•	•	±4	400	85	12-lead MSOP, 12-lead DFN

I²C マルチプレクサとアドレス変換器 / I²C Multiplexers and Address Translators

Part Number	Mux	Data Rate (kHz)	Supply Voltage (V)	Bus Voltage (V)	Channel Select	Bus Buffer	Rise Time Accelerator Options	GPIO	Stuck Bus Circuitry	HBM ESD (kV)	Address Translation	Max Temp (°C)	Packages
LTC4305	1:2	400	2.7 to 5.5	2.2 to 5.5	I ² C bus	•	Strong/off		Disconnect	±10		85	16-lead DFN, 16-lead SSOP_N
LTC4306	1:4	400	2.7 to 5.5	2.2 to 5.5	I ² C bus	•	Strong/off	×2	Disconnect	±10		85	24-lead QFN, 24-lead SSOP
LTC4312 ¹	1:2	400	2.9 to 5.5	1.5 to 5.5	Enable pin	•	Strong/2 mA/off		Disconnect and recovery	±4		85	14-lead DFN, 16-lead MSOP
LTC4314 ¹	1:4	400	2.9 to 5.5	1.5 to 5.5	Enable pin	•	Strong/2 mA/off		Disconnect and recovery	±4		85	20-lead QFN, 20-lead SSOP_N
LTC4316	1:1	400	2.25 to 5.5	2.5 to 5.5	Enable pin				Timeout	±4	•	85	10-lead DFN, 10-lead MSOP
LTC4317	1:2	400	2.25 to 5.5	2.5 to 5.5	Enable pin				Timeout	±4	•	85	16-lead DFN
LTC4318	2× 1:1	400	2.25 to 5.5	2.5 to 5.5	Enable pin				Timeout	±4	•	85	20-lead QFN

¹ 車載アプリケーション認定モデルが利用可能です。詳細については、製品ページをご参照ください。

³ 立ち上がり時間アクセラレータ回路は無効化できません。

⁴ SCL_{IN} および SDA_{IN} 1 V まで、SDA_{OUT} 2.7 V ~ 5.5 V

⁵ SCL_{IN} および SDA_{IN} 1.8 V まで、SDA_{OUT} および SCL_{OUT} 2.3 V ~ 5.5 V

⁶ SCL_{IN} および SDA_{IN} 1 V まで、SDA_{OUT} および SCL_{OUT} 2.3 V ~ 5.5 V

I²C アイスレータ / I²C Isolators

Part Number	Insulation Rating (kV rms)	Power Supply (V)	Serial Data	Serial Clock	Max Frequency (kHz)	Integrated, Isolated Power	Isolated Power Output	Max Temp (°C)	Packages
ADM3260	2.5	3.0 to 5.5	Bidirectional	Bidirectional	1000	•		105	20-lead SSOP
ADuM1250 ¹	2.5	3.0 to 5.5	Bidirectional	Bidirectional	1000			125	8-lead SOIC
ADuM1251 ¹	2.5	3.0 to 5.5	Bidirectional	Unidirectional	1000			125	8-lead SOIC
ADuM2250 ¹	5	3.0 to 5.5	Bidirectional	Bidirectional	1000			105	16-lead SOIC_W, 16-lead SOIC_IC
ADuM2251 ¹	5	3.0 to 5.5	Bidirectional	Unidirectional	1000			105	16-lead SOIC_W, 16-lead SOIC_IC
LTM2883-3I ⁷	2.5	3.0 to 3.6	Bidirectional	Unidirectional	400	•	0.6 W (adj 3 V to 5 V, adj 12 V, adj -12 V)	105	32-ball BGA
LTM2883-5I ⁷	2.5	4.5 to 5.5	Bidirectional	Unidirectional	400	•	0.6 W (adj 3 V to 5 V, adj 12 V, adj -12 V)	105	32-ball BGA
LTM2886-3I ⁷	2.5	3.0 to 3.6	Bidirectional	Unidirectional	400	•	1 W (adj 3 V to 5 V, 5 V, -5 V)	125	32-ball BGA
LTM2886-5I ⁷	2.5	4.5 to 5.5	Bidirectional	Unidirectional	400	•	1 W (adj 3 V to 5 V, 5 V, -5 V)	125	32-ball BGA
LTM2887-3I ⁷	2.5	3.0 to 3.6	Bidirectional	Unidirectional	400	•	1 W (adj 1.8 V to 5 V, adj 0.6 V to 5 V)	125	32-ball BGA
LTM2887-5I ⁷	2.5	4.5 to 5.5	Bidirectional	Unidirectional	400	•	1 W (adj 1.8 V to 5 V, adj 0.6 V to 5 V)	125	32-ball BGA
LTM2892-I ⁷	3.5	3.0 to 5.5	Bidirectional	Unidirectional	400			125	24-ball BGA

IO リンク・トランシーバ / IO-Link Transceivers

Part Number	IO-Link Type	Drivers/Receivers	Max Data Rate (Mbps)	Supply Voltage (V)	Overvoltage Protection (V)	Load Current (mA)	LDO (mA)	Adj Slew	Wake-Up Pulse	L+ Hot Swap	Max Temp (°C)	Packages
LT3669	Device	1/1	0.23	7.5 to 40	±60	100	150				150	28-lead QFN
LT3669-2	Device	1/1	0.23	7.5 to 40	±60	300	150				150	28-lead QFN
LTC2874	Master	4/4	0.23	8.0 to 34.0, VL 2.9 to 5.5	±50			•	•	•	85	38-lead TSSOP

USB 2.0 アイスレータ / USB 2.0 Isolators

Part Number	Insulation Rating (kV rms)	Data Rate (Mbps)		Integrated Isolated Power	Isolated Power Output	ESD Protection (kV)	Max Temp (°C)	Packages
		Low Speed	Full Speed					
ADuM3160	2.5	1.5	12				105	16-lead SOIC_W
ADuM4160	5	1.5	12			10	105	16-lead SOIC_W, 16-lead SOIC_IC
LTM2884	2.5	1.5	12	•	2.5 W @ 5 V (V _{CC} = 8.6 V to 16.5 V) or 1 W @ 5 V (V _{CC} = 4.4 V to 8.6 V)	15	105	44-ball BGA
LTM2894	7.5	1.5	12			20	125	24-ball BGA

SPI デジタル・アイソレータ SPI Isolator® と絶縁型 SPI μModule / SPI Digital Isolators—SPI Isolator® or μModule Isolated SPI

Part Number	Product Feature	Power Supply (V)	Insulation Rating (kV rms)	No. Auxiliary Inputs		Slave Ports	Max SPI CLK Rate (MHz)	Integrated Isolated Power	Isolated Power Output	Max Temp (°C)	Packages
				Side 1	Side 2						
ADuM3150	High speed	3.0 to 5.5	3.75	1	1	1	40			125	20-lead SSOP
ADuM3151	Aux channels	3.0 to 5.5	3.75	2	1	1	17			125	20-lead SSOP
ADuM3152	Aux channels	3.0 to 5.5	3.75	1	2	1	17			125	20-lead SSOP
ADuM3153	Aux channels	3.0 to 5.5	3.75	0	3	1	17			125	20-lead SSOP
ADuM3154	Multiple slave support	3.0 to 5.5	3.75	0	0	4	17			125	20-lead SSOP
ADuM4150	High speed	3.0 to 5.5	5	1	1	1	40			125	20-lead SOIC_IC
ADuM4151	Aux channels	3.0 to 5.5	5	2	1	1	17			125	20-lead SOIC_IC
ADuM4152	Aux channels	3.0 to 5.5	5	1	2	1	17			125	20-lead SOIC_IC
ADuM4153	Aux channels	3.0 to 5.5	5	0	3	1	17			125	20-lead SOIC_IC

¹ 車載アプリケーション認定モデルが利用可能です。詳細については、製品ページをご参照ください。

⁷ ロジック電源電圧範囲 (V_L または V₀) 3 V ~ 5.5 V。LTM2883、LTM2887、LTM2892 には補助チャンネルが含まれます。

SPI デジタル・アイソレータ SPIsolator® と絶縁型 SPI μModule (続き) /
 SPI Digital Isolators—SPIsolator® or μModule Isolated SPI (Continued)

Part Number	Product Feature	Power Supply (V)	Insulation Rating (kV rms)	No. Auxiliary Inputs		Slave Ports	Max SPI CLK Rate (MHz)	Integrated Isolated Power	Isolated Power Output	Max Temp (°C)	Packages
				Side 1	Side 2						
ADuM4154	Multiple slave support	3.0 to 5.5	5	0	0	4	17			125	20-lead SOIC_IC
LTM2883-3S ²	Aux channels	3.0 to 3.6	2.5	0	2	1	8	•	0.6 W (adj 3 V to 5 V, adj 12 V, adj -12 V)	105	32-ball BGA
LTM2883-5S ²	Aux channels	4.5 to 5.5	2.5	0	2	1	8	•	0.6 W (adj 3 V to 5 V, adj 12 V, adj -12 V)	105	32-ball BGA
LTM2886-3S ²	Aux channels	3.0 to 3.6	2.5	0	2	1	8	•	1 W (adj 3 V to 5 V, 5 V, -5 V)	125	32-ball BGA
LTM2886-5S ²	Aux channels	4.5 to 5.5	2.5	0	2	1	8	•	1 W (adj 3 V to 5 V, 5 V, -5 V)	125	32-ball BGA
LTM2887-3S ²	Aux channels	3.0 to 3.6	2.5	0	2	1	8	•	1 W (adj 1.8 V to 5 V, adj 0.6 V to 5 V)	125	32-ball BGA
LTM2887-5S ²	Aux channels	4.5 to 5.5	2.5	0	2	1	8	•	1 W (adj 1.8 V to 5 V, adj 0.6 V to 5 V)	125	32-ball BGA
LTM2892-S ²	Aux channels	3.0 to 5.5	3.5	0	2	1	8			125	24-ball BGA
LTM2893 ²	ADC	3.0 to 5.5	6	0 to 3	0 to 3	2	100			125	36-ball BGA
LTM2895 ²	DAC	3.0 to 5.5	6	0 to 3.3	0 to 3	2	100			125	36-ball BGA

² ロジック電源電圧範囲 (V_L または V_{DD}) 1.6 V ~ 5.5 V

² ロジック電源電圧範囲 (V_L または V_{DD}) 1.71 V ~ 5.5 V

WHEN ANALOG DEVICES AND LINEAR TECHNOLOGY COMBINE ...

さらなるイノベーションの創出を可能に

アナログ・デバイスとリニアテクノロジーは統合し、最高峰のイノベーションを生み出し、お客様の戦略的パートナーとなります。

アナログ・デバイス株式会社

本社 〒105-6891 東京都港区海岸 1-16-1 ニューピア竹芝サウスタワービル 10F
 大阪営業所 〒532-0003 大阪府大阪市淀川区宮原 3-5-36 新大阪トラストタワー 10F
 名古屋営業所 〒451-6038 愛知県名古屋市中区牛島町 6-1 名古屋ルーセントタワー 38F



想像を超える可能性を
 AHEAD OF WHAT'S POSSIBLE™